



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 36096

Pneumatic piston pump s. 650 for distributing oil and similar, R 5:1 - 18 l/min with NBR seals and suction tube 940 mm with bung adaptor for 180÷220 kg drums

### AREAS OF USE

Aeronautics, Automotive, Building and road construction, Manufacturing industry, Lube trucks and transports, Railway transport

### FEATURES

Flow rate	18 l/min
Ratio	5:1
Compatible fluids	oils, lubricants and similar
Suction tube upper body	aluminum
Suction tube	carbon steel
Air inlet connection	G 1/4" (f)
Fluid outlet connection	G 1/2" (f)
Air working pressure	6 ÷ 8 bar
Average air consumption	350 l/min
Noise level	81 dB
max deliverable oil viscosity	SAE 240
Bung adaptor	p/n 38042
Suitable for drums or tanks	suitable for drums 180 ÷ 220 kg
Packing	No. 1 - 0,02 m3
Weight	6,8 kg



### OVERALL DIMENSIONS (mm)

