

CE **Made in Italy**
DESIGNED AND MANUFACTURED
AT **RAASM - ITALY**



technology, functionality, safety

Automotive Lubrication



Industrial Hose reels



Industrial Pumps



Catalogue No 219

1st January 2011



technology
functionality
safety

founded in 1975



RAASM

FLUIDS AND LUBRICATION EQUIPMENT





General view of RAASM Area in San Zeno di Cassola - Vicenza





RAASM branch in Romano d'Ezzelino - Vicenza



THE IMPORTANCE OF RESEARCH AND DEVELOPMENT





The starting point for the entire production cycle is the research and design of new solutions that will become cutting-edge products.





PRODUCTS DEVELOPED AND TESTED IN EVERY SINGLE DETAIL





A sophisticated testing room allows to check carefully the quality of the new products before introduce them in the market.





High precision dies developed in partnership with specialist companies, using cutting edge technology.

FULL ROBOTIZED WELDING





Welding quality is guaranteed by :

- the material used
- a high-tech robot
- an appropriate welding programme



- precise torch positioning
- control of temperature
- testing and a complete visual check of all welds on each product

...FOR THE HIGHEST QUALITY ALSO
IN PAINTING

The painting is guaranteed by innovative systems with lead and heavy metal-free non-toxic polyester resin for exteriors, with average thickness of 80 μ .

The painting is highly resistant to atmospheric agents and impacts.

The painted products undergo "saline mist resistance" corrosion testing according to UNI 9227 standards.



Computerised laser cutting enables the execution of complex work requiring extreme precision.



The excellence of the die-castings is ensured by the consistent quality of the castings obtained by means of computerised control of the presses and castings during the course of production.



Robotised injection moulding of components in thermoplastic material with subsequent structural inspection of the moulded pieces.





Turning, with state of the art machinery, as a result of continuing investment. Allowing the manufacture of complex components.



AN ALWAYS IN THE FOREFRONT REALITY





High precision instruments allow a careful control of the parts produced by evaluating their features: dimensions, hardness, roughness, etc.

CONTROL ROOM FOR BETTER QUALITY





A WAREHOUSE CONSTANTLY WELL-STOCKED
...to grant a fast and efficient spare parts
replacement service

Automated vertical store complete with
travelling lift for storage and handling
of material.

... a static structure for a dynamic system.
Control is carried out by means of company
management software, offering efficiency
and maximum flexibility.



MODULA

MODULA



SYSTEM
LOGISTICS

SYSTEM
LOGISTICS

RAASM

32



Pumps assembling with final control using a special software to verify pump's functionality.

EFFICIENT AND WELL ORGANIZED ASSEMBLY LINES





Careful packaging with special protections to avoid any damage during transport.





A WAREHOUSE CONSTANTLY WELL-STOCKED



Our inventory of finished products allows us to have the most popular items always available and ready to be shipped.



...to provide a fast and efficient order fulfillment

the packaging department prepares the products with packing materials suitable for specific protection requirements. This phase includes a final visual check of each article.



After a careful packaging, products are ready for shipment.



Technical and commercial brochures realized by qualified personnel.



TRAINING COURSE FOR CUSTOMERS AND DISTRIBUTORS

RAASM organizes refresher courses to improve the efficiency of our customer care service.






ONGOING TECHNICAL TRAINING FOR ALL RAASM STAFF




Automotive lubrication



A wide variety of products for lubrication in the automotive, industrial, agricultural, marine and other sectors.


Our products are designed to make work easier and quicker, according to the needs of our customers.

Industrial hose reels



RAASM hose reels enable safe and practical management of any type of hose for use with all types of fluids.

Industrial pumps



RAASM has created a wide range of industrial pumps to meet the most complex needs in application sectors such as industry, building, mining, shipyards, etc. This large range will certainly have the right pump for your application.




1 BRAKE BLEEDING - WASHING - INFLATING page **31**

2 WASTE OIL SUCTION/DRAINERS page **41**



3 MANUAL OIL AND GREASE PUMPS page **59**



4 OIL PUMPS FOR TRANSFERRING AND DISTRIBUTION page **67**




5 GREASE PUMPS AND ACCESSORIES page **115**



6 SERVICE COLUMNS page **133**



7 HOSE REELS AND ACCESSORIES page **143**



8 INDUSTRIAL PUMPS AND ACCESSORIES page **189**







AUTOMOTIVE LUBRICATION





FLUIDS AND LUBRICATION EQUIPMENT



Brake bleeding - washing - inflating

1



BRAKE - CLUTCH BLEEDING

page 32



PRESSURE SPRAYERS

page 36



WASHING TANK

page 37



TYRE INFLATOR

page 38




Brake-clutch bleeding equipment


with 2 chambers

with 3 chambers


The simplified air-operated two-chamber or three chamber, brake bleeding device is suitable for bleeding the hydraulic brakes and clutches of all motor vehicles. Bleeding can be carried out in a few minutes by just one person. The brake-bleeding device is equipped with an elastic inner membrane which hermetically separates the oil from the air, thus avoiding the risk of emulsion. It is also suitable for systems with braking control and ABS (max. at 1 bar).



Article		10105	10205	10207	10705	10805	10807
Tank capacity	litres	5	5	5	5	5	5
Set of plugs	Art.	-	11001	11004	-	11001	11004
clutch bleeding tube	Art.	-	10802	10802	-	10802	10802
2 collection containers	Art.	10801	10801	10801	10801	10801	10801
Filler funnel		yes	yes	yes	yes	yes	yes
Max working pressure	bar	2	2	2	2	2	2
Tank max pressure	bar	2	2	2	10	10	10
Delivery hose length	m	3	3	3	3	3	3
Safety valve	bar	3	3	3	10	10	10
Packing	N° - m ³	1 - 0,065	1 - 0,065	1 - 0,065	1 - 0,065	1 - 0,065	1 - 0,065
Weight	kg	8,5	9,5	9,7	10,2	11,2	11,4
Dimensions (A - B - C)	cm	43 - 25 - 65	65 - 43 - 25	43 - 25 - 65	45 - 25 - 65	45 - 25 - 65	45 - 25 - 65



Braking system
bleeding phase




Truck clutch system
bleeding phase



Brake bleeder operation


2 chambers operation



The brake-bleeding device is equipped with an elastic inner membrane (3) which hermetically separates the oil contained in the oil tank (1), from the air contained in the air "expansion" tank (2), thus avoiding the risk of emulsion (working pressure 1 - 2 bar controllable on the upper pressure gauge).

The oil tank (4) filler cap is equipped with a "reserve indicator" that signals when the fluid is finishing, and an air venting valve to be used in the device activation phase.

3 chambers operation



The brake-bleeding device is equipped with an elastic inner membrane (2) which hermetically separates the oil contained in the oil tank (1), from the air contained in the air "expansion" tank (5), thus avoiding the risk of emulsion. It is also equipped with a third air reserve tank (high pressure air 8-10 bar) (6) which, delivered by means of a pressure regulator (3), enables several bleeding operations to be carried out at a constant pressure without having to recharge the device.

The oil tank (4) filler cap is equipped with a "reserve indicator" that signals when the fluid is finishing, and an air venting valve to be used in the device activation phase.

Procedures for applying the connection plugs



Before bleeding it is important to fill the brake fluid reservoir by means of the brake bleeder quick-release connector.



The extended nozzle of the plug must be immersed in the fluid to avoid sprays or air and oil emulsions.



Connect the brake bleeding device to the reservoir by means of the quick-release connector.

LIST OF SCREW PLUGS FOR CARS

ALFA.....	A-D-L
AUDI.....	D
AUSTIN MORRIS.....	A-D-T
AUTOBIANCHI.....	B-H
BMW.....	D-W
CITROËN.....	D-E-I
CHRYSLER.....	W
DAEWOO.....	D-W
FERRARI.....	D-G-H
FIAT.....	A-B-D-H-I
FORD.....	A-D-T
HYUNDAI.....	W
INOCENTI.....	A-D-L
JAGUAR.....	L

JEEP.....	W
KIA.....	D
LAMBORGHINI.....	D-H-W
LADA.....	H
LANCIA.....	D-H
LAND ROVER.....	T-W
LEYLAND.....	A
MASERATI.....	D-G-L
MITSUBISHI.....	K-U
MAZDA.....	D-W
MERCEDES.....	D
MG.....	W
NISSAN.....	W
OPEL.....	D-F

PEUGEOT.....	D-F-M
PORSCHE.....	C-D
RENAULT.....	D-G-I-M
ROVER.....	A-D-W
SAAB.....	D
SEAT.....	D-H
SUBARU.....	U-W
SUZUKI.....	D-W
TALBOT.....	D-F
TOYOTA.....	W
TRIUMPH.....	T
VAUXHALL.....	A
VOLKSWAGEN.....	C-D
VOLVO.....	D-G-U

LIST OF SCREW PLUGS FOR TRUCKS

ASTRA.....	H
BEDFORD.....	A-G-L
BERLIET.....	D-F-T-X-Z
DAF.....	D

FIAT.....	A-B-D-F-H-I-P
FORD.....	D-G
IVECO.....	D-H-L
MERCEDES.....	D

RENAULT.....	D-F-I-X-Z
SCANIA.....	D-G
VOLVO.....	R

LIST OF PRESSURE PLUGS FOR CARS

HONDA.....	Art. 11003/4, /6
KIA.....	Art. 11003/5, /8
LEXUS.....	Art. 11003/1

MAZDA.....	Art. 11003/5, /9
OPEL.....	Art. 11003/3
ROVER.....	Art. 11003/6

SUZUKI.....	Art. 11003/7
LEXUS.....	Art. 11003/1
TOYOTA.....	Art. 11003/1, /2



Screw connection plugs



Art. 11001


Series of standard screw connection plugs, supplied with Art. 10205 or Art. 10805 (refer to page 32), consisting of:

- 5 screw plugs: 11000/A/D/F/I/T

- 1 universal plug 11000/W

Note: the above plugs can also be supplied individually. The universal plug 11000/W can be used on many types of cars and trucks in addition to those given in the plug list (refer to page 33)

Application examples of universal plug 11000/W








Art. 11002

Series of special screw connection plugs, consisting of: 11000/B/C/E/G/H/K/L/M/P/R/U/X/Y/Z

Note: the series of special plugs is only supplied by request

List of screw plugs supplyable individually

	Article	Plug series	Diameter (A) mm		Article	Plug series	Diameter (A) mm
	11000/A	type A	25		11000/M	type M	68,5
	11000/B	type B	21,5		11000/P	type P	77
	11000/C	type C	26,5		11000/R	type R	33,5
	11000/D	type D	43		11000/T	type T	44
	11000/E	type E	48		11000/U	type U	76
	11000/F	type F	52,5		11000/X	type X	44,5
	11000/G	type G	64		11000/Y	type Y	34,5
	11000/H	type H	41,5		11000/Z	type Z	58,5
	11000/I	type I	59		11000/W Universal plug W with 3 tapered plugs:		
	11000/K	type K	61,5				
	11000/L	type L	76,5				
						1) ø 20 mm	
						2) ø 28 mm	
						3) ø 45 mm	

Note: to choose the connection plug see the "Brake bleeder plug list" tables (refer to page 33)




Pressure connection plugs




Art. 11004

Adjustable universal bracket (Art.11003) with series of pressure plugs 11003/1/2/3/4/5/6/7/8/9

Application examples of universal pressure plugs



List of pressure plugs suppliable individually

	Article	Plug series	Diameter (A) mm	Article	Description
	11003/1	pressure	42,2 42,5		11003 Adjustable universal bracket for pressure plugs.
	11003/2	pressure	42,8		
	11003/3	pressure	53,8 54		
	11003/4	pressure	56		10801 Brake fluid collection containers, complete with transparent tube and 90° flexible attachment for connection to the bleeder valve.
	11003/5	pressure	65,7		
	11003/6	pressure	74,2		
	11003/7	pressure	58,8		10802 Clutch bleeding connection tube, length 600 mm.
	11003/8	pressure	33,7		
	11003/9	pressure	35,8		

Note: to choose the connection plug see the "Brake bleeder plug list" tables (refer to page 33)



Non-toxic pressure sprayers

Painted carbon steel

Stainless steel AISI 304

Devices for the **non-toxic spraying** of low viscosity detergent liquids, such as lubrication oils and similar. Suitable for washing motor vehicles, graphiting, lubricating, delivering dismantling oils, etc. Filled to 3/4 their capacity with the required liquid and pressurised with air at 6 - 8 bar, they work independently without requiring continuous connection to the compressed air line.



Art. 24891
Antisplash
funnel




Painted

Polished


Article		22017	22024	23024	23025
Tank capacity	litres	16	24	24	24
Delivery hose length	m	5	5	5	5
Max working pressure	bar	10	8	8	8
Gun length	m	0,65	0,65	0,65	0,65
Safety valve	bar	10	8	8	8
Level gauge		yes	yes	yes	yes
Spray gun	Art.	24805	24805	24806	24806
Spray nozzle	Art.	24801	24801	24801	24801
Antisplash funnel	Art.	24891	24891	24891	24891
Packing	N° - m³	1 - 0,080	1 - 0,090	1 - 0,090	1 - 0,090
Weight	kg	9,8	13	12,8	12,8
Dimensions (A - B - C)	cm	25,5 - 22,5 - 95	28 - 33 - 92	28 - 33 - 92	28 - 33 - 92

Caution: do not use with flammable or corrosive liquids

Attention: stainless steel pressure sprayers may also use aggressive fluids (such as some acid solutions) if only compatible with the materials composing the device



Spraying of detergent
for washing engines



Spraying antioxidant, oil, diesel oil
on mechanical parts




Washing tank

Universal washing tank for quick washing of mechanical parts and components in general.

The low-pressure pneumatic system enables:

- continuous liquid detergent flow with brush for thorough washing
- washing by dipping, with the parts dipped in the liquid detergent in the tank.



Art. 70809
Knurled
bristle
brush


Important: do not use corrosive liquids with flashpoint below 55°C, that can give off toxic and harmful fumes.
Use specific chemical products for washing mechanical parts, according to the instructions supplied by the manufacturer




Article		70365
Tank capacity	litres	65
Washing tank capacity	litres	50
Max working pressure	bar	0,5
Required quantity of liquid	litres	50
Max blowing gun pressure	bar	12
Knurled bristle brush	Art.	70809
Packing	N° - m³	2 - 0,290
Weight	kg	47,1
Dimensions (A - B - C)	cm	51 - 67 - 107




Details and advantages




For **correct use**, add **48 - 52 litres** of detergent liquid




The pneumatic systems works at low pressure **0,5 bar**, consuming very little air




Washing with brush, with continuous liquid flow



Dip washing, with parts placed in the tank



Brush or dip wash management unit



Decanting filter/screen



Portable tyre inflator

automatic
charging

standard
charging

Type-approved tyre inflator for checking and restoring the pressure of any type of tyre.

13 litres tank is available with standard or automatic charger, whereas **24 litres** tank is available only with standard charger.

Tyre pressure checking and inflation operations are carried out with the gun equipped with pressure gauge ø 60 mm with scale 0 - 10 bar.



Article		52013	52015	53016	52024	53024
Tank capacity	litres	13	13	13	24	24
Max tank pressure	bar	10	10	10	8	8
Calibrated safety valve	bar	10	10	10	8	8
Manometer ø 50 tank pressure	bar	0 - 10	0 - 10	0 - 10	0 - 10	0 - 10
Max working pressure	bar	7	7	7	7	7
Manometer working pressure		0 - 10 bar supplied with the inflating group	0 - 10 bar supplied with the inflating gun	0 - 10 bar supplied with the inflating gun	0 - 10 bar supplied with the inflating gun	0 - 10 bar supplied with the inflating gun
Working temperature	°C	-20° +60°	-20° +60°	-20° +60°	-20° +60°	-20° +60°
Inflating hose length	m	1,2	1,2	1,2	1,2	1,2
Inflating gun		with twin air valve	standard	standard	standard	standard
Automatic charger	Art.	52020	-	-	-	-
Packing	N° - m ³	1 - 0,088	1 - 0,088	1 - 0,088	1 - 0,090	1 - 0,090
Weight	kg	8,8	6,5	6,5	10	10
Dimensions (A - B - C)	cm	31 - 31 - 75	31 - 31 - 60	31 - 31 - 60	28 - 33 - 86	28 - 33 - 86

Note: type-approved for public use

Note: not type-approved for public use



Note: not type-approved for public use



Details and advantages

The tyre inflation and deflating operations are done with single 3-position lever


- ① idle
- ② deflation
- ③ inflation



Tyre pressure control and/or inflation operations are carried out with the inflating gun

INSTALLATION MEASURES for Art. 52013

In order to have the tyre inflator always ready for use, just place it on the automatic charger as shown in the illustration





The inflator hose reel

Inflation system with hose reel for checking and restoring the pressure of any type of tyre by means of the inflation gun equipped with pressure gauge ø 60 mm with scale 0 - 10 bar. Constant connection to the compressed air system makes the inflation system always ready for use. The hose reel is equipped with a system for quick hooking to the wall support to facilitate possible moving.




Art. 89001
Bayonet
hooking
support




type-
approved


Article		52010
Length tube	m	11
Length tube connection	m	1,5
Diameter of tube	mm	8 x 12
Inlet connection thread		M 1/4" G
Max working pressure	bar	10
Manometer ø 60 working pressure	bar	0 - 10
Working temperature	°C	-20° +60°
Packing	N° - m ³	1 - 0,019
Weight	kg	6,8
Dimensions (A - B - C)		31 - 11,5 - 39



Details and advantages



Pic. 1



Pic. 2

Pic. 1 The inflation hose reel is provided with a **wall bracket** with automatic bayonet hooking (Art. 89001) enabling **very quick and easy** installation or shifting.

The ease of this operation enables - also for safety reasons - the hose reel to be put away in a closed place at the end of the working day.

Also, the application of a wall support for every service point, either inside or outside, facilitates quick shifting and application of the hose reel in the workstation required by the operator.


Pic. 2 To prevent removal or theft of the hose reel it can be locked with a bolt or padlock.



FLUIDS AND LUBRICATION EQUIPMENT



Waste oil suction-drainers



SUCTION POWER

page 42



PROBES AND ACCESSORIES

page 44



WHEEL-MOUNTED - PORTABLE SUCTION-DRAINERS

page 45



SUCTION-DRAINERS

page 46



UNIVERSAL PANTOGRAPH SUCTION-DRAINERS

page 48



GRAVITY DRAINERS

page 51




SUCTION DRAINER-DISPENSERS WITH AIR-OPERATED PUMP page 54



Suction power

To understand the concept of **suction power** it is important to remember the difference between **pressure** and **depression**.


In this way the characteristics and advantages offered by the **oil drainer** will be clearly understood.




Pic. 1

Therefore, however, it is necessary to refer to the structure of the atmosphere that surrounds us and, above all, its barometric stratification and **compressibility**. Its lower layers, i.e. those nearest the ground, are more densely compressed than those higher up, precisely like what **happens with a pile of bags of compressible material**. (see Pic. 1).

The atmospheric pressure decreases as the altitude increases: at sea level it is 1 atm, at 2.000 metres a.s.l. it is approx. 0,8 atm, at 10.000 metres it falls to approx. 0,3 atm (see Pic. 2).



Pic. 2



In general, pressure is obtained by compressing any type of fluid inside a given container, until reaching the required values: 1 - 3 - 10 - 100 atm without limits, apart from those of the fluid container's structure and the power of the pump used.



On the other hand, a **depression** or vacuum is obtained by removing all the air contained in a given recipient or tank, and the maximum value obtainable (vacuum or suction power) is independent of the pumping or suction system used. Whatever the pump used (**electric pump, air pump, Venturi principle, etc.**) the maximum depression (or suction power) obtained is equal to the atmospheric pressure outside the suction system.

In fact, this value cannot be exceeded because, obviously, it is not possible to remove from a container more air than what it contains.

Pump operation with Venturi principle

Connect a compressed air line (7 atm) to the special connection on the suction device. Obligated to pass through a special "MULTIPLIER NOZZLE" of the Venturi unit, the air considerably increases in speed, creating "EDDIES" that can **suck** and "**pump**" all the air contained in the suction device tank, thus creating a complete vacuum.

Therefore the suction force generated by the **Venturi principle** is equal to that obtained with any other air-operated and/or electric pump.



For correct depressurisation, the pressure of the air passing through the Venturi system must be between **6,5 and 7 bar**.






Flexible and metal probes - Special connections

All the drainers used for changing engine oil come with a series of standard metal and flexible probes in addition to connections for engines with incorporated probes.

Standard probe series




Art. 45504
Art. 45505
Art. 45506
Art. 45516
Art. 45517
Art. 45518
Art. 45500
Art. 45501
Art. 45502

Art. 45560 consisting of:

- Art. 45504 flexible probe $\varnothing$ 5 mm - length 700 mm
- Art. 45505 rigid probe $\varnothing$ 5 mm - length 700 mm
- Art. 45506 flexible probe $\varnothing$ 6 mm - length 700 mm
- Art. 45516 rigid probe $\varnothing$ 6 mm - length 700 mm
- Art. 45517 flexible probe $\varnothing$ 7 mm - length 1000 mm
- Art. 45518 flexible probe $\varnothing$ 8 mm - length 700 mm
- Art. 45500 connection for incorporated probes Volkswagen
- Art. 45501 connection for incorporated probes BMW
- Art. 45502 connection for incorporated probes Citroen

Note: the probes can be supplied separately

Probes supplied by request




Art. 45515
Art. 45526
Art. 45527
Art. 45528
Art. 45538
Art. 45539
Art. 45540

Non-standard probes available by request. Specify for vehicles requiring a longer probe for draining the oil from the bottom of the sump.

- Art. 45515 flexible probe $\varnothing$ 5 mm - length 1000 mm
- Art. 45526 flexible probe $\varnothing$ 6 mm - length 1500 mm
- Art. 45527 flexible probe $\varnothing$ 7 mm - length 1500 mm
- Art. 45528 flexible probe $\varnothing$ 7 mm - length 2000 mm
- Art. 45538 flexible probe $\varnothing$ 8 mm - length 1500 mm for suction in trucks
- Art. 45539 flexible probe $\varnothing$ 8 mm - length 2000 mm
- Art. 45540 special flexible probe $\varnothing$ 12 mm - length 700 mm for quick suction.

Already supplied with the following articles:
Art. 45100 - 45110 - 45150 - 45180 - 45250 - 45280 - 43116 - 43190 - 42164 - 42215

Connectors for incorporated probes




- for Mercedes cars connect the quick-release connector A of the oil drainer directly to the probe incorporated in the engine.
- for JTD Fiat Group cars: Art. 45498
- for Audi cars: Art. 45499
- for Volkswagen cars: Art. 45500
- for BMW cars: Art. 45501
- for Citroen cars: Art. 45502



Art. 45570

Wall-mounted probe kit, a handy container for the longest and less-used probes, useful for avoiding having to carry them with the drainer



Art. 45550

3/8" connection for outboard engines supplied with the drainers for boating

Art. 45551

3/4" connection for inboard engines supplied with the drainers for boating







PORTABLE waste oil drainers

manual emptying

Air-operated drainers.

Ideal for quick engine oil change of any motor vehicle. The old oil is sucked from the engine by means of the probes supplied. After depressurisation the drainer works independently without requiring continuous connection to the compressed air system. **Suck hot oil at 70 - 80 °C.**




Article	portable	wheel-mounted
	43016	43024
Tank capacity litres	16	24
Max draining capacity litres	13	20
Air pressure for depressurisation bar	6,5 - 7	6,5 - 7
Depressurisation time min	1	1 - 1,5
Noise level dB	75	75
Suction speed l/min	1,5 - 2	1,5 - 2
Total suction capacity litres	9 - 10	15 - 16
Suction hose m	2	2
Set of probes Art.	45560	45560
Packing N° - m³	1 - 0,080	1 - 0,090
Weight kg	10,5	13,7
Dimensions (A - B - C) cm	25,5 - 22,5 - 84,5	28 - 33 - 86


Caution: do not suck brake fluids, fuels, flammable or corrosive liquids



Details and advantages



For correct depressurisation, the pressure of the air passing through the Venturi system must be between **6,5 and 7 bar**








PROFESSIONAL waste oil suction-drainers

gravity-drainers

Gravity and air operated suction drainers. Ideal for quick engine oil change of any motor vehicle. Waste oil can be collected by gravity, using the bowl mounted on the adjustable support, or by suction through the supplied probes. After depressurisation the drainer works independently without requiring continuous connection to the compressed air system. **Suck hot oil at 70 - 80 °C.**




central bowl

side bowl

Article		42065	42090	42115	42066	42091	42116
Tank capacity	litres	65	90	115	65	90	115
Max draining capacity	litres	52	75	97	52	75	97
Prechamber capacity	litres	-	-	-	-	-	-
Bowl capacity	litres	15	15	15	15	15	15
Air pressure for depressurisation	bar	-	-	-	-	-	-
Depressurisation time	min	-	-	-	-	-	-
Noise level	dB	-	-	-	-	-	-
Suction speed	l/min	-	-	-	-	-	-
Total suction capacity	litres	-	-	-	-	-	-
Discharging/suction hose	m	draining 2	draining 2	draining 2	draining 2	draining 2	draining 2
Max pressure for draining	bar	0,5	0,5	0,5	0,5	0,5	0,5
Set of probes	Art.	-	-	-	-	-	-
Packing	N° - m ³	2 - 0,270	2 - 0,300	2 - 0,420	2 - 0,270	2 - 0,300	2 - 0,420
Weight	kg	33	34	42	33	34	42
Dimensions (A - B - C)	cm	60-42-127	64-42-140	66-49-142	60-42-134	64-42-125	66-49-128
Ingombro max (D)	cm	178	190	192	175	170	173

To connect waste oil gravity and suction drainers to emptying kit see page 50




suction-drainers

combined drainers

											
standard			with prechamber			standard			with prechamber		
43060	43090	43114	43065	43091	43115	44060	44090	44115	44065	44091	44116
65	90	115	65	90	115	65	90	115	65	90	115
52	75	97	52	75	97	52	75	97	52	75	97
-	-	-	8	8	8	-	-	-	8	8	8
-	-	-	-	-	-	15	15	15	15	15	15
6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7	6,5 - 7
2	2,5 - 3	3 - 3,5	2	2,5 - 3	3 - 3,5	2	2,5 - 3	3 - 3,5	2	2,5 - 3	3 - 3,5
75	75	75	75	75	75	75	75	75	75	75	75
1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2
43 - 45	60 - 65	85 - 90	43 - 45	60 - 65	85 - 90	43 - 45	60 - 65	85 - 90	43 - 45	60 - 65	85 - 90
2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2
0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
45560	45560	45560	45560	45560	45560	45560	45560	45560	45560	45560	45560
2 - 0,230	2 - 0,250	2 - 0,420	2 - 0,230	2 - 0,225	2 - 0,420	3 - 0,330	3 - 0,360	3 - 0,460	3 - 0,330	3 - 0,360	3 - 0,460
26,9	31,4	42	32,9	36	43	34,6	38,2	43	38,2	42,1	50
60-42-86	64-42-100	66-49-102	60-42-128	64-42-140	66-49-142	62-42-134	62-42-138	66-49-170	60-42-153	62-42-166	66-49-168
-	-	-	-	-	-	175	188	190	175	188	190

Caution: do not suck brake fluids, fuels, flammable or corrosive liquids


Details and advantages



Removable oversize funnel

Antisplash screen

Adjustable bowl to increase operating range




Vacuum gauge for checking suction power

To activate air pressure must be **6,5/7 bar** (activation time from **2 to 3,5 min**)

Prechamber/ tank connection and oil draining cock

Transparent prechamber 8 litre with level indicator

2 m suction hose with probe connection.
Waste oil suction speed 1,5-2 l/min (oil 70°-80°C, with 6 mm probe)



2 m hose for draining tank with air







PANTOGRAPH waste oil suction-drainers

moto and cars

Air-operated combination suction-drainer (50 litre) with pantograph collection bowl and wheel-mounted 115 litre tank. Waste oil can be collected whether by gravity, using the recovering basin on the floor or in the upper position if vehicles are over car lift, or by suction through the supplied probes. After depressurisation the drainer works independently without requiring continuous connection to the compressed air system
Suck hot oil at 70 - 80 °C




suction-drainers

combination

Article	46064	46065
Tank capacity litres	65	65
Max draining capacity litres	52	52
Prechamber capacity litres	-	-
Bowl capacity litres	14	14
Air pressure for depressurisation bar	-	6,5 - 7
Depressurisation time min	-	2
Noise level dB	-	75
Suction speed l/min	-	1,5 - 2
Total suction capacity litres	-	43 - 45
Discharging/suction hose m	2	2/2
Max pressure for draining bar	0,5	0,5
Set of probes Art.	-	45560
Packing N° - m³	3 - 0,247	4 - 0,310
Weight kg	38,2	42,7
Dimensions (A - B - C) cm	57 - 49 - 100	57 - 49 - 100
Max dimensions (D) cm	200	200



Caution: do not suck brake fluids, fuels, flammable or corrosive liquids




cars

trucks




suction-drainers	combination	with prechamber	with collecting basin (50 litres)
46114	46115	46116	46215
115	115	115	115
97	97	97	97
-	-	8	-
14	14	14	50
-	6,5 - 7	6,5 - 7	6,5 - 7
-	3 - 3,5	3 - 3,5	3 - 3,5
-	75	75	75
-	1,5 - 2	1,5 - 2	1,5 - 2
-	85 - 90	85 - 90	85 - 90
2	2/2	2/2	2/2
0,5	0,5	0,5	0,5
-	45560	45560	45560
3 - 0,360	4 - 0,420	4 - 0,420	4 - 0,5
51	54	58	68
65 - 58 - 150	65 - 58 - 150	65 - 58 - 150	70 - 62 - 156
240	240	240	255

Details and advantages




Protection screen/filter splash guard and support base for filter



Tank with antisplash



To empty the tank with device already depressurised, open the bowl/tank connection cock and in a few seconds the oil will be sucked in the tank




The air pressure for correct depressurisation is between **6,5 and 7 bar**



Modular kit for TRANSFER or EMPTYING oil, waste oil and similar

Wall-mounted transfer kit. A practical solution for draining movable equipment, waste oil suction/drainers by means of connection with quick-coupling valve. Wall application enables connection to a fixed system for discharging the sucked liquid directly into the storage tank.




Art. 33134
Female quick coupler and nipple to connect pump suction hose with waste oil drainers. In their turn drainers must be equipped with male quick coupler.




Aticle with seals in	VITON		33125
Aticle with seals in	NBR	33550	
Ratio		1:1	1:1
Capacity	l/min	40	23
Pump	Art.	33/2011NHHV2	33070
Flexible suction tube 2 m	Art.	38026	38026
Air inlet flow regulator	Art.	37803	37803
Wall bracket	Art.	33590	33115
Packing	N° - m ³	1 - 0,030	1 - 0,029
Weight	Kg	14	8,4
Distance (A)	cm	150	150



1 Pit waste oil drainer




2 Floor waste oil drainer



3 Standard waste oil drainer

To connect waste oil drainers with above mentioned emptying kit it is necessary to mount a male quick coupler. Depending on the kind of waste oil drainers (standard, for pit or floor mounted) a different nipple must be used as shown in the examples (Pic. 1 - 2 - 3).



Art. 33134

Art. 33127

Art. 33118





Waste oil drainers for DRUM

15 litre adjustable bowl

Wheel-mounted waste oil drainers. Ideal for use with jerry cans, drums and containers of various sizes, up to 220 kg. Suitable for gravity draining of engine, gearbox and differential oil from all motor vehicles placed on an car lift or pit.





The height-adjustable **bowl** (15 litres) is mounted on a swivel joint that facilitates positioning.



		adjustable bowl	wheel-mounted	wheel-mounted
Article		42004	42050	42000
Trolley capacity	litres	-	20 - 60	180 - 220
trolley	Art.	-	80050	80200
Bowl capacity	litres	15	15	15
Antisplash screen		yes	yes	yes
Drum clamping ring		yes	yes	yes
Packing	N° - m³	1 - 0,350	2 - 0,120	2 - 0,150
Weight	kg	9	17	29
Dimensions (A - B - C)	cm	58 - 58 - 115	64 - 50 - 120	70 - 77 - 130
Max dimensions (D)	cm	115	180	180

Caution: do not use with flammable or corrosive liquids

Details and advantages







Waste oil pit drainer

Pit waste oil drainers.




Suitable for gravity draining of engine, gearbox and differential oil from all motor vehicles placed on a pit. Equipped with antisplash screen which can be used as a support for draining oil filters.



Article	42059	42060	42061	42062	42055	42056
Tank capacity litres	65	65	110	110	150	150
Wheels	adjustable carriage	adjustable carriage	adjustable carriage	adjustable carriage	adjustable carriage	adjustable carriage
Emptying	by suction	by gravity	by suction	by gravity	by suction	by gravity
Equipped with	quick-release connector	hose-holder ø 30	quick-release connector	hose-holder ø 30	quick-release connector	hose-holder ø 30
Packing N° - m ³	1 - 0,140	1 - 0,140	1 - 0,220	1 - 0,220	1 - 0,270	1 - 0,270
Weight kg	27,5	28	39,5	40	53,5	54
Dimensions (A - B - C) cm	51 - 66 - 22	51 - 66 - 22	63,5 - 79 - 26,4	63,5 - 79 - 26,4	63,5 - 79 - 35,7	63,5 - 79 - 35,7
Dimensions (D - E) cm	75 - 120	75 - 120	84 - 125	84 - 125	84 - 125	84 - 125

Caution: do not use with flammable or corrosive liquids

Antisplash screen





The drained oil can be transferred from the collection bowl to the storage tank by gravity or by using an emptying pump connected to the fixed system






Waste oil floor drainer

Wheel-mounted floor waste oil drainers. Suitable for gravity draining of engine, gearbox and differential oil from all motor vehicles. Equipped with antisplash screen which can be used as a support for draining oil filters.



Article	42069	42070	42072	42073	42075	42076
Tank capacity litres	50	50	95	95	150	150
Wheels	4 castors	4 castors	2 castors + 2 fixed	2 castors + 2 fixed	2 castors + 2 fixed	2 castors + 2 fixed
Emptying	by suction	by suction	by suction	pneumatic	by suction	pneumatic
Equipped with	quick-release connector	junction tube	quick-release connector	pump 33070	quick-release connector	pump 33/2011NHHV2
Packing N° - m ³	1 - 0,140	1 - 0,140	1 - 0,200	1 - 0,200	1 - 0,330	1 - 0,330
Weight kg	20,5	21	37,5	40	53	61
Dimensions (A - B - C) cm	63 - 66 - 23,5	63 - 66 - 23,5	72,5 - 99 - 20	72,5 - 99 - 20	74,2 - 99,6 - 29,5	74,2 - 99,6 - 29,5
Dimensions (D - E) cm	78	78	119,9	119,9	123,8	123,8

Caution: do not use with flammable or corrosive liquids



The drained oil can be transferred from the collection bowl to the storage tank by suction with the incorporated probe or by an emptying pump connected to the fixed system or mounted directly on the collection basin



Suction drainer with pump


wheel-mounted

oil, waste oil, antifreeze liquid
and similar products

Air pump operated fixed drainers.

They enable **draining** by means of the probes supplied. The air pump, equipped with special VITON seals, is particularly suitable for sucking and delivering fluids such as: various oils, old oil, antifreeze liquid, diesel oil and similar products.


Wall-mounting enables connection to a fixed system for draining the sucked liquid directly in the storage tank.



Article		for drums 30 - 60 kg	for drums 180 - 220 kg
Pump	Art.	45150	45180
Max air pressure	bar	33070/A	33070/A
Noise level	dB	6	6
Suitable for drums	kg	81	81
Length of suction hose	m	30 - 60	180 - 220
Length of draining hose	m	1/2" x 2	1/2" x 2
Suction speed	l/min	1/2" x 2	1/2" x 2
Trolley	Art.	1,5 - 2	1,5 - 2
Column	Art.	80050	80200
Wall bracket	Art.	-	-
Wall-mounted probe kit	Art.	-	-
Hose reels	Art.	-	-
Set of probes	Art.	45560	45560
Special probe	Art.	45540 ø 12	45540 ø 12
Packing	N° - m³	2 - 0,080	2 - 0,113
Weight	kg	19,5	32,1
Dimensions (A - B - C)	cm	100 - 50 - 64	87 - 76 - 67

Caution: do not suck any flammable or corrosive liquids



Overall dimensions



Details and advantages

For correct draining, the pump must operate slowly.

To adjust the working speed, operate the flow regulator, "metering" the inlet air feed.
Make sure the vacuum gauge indicator is always in the optimum position



wall-mounted




wall-mounted - suction hose **4 m**

wall-mounted - suction hose **10 m**



column-mounted - suction hose **10 m**

45100	45300	45110	45310	45111	45311
33070/A	33/2011NHHV2	33070/A	33/2011NHHV2	33070/A	33/2011NHHV2
6	6	6	6	6	6
81	75	81	75	81	75
wall-mounted	wall-mounted	wall-mounted	wall-mounted	wall-mounted	wall-mounted
1/2" x 4	1/2" x 4	1/2" x 10	1/2" x 10	1/2" x 10	1/2" x 10
1/2" x 4	1/2" x 4	1/2" x 4	1/2" x 4	1/2" x 4	1/2" x 4
1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2
-	-	-	-	-	-
-	-	-	-	39320	39320
33115	33590	33115	33590	33115	33590
45570	45570	45570	45570	45570	45570
		8430.401/AS	8430.401/AS	8430.401/AS	8430.401/AS
45560	45560	45560	45560	45560	45560
45540 ø 12	45540 ø 12	45540 ø 12	45540 ø 12	45540 ø 12	45540 ø 12
1 - 0,056	2 - 0,070	2 - 0,116	3 - 0,130	3 - 0,250	4 - 0,260
12,2	14	29,1	31	75	77
130 - 60 - 220	130 - 60 - 220	130 - 60 - 220	130 - 60 - 220	245 - 29 - 59	245 - 29 - 59

Overall dimensions



Connectors for engines with incorporated probe for faster suction of the waste oil





Suction drainer-dispensers for fuels

IN ACCORDANCE
WITH DIRECTIVE:
ATEX 94/9



Wheel-mounted air-operated suction systems, for the management of fuels.

The air pump, equipped with special VITON seals, is suitable for **sucking petrol or diesel oil** from any vehicle or motorcycle by means of the probes or connections supplied. The wheel-mounted drainer with pump is easy to handle, versatile. The system is equipped with an earth connection for discharging electrostatic current.



wall-mounted

wheel mounted for drums **30 - 60 kg**


wheel mounted for drums **180 - 220 kg**

Article		45200	45250	45280
Pump suction	Art.	-	33070/A	33070/A
Max pressure air to pump	bar	4	4	4
Noise level	dB	81	81	81
Suitable for drums	kg	-	50 - 60	180 - 220
Lenght of suction hose	m	-	2	2
Lenght of draining hose	m	-	2	2
Suction speed	l/min	5 - 10	5 - 10	5 - 10
Trolley	Art.	-	80050	80200
Wall bracket	Art.	33115	-	-
Set of probes	Art.	-	probe ø 8 - probe ø 12	probe ø 8 - probe ø 12
Connections for tubes ø 6 - 8 - 10	Art.	-	45290 - 45291 - 45292	45290 - 45291 - 45292
Earth connection 3 m		yes	yes	yes
Packing	N° - m³	1 - 0,015	2 - 0,080	2 - 0,113
Weight	kg	6,2	19,5	32,1
Dimensions (A - B - C)	cm	13,6 - 6,5 - 36	50 - 50 - 100	76 - 67 - 87

Details and advantages

For correct draining, the pump must operate slowly.

To adjust the working speed, operate the flow regulator, "metering" the inlet air feed. Make sure the vacuum gauge indicator is always in the optimum position



Art. 45290
Connection for
tube ø 6



Art. 45291
Connection for
tube ø 8




Art. 45292
Connection for
tube ø 10




Dual use

Draining phase



Draining occurs by means of one of the probes supplied. For fuels use the $\varnothing$ 12 mm flexible probe.
Note: connect to earth before use

Delivery phase of previously sucked liquid



Delivery of sucked liquids occurs by reversing the position of the tubes. Insert the suction tube in the container of previously sucked liquid. Insert the draining tube in the container (or tank) just emptied.
Note: connect to earth before use



FLUIDS AND LUBRICATION EQUIPMENT



Manual pumps for oil and grease

3



MANUAL OIL PUMPS

page 60



MANUAL OIL DISPENSERS

page 62



13 KG MANUAL GREASE PUMPS

page 63



HAND-OPERATED HIGH PRESSURE GREASE PUMPS

page 64



HAND-OPERATED GREASE TRANSFER PUMPS

page 65




Manual pumps oil and similar

single-
acting

double-
acting

Manual pump for oil and allied products. Single-acting and VITON seals. Double-acting and NBR seals. The telescopic suction tube enables direct application on containers of different capacities. Suitable for delivering low-viscosity oil.



Article with seals in	VITON	31200	31201	
Article with seals in	NBR			30200
Tank capacity	litres	-	-	-
Suitable for drums	kg	50 - 220	50 - 220	50 - 220
Delivery hose length	m	2	-	2
Suction tube length	m	0,7 - 1,04	0,7 - 1,04	0,7 - 1,04
Quantity delivered for complete cycle of the lever	g	240	240	220
Max oil density delivered	SAE	130	130	240
Drum clamping ring	Art.	-	-	38044
Trolley	Art.	-	-	-
Antisplash funnel	Art.	-	-	-
Packing	N° - m³	1 - 0,016	1 - 0,016	1 - 0,016
Weight	kg	4,2	4,0	4,4
Dimensions (A - B - C)	cm	5,7 - 5,7 - 138	5,7 - 5,7 - 138	3,8 - 3,8 - 115


Caution: do not use with flammable or corrosive liquids



Art. 24891



Antisplash funnel

With antisplash rim to prevent the liquid from spilling out when filling the tank



Art. 32713

Digital litre-counter
complete with
connection unions



double-acting

double-acting pump




30050	32016	32024	32065
-	16	24	65
30 - 60	-	-	-
2	2	2	2
0,7 - 1,04	-	-	-
220	220	220	220
240	240	240	240
38044	-	-	-
80050	-	-	-
-	24891	24891	24891
2 - 0,040	1 - 0,080	1 - 0,090	2 - 0,185
13,6	10,6	13,7	24
46 - 50 - 123	25,5 - 22,5 - 86	28 - 33 - 89	60 - 42 - 88


Single-action (Pic. 1) occurs when the pumping piston delivers the fluid only in the pumping lever downstroke



Double-action (Pic. 2) occurs when the pumping piston delivers the fluid in its upstroke and downstroke. Double-action delivers the fluid with a continuous and constant flow



Lever hooking variation table



Hooking position	Pumping shaft stroke	Compression ratio obtainable	Delivery capacity with complete cycle	Indication of types of oil that can be delivered according to the lever position
n°3	127 mm	1 : 2,2	220 g	SAE W 80/90
n°2	100 mm	1 : 3,6	170 g	SAE W 85/140
n°1	60 mm	1 : 6,9	100 g	SAE 240

The position of lever pivot can be varied (3 hookings) to adapt the pumping force to the viscosity of the oil used



Air-operated oil dispensers

portable

wheel-mounted

Air-operated oil dispensers

suitable for high-viscosity oil.
Filled with oil to 4/5 their capacity
and pressurised to 6 - 8 bar,
they work independently without
requiring connection to the
compressed air system.

The air-operated oil dispensers are
ideal for filling or topping-up engine,
gearbox, differential, hydraulic power
pack, reduction unit oil, etc.




Article		33016	33024
Tank capacity	litres	16	24
Working pressure	bar	6 - 8	6 - 8
Safety valve	bar	10	8
Delivery hose length	m	2	2
Gun hose length	m	0,27	0,27
Max oil density delivered	SAE	130	130
Antisplash funnel	Art.	24891	24891
Packing	N° - m³	1 - 0,080	1 - 0,090
Weight	kg	9,9	13,1
Dimensions (A - B - C)	cm	25,5 - 22,5 - 86	28 - 33 - 89

Caution: do not use with flammable or corrosive liquids

Art. 24891



Antisplash funnel.

With antisplash rim to prevent the
liquid from spilling out when filling
the tank



Art. 32713

Digital litre-counter kit with partial
and cumulative reading, complete
with connection unions.
Application between the pump and
delivery hose allows the quantity of oil
delivered to be controlled





Portable grease dispenser

manual

air operated

Portable and wheel-mounted or air operated manual grease pumps. Practical and functional, they can be used in all workplaces and enable quick, high-pressure greasing on any motor vehicle or mechanism.




They are equipped with a grease follower plate that protects the lubricant and ensures positive priming.



Article		68012	68113	68213
Tank capacity	kg	13	13	13
Delivery hose length	m	2,5 - 1/4"	2,5 - 1/4"	4 - 1/4"
Delivery hose	Art.	KR6802	KR6802	993.504
Max outlet pressure	bar	350/400	300/350	350/400
Capacity every 10 cycles of lever Pump	g	60	40	-
	Art.	-	-	62041
Compression ratio		-	-	50:1
Noise level	dB	-	-	81
Max working pressure	bar	-	-	8
Max air consumption	l/min	-	-	330
Capacity (free outlet 6 bar self-levelling grease at 20° C)	g/min	-	-	1000
Grease follower plate	Art.	yes	yes	yes
Grease coupler	Art.	66739	66739	66740
Nipple	Art.	-	-	66892
Grease gun	Art.	-	-	66888
Packing	N° - m ³	1 - 0,070	1 - 0,070	1 - 0,100
Weight	kg	10,4	14	16,7
Dimensions (A - B - C)	cm	34 - 24,5 - 71	52 - 34 - 84	30 - 34 - 84



Details and advantages











Manual grease pumps

high pressure **350 bar**

Portable lever-operated manual grease pumps. Practical and functional, they can be used in all workplaces, and in particular on rough ground such as in farming or building sites. They enable easy change of the grease container (drum or bucket) and quick greasing on any motor vehicle or mechanism. They are equipped with a grease follower plate that protects the lubricant and ensures positive priming.



Article		60280	60310	60311
Suitable for drums	kg	12 - 20	16 - 30	16 - 30
		from 240 to 280	from 260 to 300	from 270 to 330
For drums with external ø	mm			
Delivery hose length	m	2,5 - 1/4"	2,5 - 1/4"	2,5 - 1/4"
Max outlet pressure	bar	350/400	350/400	350/400
Capacity every 10 cycles of lever	g	60	60	60
Drum cover ø	mm	280	310	337
Grease follower plate ø	mm	265	310	310
Grease coupler	Art.	66739	66739	66739
Packing	N° - m³	1 - 0,022	1 - 0,022	1 - 0,036
Weight	kg	5,4	6,5	7,2
Dimensions (A - B - C)	cm	63 - 28 - 35	63 - 31 - 35	63 - 33,7 - 35






Manual grease pumps

low pressure transferring **20 bar**

Portable manual lever-operated grease transfer pumps.

Each cycle of the lever delivers 50 g of grease. Practical and handy, they are used for filling gearcases, casings, hand-operated grease guns. They enable easy changing of the grease container (drums or bucket) and are equipped with a grease follower plate that protects the lubricant and ensures positive priming.



Article		60410	60411
Suitable for drums	kg	16 - 30	16 - 30
		from 260 to 300	from 270 to 330
For drums with external ø	mm		
Delivery hose length	m	2 - 1/2"	2 - 1/2"
Max outlet pressure	bar	18/20	18/20
Capacity every 10 cycles of lever	g	500	500
Drum cover ø	mm	310	337
Grease follower plate ø	mm	310	310
Packing	N° - m ³	1 - 0,030	1 - 0,040
Weight	kg	6	6,7
Dimensions (A - B - C)	cm	78 - 31 - 35	78 - 33,7 - 35



Art. 60450

Female quick connector
complete with check valve,
1/4" F thread for filling central
greasing system.
Max pressure 350 bar





Art. 60451

Male quick connector
complete with check valve,
1/4" F thread for filling central
greasing system.
Max pressure 350 bar



Quick connect coupling




Filling central greasing system




Transfer in small drums



FLUIDS AND LUBRICATION EQUIPMENT



Oil pumps for transfer and distribution



EXAMPLE OF SYSTEM

page 68



OIL PUMPS FOR TRANSFER AND DISTRIBUTION

page 70



TROLLEY-MOUNTED - FIXED - MODULAR KITS

page 82



OIL BAR

page 92



DIGITAL METER - OIL HANDLE AND ACCESSORIES

page 94



Example of installation


All distribution lines, for oil, grease and similar products, must be prepared with tubing (in steel, rubber ...) for high pressures, and must be smooth and seamless, with connections possibly having an inside diameter greater than the tube itself so as not to create any constrictions.

The tubing for an oil line must be capable of withstanding a minimum working pressure of 60 bar.

For grease installation the tubing must withstand a minimum working pressure of 600 bar.

Air and water tubing may be welded. For water, non corrosive pipework is recommended with min. pressure rating 8 - 10 bar.

For compressed air, 18 - 20 bar minimum pressure rating is recommended.



OIL

MOTOR OIL MAIN LINE

Tube characteristics:

- 0 - 15 m minimum inside diameter 3/4" (ø 19 mm)
- 16 - 50 m minimum inside diameter 1" (ø 25 mm)
- 51 - 100 m minimum inside diameter 1.1/4" (ø 30 mm)
- 101 - 200 m minimum inside diameter 1.1/2" (ø 38 mm)

Discharge: minimum inside diameter 3/4" (ø 19 mm)


GEAR OIL MAIN LINE

Tube characteristics:

- 0 - 15 m minimum inside diameter 1" (ø 25 mm)
- 16 - 50 m minimum inside diameter 1.1/2" (ø 38 mm)
- 51 - 100 m minimum inside diameter 1.1/4" (ø 30 mm)
- 51 - 250 m minimum inside diameter 2" (ø 50 mm)

Discharge: minimum inside diameter 3/4" (ø 19 mm)

...in relation to the computerized control system of fluids and the managing of stock room, please refer to the specific catalogue **"FLUIDS CONTROL SYSTEM"**



GREASE - WATER - AIR

GREASE MAIN LINE

Tube characteristics:
0 - 200 m minimum inside diameter 1/2" (ø 15 mm)

Discharge: minimum inside diameter 3/8" (ø 10 mm)

AIR AND WATER MAIN LINE


Tube characteristics:
0 - 30 m minimum inside diameter 1" (ø 25 mm)
31 - 300 m minimum inside diameter 1.1/2" (ø 38 mm)

Discharge: minimum inside diameter 3/4" (ø 19 mm)



Air-operated pumps for TRANSFER

Ratio 1:1 Flow rate 35 l/min



HIGH FLOW RATE
SHORT DISTANCE



Air-operated pumps for short and medium-distance transfer.

Ideal for transferring low-medium viscosity fluids such as: oils, lubricants and similar products. The wall-mounted version of these pumps, mounted on wall or in a fixed position by means of the special accessories (refer to page 107), enables numerous uses through the application of modular extensions (refer to page 112).




series 500

Article with seals in NBR				
Article with seals in VITON	26090	26091	26093	26094
Article with seals in TEFLON				
Compatible fluids	Oils, lubricants and similar			
Suction tube upper body	Aluminium			
Suction tube	Carbon steel			
Air inlet connection	bsp	F 1/4" G	F 1/4" G	F 1/4" G
Fluid outlet connection	bsp	F 3/4" G	F 3/4" G	F 3/4" G
Air working pressure	bar	6 - 8	6 - 8	6 - 8
Average air consumption	l/min	250	250	250
Noise level	dB	81	81	81
Max deliverable oil viscosity	SAE	80	80	80
Bung adaptor	-	standard	standard	standard
Suitable for drums or tanks	modular	customisable 1"	suitable for drums 50-60 Kg	suitable for drums 180-220 Kg
Packing	N° - m³	1 - 0,010	1 - 0,010	1 - 0,020
Weight	Kg	5,5	6	7,2
Dimensions (A - B - C)	cm	33,2 - 20,8 - 5	33,2 - 16,8 - 5	33,2 - 74 - 5



Ratio 1:1 Flow rate 23 l/min

Ratio 1:1 Flow rate 40 l/min



series 600

serie 650

33080	33081	33082	33083			
33070	33071	33072	33073	33170	33172	33173
33060	33061	33094	33096	33160	33194	33196


Oils, lubricants and similar

Oils, lubricants and similar


Aluminium
Carbon steel

Aluminium
Carbon steel

F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G
F 1/2" G	F 1/2" G	F 1/2" G	F 1/2" G	F 3/4" G	F 3/4" G	F 3/4" G
6 - 8	6 - 8	6 - 8	6 - 8	6 - 8	6 - 8	6 - 8
230	230	230	230	370	370	370
81	81	81	81	81	81	81
80	80	80	80	130	130	130
-	standard	-	standard	-	-	standard



modular




customisable 1"




suitable for drums
180-220 Kg



suitable for drums
180-220 Kg



modular





suitable for drums
180-220 Kg



suitable for drums
180-220 Kg


1 - 0,006	1 - 0,006	1 - 0,020	1 - 0,020	1 - 0,010	1 - 0,020	1 - 0,020
4,3	5	6,2	6,3	5,3	7,3	7,4
35,5 - 0 - 0	35,5 - 22 - 4,2	35,5 - 94 - 4,2	35,5 - 94 - 4,2	50,5 - 0 - 0	50,5 - 94 - 4,2	50,5 - 94 - 4,2






Air-operated pumps for DISTRIBUTION




Ratio **3:1** Flow rate **20 l/min**





Air-operated pumps series 500 and 600 for medium distance distribution. Ideal for transferring low-medium viscosity fluids such as: oils, lubricants and similar products. Suitable for mobile unit or fixed installation. The wall-mounted version of these pumps, mounted on wall or in a fixed position by means of the special accessories (refer to page 107), enables numerous uses through the application of modular extensions (refer to page 112).







series 500

Article with seals in	NBR			
Article with seals in	NBR			
Article with seals in	VITON	35060	35061	35063
Compatible fluids		Oils, lubricants and similar		
Suction tube upper body		Aluminium		
Suction tube		Carbon steel		
Air inlet connection	bsp	F 1/4" G	F 1/4" G	F 1/4" G
Fluid outlet connection	bsp	F 1/2" G	F 1/2" G	F 1/2" G
Air working pressure	bar	4 - 8	4 - 8	4 - 8
Average air consumption	l/min	350	350	350
Noise level	dB	81	81	81
Max deliverable oil viscosity	SAE	130	130	130
Bung adaptor		-	standard	standard
Suitable for drums or tank		 modular	 customisable 1"	 tank
Packing	N° - m³	1 - 0,01	1 - 0,01	1 - 0,01
Weight	Kg	5,35	5,8	5,8
Dimensions (A - B - C)	cm	33,2 - 20 - 3,2	33,2 - 18,5 - 3,2	33,2 - 125 - 3,2





series 500		series 600					
		35160	35161	35163	35173	35194	
					35176	35196	
35076	35094						
Oils, lubricants and similar		Oils, lubricants and similar					
Aluminium		Aluminium					
Carbon steel		Carbon steel					
F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G
F 1/2" G	F 1/2" G	F 1/2" G	F 1/2" G	F 1/2" G	F 1/2" G	F 1/2" G	F 1/2" G
4 - 8	4 - 8	6 - 8	6 - 8	6 - 8	6 - 8	6 - 8	6 - 8
350	350	330	330	330	330	330	330
81	81	81	81	81	81	81	81
130	130	130	130	130	130	130	130
standard	standard	-	standard	standard	standard on 35176	standard on 35196	
							
suitable for drums 50-60 Kg	suitable for drums 180-220 Kg	modular	customisable 1"	tank	suitable for drums 50-60 Kg	suitable for drums 180-220 Kg	
1 - 0,01	1 - 0,01	1 - 0,01	1 - 0,01	1 - 0,02	1 - 0,020	1 - 0,020	
5,8	6,5	4,4	5,0	6,8	5,8	6,5	
33,2 - 74 - 3,2	33,2 - 94 - 3,2	28,5 - 28,5 - 4,2	28,5 - 22 - 4,2	28,5 - 125 - 4,2	28,5 - 74 - 4,2	28,5 - 94 - 4,2	





Air-operated pumps for DISTRIBUTION

Ratio **5:1** Flow rate **18 l/min**



**MEDIUM PRESSURE
MEDIUM-LONG DISTANCE**

Series 650 air-operated double-acting pumps for medium distance oil distribution. Ideal for also distributing high viscosity oil. The double action guarantees the delivery of a continuous and constant flow, ideal for all installations, excellent for centralised distribution systems. The wall-mounted version of these pumps, mounted on wall or in a fixed position by means of the special accessories (refer to page 107), enables numerous uses through the application of modular extensions (refer to page 112).

Article with seals in **NBR**

Article with seals in **NBR**

Compatible fluids

Suction tube upper body

Suction tube

Air inlet connection bsp

Fluid outlet connection bsp

Air working pressure bar

Average air consumption l/min

Noise level dB

Max deliverable oil viscosity SAE


Bung adaptor

Suitable for drums or tanks

Packing N° - m³

Weight Kg

Dimensions (A - B - C) cm



series 650

36060

36061

36063

Medium/high-viscosity oil

Aluminium

Carbon steel

F 1/4" G

F 1/4" G

F 1/4" G

F 1/2" G

F 1/2" G

F 1/2" G

6 - 8

6 - 8

6 - 8

350

350

350

81

81

81

240


240

240


-

standard


standard



modular



customisable 1"



tank

1 - 0,01

4,7

34,5 - 27 - 4,2

1 - 0,01

5,2

34,5 - 27 - 4,2

1 - 0,02

7,2

34,5 - 125 - 4,2

PUMP AIR
FEEDING
PRESSURE

A A

8 bar

116 psi

B B


6 bar

87 psi

C C

4 bar

58 psi




Advantages of double-action

There are many technical solutions for obtaining a reciprocating double-acting pump.



The double-action of RAASM pumps is obtained with solutions that have simplified the pump mechanism itself, ensuring that delivery of the fluid in both alternating movements (upstroke and downstroke) of the pump occurs only through the difference in volume between the diameters of the pumping piston (A) and the pump shaft (B).

On the **upstroke**, delivery is caused by the **pumping piston (A)**.

On the **downstroke** it is caused by the difference in **volume** between the diameter of the motor shaft (B) and the diameter of the pumping piston (A).



series 650	
36073	36094
36076	36096
Medium/high-viscosity oil	
Aluminium	
Carbon steel	
F 1/4" G	F 1/4" G
F 1/2" G	F 1/2" G
6 - 8	6 - 8
350	350
81	81
240	240
standard on 36076	standard on 36096
	
suitable for drums 50-60 Kg	suitable for drums 180-220 Kg
1 - 0,02	1 - 0,02
6,2	6,8
34,5 - 74 - 4,2	34,5 - 94 - 4,2




In addition to guaranteeing regular delivery of the fluid, this solution offers the further advantage of having fewer parts inside the pump. This means less wear plus greater and longer reliability.





Stainless steel AISI 304 pumps for TRANSFER

Ratio 1:1 Flow rate 30 l/min



Stainless steel AISI 304 air-operated pumps for short-medium distance transfer. Ideal for transferring low-medium viscosity fluids such as: antifreeze liquid, windshield washing liquid and chemical products.



series 600 INOX

Article with seals in	VITON	33360	33396	33300
Compatible fluids		Suitable for antifreeze and windshield washing liquid		
Suction tube lower body		Stainless steel AISI 304		
Suction tube		Stainless steel AISI 304		
Air inlet connection	bsp	F 1/4" G	F 1/4" G	-
Fluid outlet connection	bsp	F 1/2" G	F 1/2" G	-
Air working pressure	bar	6 - 8	6 - 8	-
Average air consumption	l/min	370	370	-
Noise level	dB	81	81	-
Max deliverable oil viscosity	SAE	50	50	-
Bung adaptor		-	standard	33434
Suitable for drums or tanks		 modular	 suitable for drums 180-220 Kg	 modular
Packing	N° - m ³	1 - 0,10	1 - 0,020	1 - 0,29
Weight	Kg	5,3	7,4	11,4
Dimensions (A - B - C)	cm	41 - 0 - 0	41 - 94 - 3,4	41 - 94 - 3,4

Art. 33440
Gun for antifreeze and windshield liquid applicable to kit Art. 33300 equipped with:
- inlet joint F 1/2"
- stainless steel rigid terminal with free outlet




PUMP AIR FEEDING PRESSURE

A A
8 bar
116 psi

B B
6 bar
87 psi

C C
4 bar
58 psi




Art. 33360

Art. 33115

Art. 33426

Art. 33427

Art. 33434






DIAPHRAGM Pumps

S. 340-AB

in aluminium

3/4" Ratio **1:1** Flow rate **70 l/min**



The transfer diaphragm pumps, specific for oil and similar products in die-cast aluminium, with high-quality components, ensure lasting and reliable operation even in extreme conditions. Ideal for transferring fluids even in the presence of suspended solids.





series **340-AB**

Article with membrane in **NBR High Nitrile**



Compatible fluids	Water, mineral-vegetable oils, diesel oil		
Pump material	Aluminium		
Ball valve material	Hytrel		
Air inlet connection	bsp F 3/8" G	F 3/8" G	F 3/8" G
Fluid inlet-outlet connection	bsp F 3/4" x F 3/4" G	suction tube ø 34 mm - F 3/4" G	suction tube ø 34 mm - F 3/4" G
Air working pressure	bar 2 - 6	2 - 6	2 - 6
Air max pressure	bar 8	8	8
Average air consumption	l/min 500	500	500
Noise level	dB 75	75	75
Fluid temperature	°C -10 +90	-10 +90	-10 +90
Max solids diameter	mm ø 1,5	ø 1,5	ø 1,5

Suitable for drums or tanks



Suction-delivery ball valve with spring


Packing	N° - m³	1 - 0,015	2 - 0,040	2 - 0,040
Weight	Kg	8	10	11
Dimensions (A - B - C)	cm	16 - 20 - 25,6	16 - 20 - 25,6	16 - 20 - 25,6
Suction tube length and ø	cm	-	94x3,4	124x3,4





DIAPHRAGM Pumps S. 1000-AB - 1140-AB

in aluminium



The transfer diaphragm pumps, specific for oil and similar products in die-cast aluminium, with high-quality components, ensure lasting and reliable operation even in extreme conditions. Ideal for transferring fluids even in the presence of suspended solids.

1" Ratio 1:1
Flow rate **170 l/min**

1.1/4" Ratio 1:1
Flow rate **200 l/min**



series **1000-AB**

33/2611NHHV2



series **1140-AB**

33/3011NHHV2

Article with membrane in **NBR High Nitrile**

Compatible fluids

Pump material

Ball valve material

Air inlet connection

bsp

Fluid inlet-outlet connection

bsp

Air working pressure

bar

Air max pressure

bar

Average air consumption

l/min

Noise level

dB

Fluid temperature

°C

Max solids diameter

mm

Suction-delivery ball valve
with spring

Packing



N° - m³

Weight



Kg

Dimensions (A - B - C)

cm

Water, mineral-vegetable oils,
diesel oil

Aluminium

Hytrel

F 3/8" G

F 1.1/4" x F 1" G

2 - 6

8

1200

75

-10 +90

ø 3



1 - 0,025

14

20 - 26 - 34,5

Water, mineral-vegetable oils,
diesel oil

Aluminium

Hytrel

F 3/4" G

F 1.1/4" x F 1.1/4" G

2 - 6

8

1400

75

-10 +90



ø 3



1 - 0,041

16


23,8 - 28,6 - 38,6






DIAPHRAGM Pumps S. 120-PB



in polypropylene



Diaphragm pumps are used in different kind of application. They can be installed on wall brackets, on trailers, on moving machines, on drums, on big reservoirs and in many other places. Ideal for transferring fluids even in the presence of suspended solids. Double inlet version is suitable to mix together two different kind of liquids i. e. water and antifreeze.




Article with membrane	NBR High Nitrile	2B3/16117NH22		2B8/16117NH22	
Article with membrane	PTFE	2B3/16117TT22		2B8/16117TT22	
Compatible fluids		Water, mineral-vegetable oils, diesel oil	Windshield washing liquid and antifreeze	Water, mineral-vegetable oils, diesel oil	Windshield washing liquid and antifreeze
Motor and inside flanges material		Aluminium	Aluminium	Aluminium	Aluminium
Wetted parts		Polypropylene	Polypropylene	Polypropylene	Polypropylene
Ball valve material		Hytrel	Teflon	Hytrel	Teflon
Air inlet connection	bsp	F 3/8" G	F 3/8" G	F 3/8" G	F 3/8" G
Fluid inlet-outlet connection	bsp	F 3/4" x F 1/2" G	F 3/4" x F 1/2" G	F 3/4" x F 1/2" G	F 3/4" x F 1/2" G
Air working pressure	bar	2 - 6	2 - 6	2 - 6	2 - 6
Air max pressure	bar	8	8	8	8
Average air consumption	l/min	400	400	400	400
Noise level	dB	75	75	75	75
Fluid temperature	°C	-10 +65	-10 +65	-10 +65	-10 +65
Max solids diameter	mm	ø 1,5	ø 1,5	ø 1,5	ø 1,5
Suction-delivery ball valve with spring					
Packing	N° - m ³	1 - 0,015	1 - 0,015	1 - 0,015	1 - 0,015
Weight	Kg	7,5	7,5	7	7
Dimensions (A - B - C)	cm	17,8 - 21,8 - 32,6	17,8 - 21,8 - 32,6	17,8 - 22 - 32,6	17,8 - 22 - 32,6





Air-operated pumps for DISTRIBUTION

Ratio **5:1** Flow rate **45 l/min**



Series 900 industrial air-operated double-acting pumps for distribution.

Suitable for transferring oils, lubricants and similar products also with very high viscosity. The double action guarantees the delivery of a continuous and constant flow, ideal for all needs. Particularly effective in systems equipped with several distribution points.



Article with seals in **PU**

Compatible fluids	
Suction tube upper body	
Suction tube	
Air inlet connection	bsp
Fluid outlet connection	bsp
Air max pressure	bar
Max air consumption 8 bar	m ³ /min
Noise level	dB

Suitable for drums or tanks

Packing	N° - m ³
Weight	Kg
Dimensions (A - B - C)	cm



series **900**

90C/51

Oils, lubricants and similar

Aluminium

Carbon steel

F 1 1/2"

F 3/4"

8

1,6

80




modular

1 - 0,040


12

43 - 23 - 6,2



Ratio **7:1** Flow rate **30 l/min**

Ratio **11:1** Flow rate **30 l/min**



series 900

series 900

90C/71

91C/71

92C/71

90C/111

91C/111

92C/111

Oils, lubricants and similar

Oils, lubricants and grease

Aluminium

Aluminium

Carbon steel

Carbon steel

F 1/2"
F 3/4"

F 1/2"
F 3/4"

F 1/2"
F 3/4"

F 1/2"
F 3/4"

F 1/2"
F 3/4"

F 1/4"
F 3/4"

8

8

8

8

8

8

1,6

1,6

1,6

1,7

1,7

1,7

80


80

80


80

80


80




modular




suitable for drums
180-220 Kg



tank



modular



suitable for drums
180-220 Kg



suitable for drums
50-60 Kg

1 - 0,040

11

43 - 27 - 5,3

1 - 0,070

13

43 - 94 - 5,3

1 - 0,080

15

43 - 126 - 5,3

1 - 0,040

11

43 - 27 - 4,5

1 - 0,070

16


43 - 94 - 4,5

1 - 0,070

15


43 - 74 - 4,5

PUMP AIR
FEEDING
PRESSURE
A **A**
8 bar
116 psi
B **B**
6 bar
87 psi
C **C**
4 bar
58 psi



KIND OF FLUID: SAE30 oil (ISO VG 100) - 20 °C

PUMP AIR
FEEDING
PRESSURE
A **A**
8 bar
116 psi
B **B**
6 bar
87 psi
C **C**
4 bar
58 psi



KIND OF FLUID: SAE30 oil (ISO VG 100) - 20 °C




Mobile oil DISPENSER unit




trolley super
for drums **180-220 kg**

Mobile oil dispenser unit.

The ideal combination for dispensing oil in any workplace. The very easy to handle trolley is equipped with a drum (180 - 220 kg) clamping device, adjustable side support for stowing accessories, wheel with brake. The unit comes with a handy hose reel with 10 m of hose, and digital hose end meter.



Article		35201	35200	37100	35209	35210	37150
Ratio		3:1	3:1	5:1	3:1	3:1	5:1
Flow rate	l/min	20	14	18	20	14	18
Pump	Art.	35094	35194	36094	35094	35194	36094
Trolley	Art.	80201	80201	80201	80201	80201	80201
Hose reel	Art.	8430.401	8430.401	8430.401	-	-	-
Bung adaptor	Art.	38046	38042	38042	38046	38042	38042
Nipple	Art.	38071	38071	38071	38071	38071	38071
Digital metering gun	Art.	37758	37758	37758	37758	37758	37758
Hose	Art.	996.302	996.302	996.302	996.304	996.304	996.304
Packing	N° - m³	4 - 0,210	4 - 0,210	4 - 0,210	3 - 0,176	3 - 0,176	3 - 0,176
Weight	kg	74	76	76	55	57	57
Dimensions (A - B - C) cm		93 - 81 - 143	93 - 81 - 138,5	93 - 81 - 144,5	93 - 81 - 143	93 - 81 - 138,5	93 - 81 - 144,5






trolley standard
for drums 180-220 kg

trolley light
for drums 180-220 kg



35198	35199	37099	35415	35425	37095	35219	35220	37200
3:1	3:1	5:1	3:1	3:1	5:1	3:1	3:1	5:1
20	14	18	20	14	18	20	14	18
35094	35194	36094	35094	35194	36094	35094	35194	36094
80210	80210	80210	80210	80210	80210	80200	80200	80200
8430.401	8430.401	8430.401	-	-	-	-	-	-
38046	38042	38042	38046	38042	38042	38046	38042	38042
38071	38071	38071	38071	38071	38071	38071	38071	38071
37758	37758	37758	37758	37758	37758	37758	37758	37758
996.302	996.302	996.302	996.304	996.304	996.304	996.304	996.304	996.304
4 - 0,28	4 - 0,28	4 - 0,28	3 - 0,246	3 - 0,246	3 - 0,246	3 - 0,121	3 - 0,121	3 - 0,121
54,6	56,1	56,2	35,8	37,3	37,4	33,3	33,3	34,1
90-77-133	90 - 77 - 128,5	90-77-134,5	90-77-133	90 - 77 - 128,5	90-77-134,5	67-77-138,5	67-77-132,5	67-77-139,5





Oil DISPENSER kit

with 65 l tank

Trolley-mounted oil dispenser kit.



The ideal combination for dispensing oil in any workplace.

The compact trolley has 2 fixed wheels and 2 castors that make it very easy to handle.


It is equipped with a pump support and is suitable for holding various types of containers (30 - 50 kg).



Article		35265	37650	35270	37670
Ratio		3:1	5:1	3:1	5:1
Flow rate	l/min	14	18	14	18
Pump	Art.	35173	36073	35173	36073
Nipple	Art.	38071	38071	38071	38071
Digital metering gun	Art.	37758	37758	38022	38022
Hose	Art.	996.304	996.304	996.304	996.304
Antisplash funnel	Art.	24891	24891	24891	24891
Trolley	Art.	-	-	-	-
Bung adaptor	Art.	-	-	-	-
Drum cover	Art.	-	-	-	-
Packing	N° - m³	3 - 0,230	3 - 0,230	3 - 0,230	3 - 0,230
Weight	kg	33	34	30,9	31,3
Dimensions (A - B - C) cm		60 - 60 - 145,5	60 - 60 - 145,5	60 - 60 - 145,5	60 - 60 - 145,5



Antisplash funnel.
With antisplash
rim to prevent
the liquid from
spilling out when
filling the tank.





35260	35250	37500	35249	35259	37499	35264	35254	37504
3:1	3:1	5:1	3:1	3:1	5:1	3:1	3:1	5:1
20	14	18	20	14	18	20	14	18
35076	35173	36073	35076	35173	36073	35076	35173	36073
38071	38071	38071	38071	38071	38071	38071	38071	38071
37758	37758	37758	37758	37758	37758	37758	37758	37758
996.304	996.304	996.304	996.304	996.304	996.304	996.304	996.304	996.304
-	-	-	-	-	-	-	-	-
80050	80050	80050	-	-	-	-	-	-
-	-	-	38046	38042	38042	38046	38042	38042
-	-	-	-	-	-	65138	65138	65138
3 - 0,085	3 - 0,085	3 - 0,085	2 - 0,044	2 - 0,041	2 - 0,041	3 - 0,087	3 - 0,084	3 - 0,084
20	20	20,5	14,7	17,1	17,3	19,2	21,6	21,8
46 - 50 - 145,5	46 - 50 - 145,5	46 - 50 - 145,5	3,2 - 3,2 - 107,2	4,2 - 4,2 - 102,5	4,2 - 4,2 - 108,5	40 - 40 - 107,2	40 - 40 - 102,5	40 - 40 - 108,5

Art. 38071

Art. 35173

Art. 35076

Art. 36073

Art. 37758


Art. 996.304

Art. 65138

Art. 38042

Art. 38046

Art. 80050




Engine oil filling up



Modular oil dispensing kit with hose reel

Oil dispensing system with pump applied on a drum or tank, equipped with open or enclosed swivelling hose reel series 420/440 and with digital metering gun. The kits are independent oil delivery station.


pump mounted on drum



Article		35275	37675	
Ratio		3:1	5:1	
Flow rate	l/min	14	18	
Pump	Art.	35194	36094	
Hose reel	Art.	8420.401	8420.401	
Bung adaptor	Art.	38042	38042	
Wall bracket	Art.	-	-	
Nipple	Art.	38071	38071	
Digital metering gun	Art.	37758	37758	
Flexible suction tube	Art.	-	-	
Rigid suction tube	Art.	-	-	
Drip-tray	Art.	88630	88630	
Packing	N° - m ³	4 - 0,128	4 - 0,128	
Weight	kg	30,1	31,1	
Dimensions (A - B - C)	cm	94 - 90 - 220	94 - 90 - 220	

Art. 88630 Modular drip-tray.

Equipped with hook for gun and removable drip-tray. Applied under the hose reel, it is a handy holder for the delivery gun. Essential for a clean and orderly workplace.





pump mounted on drum

wall mounted pump



35276	37676	35280	37680	35281	37679
3:1	5:1	3:1	5:1	3:1	5:1
14	18	14	18	14	18
35194	36094	35160	36060	35160	36060
8440.401	8440.401	8420.401	8420.401	8440.401	8440.401
38042	38042	38042	38042	38042	38042
-	-	38043	38043	38043	38043
38071	38071	38071	38071	38071	38071
37758	37758	37758	37758	37758	37758
-	-	38026	38026	38026	38026
-	-	38027	38027	38027	38027
88630	88630	88630	88630	88630	88630
4 - 0,130	4 - 0,130	4 - 0,130	4 - 0,130	4 - 0,135	4 - 0,135
37,1	38,1	38,5	39,5	45	45
94 - 90 - 220	94 - 90 - 220	170 - 90 - 220	170 - 90 - 220	170 - 90 - 220	170 - 90 - 220





Kit for DISPENSING from tank

**Oil dispensing kit from IBC tank,
equipped with wall mounted pump or
tank mounted pump.**


Kits with wall mounted pump can be
connected with centralized lube piping or
with an hose reel or a delivery hose.

They are equipped with the accessories
for air and oil connections.

Kits with tank mounted pump are provided
with hose reel and digital metering gun.



Note: the tank is not part of the kit

Article		35330	36330
Ratio		3:1	5:1
Flow rate	l/min	14	18
Pump	Art.	35160	36060
Pump support bracket	Art.	38043	38043
Support bracket drip-tray	Art.	-	-
Bung adaptor	Art.	33434	33434
Flexible suction tube	Art.	38026	38026
Rigid suction tube	Art.	38055	38055
Air hose connection	Art.	993.201	993.201
Oil hose connection	Art.	996.301	996.301
Cock	Art.	38210	38210
Nipple	Art.	38071	38071
Air regulator	Art.	37812	37812
Hose reel	Art.	-	-
Digital metering gun	Art.	-	-
Drip-tray	Art.	-	-
Packing	N° - m ³	2 - 0,040	2 - 0,040
Weight	kg	15	15
Support width (A)	cm	-	-







36340	36350	36610	36620
5:1	7:1	3:1	5:1
45	30	14	18
90C/51	90C/71	35163	36063
10/10	10/10	36602	36602
-	-	36604	36604
33434	33434	-	-
38026	38026	-	-
38055	38055	-	-
996.301	996.301	-	-
998.501	998.501	-	-
38211	38211	-	-
33119	33119	38071	38071
37817	37817	-	-
-	-	8430.401	8430.401
-	-	37758	37758
-	-	88630	88630
2 - 0,120	2 - 0,120	4 - 0,250	4 - 0,250
23	22	48	49
-	-	100	100




The possible solutions for equipping kits for tanks are many, due to the various shapes and sizes of the tanks (cube, rectangular, cylindrical) and the way in which the pump can be mounted (with suction tube dipped, connected to a cock on the bottom, etc.).

Therefore we recommend choosing the necessary components from among those indicated below, in order to make up the kit best suited to your needs.



Pump and hose reel supports available for personalized kit.





Modular kit for TRANSFER or EMPTYING oil, waste oil and similar

Wall-mounted transfer kit. A practical solution for draining movable equipment, waste oil suction/drainers by means of connection with quick-coupling valve. Wall application enables connection to a fixed system for discharging the sucked liquid directly into the storage tank.




Art. 33134
Female quick coupler and nipple to connect pump suction hose with waste oil drainers. In their turn drainers must be equipped with male quick coupler.


Article with seals in	VITON		33125
Article with seals in	NBR	33550	
Ratio		1:1	1:1
Flow rate	l/min	40	23
Pump	Art.	33/2011NHHV2	33070
Flexible suction tube 2 m	Art.	38026	38026
Air inlet flow regulator	Art.	37803	37803
Wall bracket	Art.	33590	33115
Packing	N° - m ³	1 - 0,030	1 - 0,029
Weight	Kg	14	8,4
Distance (A)	cm	150	150



1 Pit waste oil drainer




2 Floor waste oil drainer



3 Standard waste oil drainer

To connect waste oil drainers with above mentioned emptying kit it is necessary to mount a male quick coupler. Depending on the kind of waste oil drainers (standard, for pit or floor mounted) a different nipple must be used as shown in the examples (Pic. 1 - 2 - 3).






Modular TRANSFER kit

transfer kit

Oil dispensing system with wall mounted or drum mounted pump.
Kits with wall mounted pump can be connected with centralized lube piping or with an hose reel or a delivery hose. Kits with tank mounted pump are provided with hose reel and digital metering gun. The rigid suction tube can be lengthened by means of modular elements (refer to page 112 - 113) for adapting to the height of the tanks.



Article with seals in		VITON	35284			35290		
Article with seals in		NBR		35285	37685		35293	35296
Ratio			3:1	3:1	5:1	3:1	3:1	5:1
Flow rate		l/min	20	14	18	20	14	18
Pump	Art.		35060	35160	36060	35094	35194	36094
Delivery hose	Art.		-	-	-	996.304	996.304	996.304
Connection hose	Art.		-	-	-	993.201	993.201	993.201
Flexible suction tube	Art.		38026	38026	38026	-	-	-
Rigid suction tube	Art.		38027	38027	38027	-	-	-
Nipple	Art.		-	-	-	38071	38071	38071
Pressure regulator	Art.		-	-	-	37801	37801	37801
Digital metering gun	Art.		-	-	-	37758	37758	37758
Bung adaptor	Art.		38042	38042	38042	38046	38042	38042
Wall bracket	Art.		38047	38043	38043	-	-	-
Packing	 N° - m³		1 - 0,029	1 - 0,029	1 - 0,029	2 - 0,070	2 - 0,085	2 - 0,085
Weight	 Kg		11,4	11,4	11,9	14	13,5	13,5
Distance (A)		cm	150	150	150	-	-	-



Art. 36060

Art. 35060

Art. 35160

Art. 38027

The rigid suction tube can be lengthened by means of modular elements (refer to page 112 - 113) for adapting to the height of the tanks

Art. 38042

Art. 38026

Art. 38043

Art. 35194

Art. 35094

Art. 38071

Art. 36094

Art. 37801

Art. 993.201

Art. 38046

Art. 38042

Art. 996.304

Art. 37758



Oil BAR


wall-mounted

Oil bar ideal for dispensing engine oil, gear oil, antifreeze and similar liquids. It offers the availability of to 3 different types of oil. Quick and easy drawing of oil with possibility of controlling the quantity by means of the digital litre-counter available on request. Tap with double **valve** and **antisplash filter** to guarantee delivery while preventing sprays caused by possible air bubbles in the system. Closing is automatic when the lever is released. Equipped with an easy to clean, removable drip-catcher tray and sturdy support grid.



Article		37690	37689	37688	37691	37687	37686
Tap for oil bar	Art.	37692 x 1	37692 x 2	37692 x 3	37692 x 1	37692 x 2	37692 x 3
Digital litre-counter kit	Art.	-	-	-	37830 x 1	37830 x 2	37830 x 3
Packing	N° - m³	1 - 0,136	1 - 0,136	1 - 0,136	1 - 0,136	1 - 0,136	1 - 0,136
Weight	kg	23,8	25	26,2	25	26,5	28
Dimensions (A-B-C-D)cm		67-44-56-46	67-44-56-46	67-44-56-46	67-44-56-46	67-44-56-46	67-44-56-46

Note: a max of 3 taps and 3 digital litre-counter kits can be fitted on the oil bar



Kit feeding pump

Art. 37695


Kit with drum pump for feeding oil bar, equipped with:

- Art. 35194 pump
- **R 3:1 - 14 l/min**
- Art. 38042 bung adaptor
- Art. 996.304 hose 1/2" 4m
- elbow M 1/2" x M 1/2"
- nipple M 1/2" x F 1/2"

Art. 33501

Kit with drum pump for feeding oil bar, equipped with:


- Art. 33500 diaphragm pump
- **R 1:1 - 60 l/min**
- Art. 996.304 tube 1/2" 4m
- Art. 33118 nipple M 3/4" x M 1/2"
- elbow F 1/2" x M 1/2"
- nipple M 1/2" x F 1/2"



Example of installation


Example of installation with hose.

Example of installation of an oil bar with three service taps connected by hoses to the feeder pumps. This type of connection is only recommended for short distances. After the air is connected to the pump, by operating the tap handle, it will always be ready to use.



Example of installation to fixed system.

Example of installation to a fixed system with the oil bar connected to a centralized system by means of a 60 cm hose.






Drum oil BAR


Drum oil bar.
Ideal for dispensing oil
and antifreeze liquid.
The delivery tap is
connected directly to the
feed pump. Very compact,
it enables quick filling
of jugs or other small
containers.



Article		37697	37698
Ratio		3:1	3:1
Flow rate		14	14
Pump	Art.	35194	35194
Tap for oil bar	Art.	37683	37683
Drip-catcher tray	Art.	37699	-
Bung adaptor	Art.	38042	38042
Packing	IN° - m ³	2 - 0,034	2 - 0,025
Weight	kg	12	9,5
Dimensions (A-B-C) cm		28,5 - 94 - 4,2	28,5 - 94 - 4,2




Oil BAR ACCESSORIES




Art. 37692
Double valve tap
with antisplash
filter for oil bar inlet
connection
F 1/2" + M 3/4"


Note: both articles guarantee maximum delivery
while preventing sprays caused by possible
air bubbles in the system. Closing is automatic
upon releasing the lever




Art. 37683
Oil tap with pump
connection,
equipped with:
- Art. 37681 tap for
oil bar
- Art. 37682 pump
- oil bar tap
connection tube



Art. 37699
Drip-catcher
tray



Art. 37693
Kit for connecting
oil bar to
fixed system,
equipped with:
- Art. 996.301 tube
M 1/2" x F 1/2" - 1 m
- elbow
M 1/2" x F 1/2"
- nipple
M 1/2" x F 1/2"



Art. 37830
Digital litre-counter
kit for oil bar,
equipped with:
- Art. 37780
digital litre-counter
- connection unions
- connections
M 1/2" x F 1/2"



Art. 38102
2-litre jug

Art. 38105
5-litre jug

* articles not manufactured by us



DIGITAL Meter

Flow rate **35** l/min

Flow rate **70** l/min

Flow rate **40** l/min

RAASM's digital meters, besides gauging the liquid delivered, can show instant flow rates, provide a reset total and allow the setting of different units of measurement.

RAASM's digital meters are suitable for a wide variety of fluids, from low to medium to high viscosities, including lubricants, diesel fuel, antifreeze, window wash liquid and other fluids compatible with the material of the meter.




Not type-approved for public use

oil and similar products		oil and similar products		antifreeze and windshield washing liquid	
Article	37780	37781	37785		
Flow rate	l/min	35	70	40	
Compatible fluids	Oil and similar products, diesel fuel		Oil and similar products, diesel fuel		Antifreeze and windshield washing liquid
Body's material	Aluminium		Aluminium		oxidized aluminium
Gear's material	POM		POM		PVDF
Inlet	F 1/2" BSP		F 3/4" BSP		F 1/2" BSP
Outlet	F 1/2" BSP		F 3/4" BSP		F 1/2" BSP
Max operating pressure	bar		bar		bar
Burst pressure	bar		bar		bar
Accuracy	± 0,3 %		± 0,5 %		± 0,5 %
Net weight	kg		kg		kg
Packing	N° - m ³		N° - m ³		N° - m ³
Gross weight	kg		kg		kg
Dimensions (A - B - C) mm	94 - 90 - 55		94 - 92 - 77		94 - 90 - 55



TECHNICAL Features



PERFORMANCE

- Precision $\pm 0,3 \%$
- Repeatability 0,2 %
- Pressure loss $< 0,5$ bar at max. flow rate



Series 1/2" 30 TP



Series 1/2" 40 AL



Series 1/2" 40 AP

Series		1/2" 30 AT	1/2" 40 AL	1/2" 40 AP	1/2" 65 AP	3/4" 70 AP	3/4" 85 AP
Flow rate	l/min	30	40	40	65	70	85
Max pressure	bar	60	70	70	100	100	100
Inlet union		F 1/2" G	F 1/2" G	F 1/2" G	F 1/2" G	F 3/4" G	F 3/4" G
Seals		NBR	Viton	Viton	Viton	Viton	Viton



**Gun for oil
and similar**

Series 1/2" 65 AP



Series 3/4" 70 AP



Series 3/4" 85 AP





GUN for oil and similar Series 1/2" - 30TP

Art. 38023

Grip in technopolymer for oil gun

equipped with F 1/2" inlet swivel joint, filter, F 3/8" outlet



Art. 33120

Oil gun equipped with

F 1/2" inlet swivel joint, filter, high flow rate rigid terminal

Art. 37730

Oil gun with digital litre-counter

Art. 37780 equipped with

F 1/2" inlet swivel joint, filter, high flow rate rigid terminal



Art. 38024

Oil gun equipped with

F 1/2" inlet swivel joint, filter, rigid terminal and semiautomatic drip-catcher nozzle ø 16 mm

Art. 37729

Oil gun with digital litre-counter

Art. 37780 equipped with

F 1/2" inlet swivel joint, filter, rigid terminal and semiautomatic drip-catcher nozzle ø 16 mm



Art. 38025

Oil gun equipped with

F 1/2" inlet swivel joint, filter, flexible terminal and semiautomatic drip-catcher nozzle ø 16 mm



Art. 37728

Oil gun with digital litre-counter

Art. 37780 equipped with

F 1/2" inlet swivel joint, filter, flexible terminal and semiautomatic drip-catcher nozzle ø 16 mm





GUN

for oil and similar Series 1/2" - 40AL - 40AP

Art. 38020

Grip in aluminium for oil gun
equipped with
F 1/2" inlet swivel joint, filter, F 3/8" outlet

Art. 37740

Grip in aluminium for oil gun
equipped with
F 1/2" inlet swivel joint, filter, F 3/8" outlet,
lever locking button



lever locking button



Art. 33121

Oil gun equipped with
F 1/2" inlet swivel joint, filter, high flow rate rigid terminal

Art. 37743

Oil gun equipped with
F 1/2" inlet swivel joint, filter, high flow rate rigid terminal,
lever locking button

Art. 37760

Oil gun with digital litre-counter

Art. 37780 equipped with
F 1/2" inlet swivel joint, filter, high flow rate rigid terminal



Art. 38021

Oil gun equipped with
F 1/2" inlet swivel joint, filter, rigid terminal
and semiautomatic drip-catcher nozzle ø 16 mm

Art. 37742

Oil gun equipped with F 1/2" inlet swivel joint,
filter, rigid terminal, semiautomatic drip-catcher
nozzle ø 16 mm and lever locking button

Art. 37759

Oil gun with digital litre-counter

Art. 37780 equipped with F 1/2" inlet swivel joint,
filter, rigid terminal, semiautomatic drip-catcher nozzle ø 16 mm



Art. 38022

Oil gun equipped with
1/2" F inlet swivel joint, filter, flexible terminal
and semiautomatic drip-catcher nozzle ø 16 mm

Art. 37741

Oil gun equipped with
F 1/2" inlet swivel joint, filter, flexible terminal,
semiautomatic drip-catcher nozzle ø 16 mm and lever locking button



Art. 37758

Oil gun with digital litre-counter

Art. 37780 equipped with
F 1/2" inlet swivel joint, filter, flexible
terminal and semiautomatic drip-catcher nozzle ø 16 mm

Art. 37786

Oil gun with digital litre-counter

Art. 37780 equipped with F 1/2" inlet swivel joint, filter,
flexible terminal, semiautomatic drip-catcher nozzle ø 16 mm
and lever locking button






GUN for oil and similar Series 1/2" - 65AP

Art. 37750

Grip in aluminium for oil gun equipped with **F 1/2"** inlet swivel joint, filter, **F 1/2"**outlet and lever locking button



Art. 33140

High flow rate oil gun equipped with **F 1/2"** inlet swivel joint, filter, high flow rate rigid terminal and lever locking button




Art. 37796

High flow rate oil gun with digital litre-counter Art. 37780 equipped with **F 1/2"** inlet swivel joint, filter, high flow rate rigid terminal and lever locking button

Art. 37752

Oil gun equipped with **F 1/2"** inlet swivel joint, filter, rigid terminal, semiautomatic drip-catcher nozzle ø 21 mm and lever locking button




Art. 37795

Oil gun with digital litre-counter Art. 37780 equipped with **F 1/2"** inlet swivel joint, filter, rigid terminal, semiautomatic drip-catcher nozzle ø 21 mm and lever locking button

Art. 37751

Oil gun equipped with **F 1/2"** inlet swivel joint, filter, flexible terminal, semiautomatic drip-catcher nozzle ø 21 mm and lever locking button



Art. 37794

Oil gun with digital litre-counter Art. 37780 equipped with **F 1/2"** inlet swivel joint, filter, flexible terminal, semiautomatic drip-catcher nozzle ø 21 mm and lever locking button





GUN for oil and similar Series 3/4" - 70AP

Art. 37775

High delivery oil grip equipped with **F 3/4"** inlet swivel joint, filter, **F 1/2"** outlet and lever locking button



Coloured caps
supplied for
all the range

lever locking button



Art. 37778

High flow rate oil gun equipped with **F 3/4"** inlet swivel joint, filter, high flow rate rigid terminal and lever locking button

Art. 37799

High flow rate oil gun with digital litre-counter Art. 37781 equipped with **F 3/4"** inlet swivel joint, filter, high flow rate rigid terminal and lever locking button



Art. 37777

High flow rate oil gun equipped with **F 3/4"** inlet swivel joint, filter, rigid terminal 45°, semiautomatic drip-catcher nozzle ø 35 mm and lever locking button

Art. 37798

High flow rate oil gun with digital litre-counter Art. 37781 equipped with **F 3/4"** inlet swivel joint, filter, rigid terminal 45°, semiautomatic drip-catcher nozzle ø 35 mm and lever locking button



Art. 37776

High flow rate oil gun equipped with **F 3/4"** inlet swivel joint, filter, flexible terminal, semiautomatic drip-catcher nozzle ø 35 mm and lever locking button

Art. 37797

High flow rate oil gun with digital litre-counter Art. 377810 equipped with **F 3/4"** inlet swivel joint, filter, flexible terminal, semiautomatic drip-catcher nozzle ø 35 mm and lever locking button





GUN for oil and similar Series 3/4" - 85AP

Art. 33150

High delivery oil grip equipped with **F 3/4"** inlet swivel joint, filter, **F 3/4"** outlet and lever locking button

lever locking button

Art. 33153

High delivery oil gun grip equipped with **F 3/4"** inlet swivel joint, filter, lever locking button, rigid terminal with free outlet

Art. 33148

High delivery oil gun grip with digital litre-counter Art. 37781 equipped with **F 3/4"** inlet swivel joint, filter, lever locking button, rigid terminal with free outlet

Art. 33152

High delivery oil gun grip equipped with **F 3/4"** inlet swivel joint, filter, lever locking button, rigid terminal and drip-catcher nozzle ø 35 mm

Art. 33147

High delivery oil gun grip with digital litre-counter Art. 37781 equipped with **F 3/4"** inlet swivel joint, filter, lever locking button, rigid terminal and drip-catcher nozzle ø 35 mm

Art. 33151

High delivery oil gun grip equipped with **F 3/4"** inlet swivel joint, filter, lever locking button, flexible terminal and drip-catcher nozzle ø 35 mm

Art. 33146

High delivery oil gun grip with digital litre-counter Art. 37781 equipped with **F 3/4"** inlet swivel joint, filter, lever locking button, flexible terminal and drip-catcher nozzle ø 35 mm



GUN

for windshield washing liquid and antifreeze

Art. 37785

Digital meter for windshield washing liquid and antifreeze, inlet and outlet F 1/2" BSP



Antifreeze gun Series 1/2" - 40AL

Art. 37764

Antifreeze gun with digital litre-counter Art. 37785 equipped with F 1/2" inlet swivel joint, filter, high flow rate rigid terminal and lever locking button



Art. 37762

Antifreeze gun with digital litre-counter Art. 37785 equipped with F 1/2" inlet swivel joint, filter, flexible terminal and semiautomatic drip-catcher nozzle ø 16 mm



Windshield washing liquid gun Series 1/2" - 30TL

Art. 33440

Windshield washing liquid gun equipped with F 1/2" inlet swivel joint, filter, high flow rate rigid terminal




Art. 33441

Windshield washing liquid gun with digital litre-counter Art. 37785 equipped with F 1/2" inlet swivel joint, filter, high flow rate rigid terminal





Gun for oil and similar S. 1/2" - 30TP - 40AL - 40AP




Art. 38015
Semiautomatic
drip-catcher nozzle ø 10 mm



Art. 38016
Semiautomatic
drip-catcher nozzle ø 16 mm



Art. 38017
Semiautomatic
drip-catcher nozzle ø 8 mm



Art. 38010
Flexible terminal with
semiautomatic
drip-catcher nozzle ø 16 mm



Art. 38011
Rigid terminal with
semiautomatic
drip-catcher nozzle ø 16 mm



Art. 38013
Rigid terminal 45°
with semiautomatic drip-catcher
nozzle ø 16 mm



Art. 38012
High delivery rigid
terminal with free outlet ø 20 mm



Art. 38018
Curved semiautomatic
drip-catcher ø 8 mm



Art. 38014
Flexible terminal with
semiautomatic
curved-drip-catcher nozzle ø 8 mm



Art. 38023
Grip in technopolymer with
inlet swivel joint F 1/2"



Art. 38020
Grip in aluminium alloy
with inlet swivel
joint F 1/2"



Art. 37740
Grip in aluminium alloy
with F 1/2" inlet swivel joint
and lever locking button



Art. 38062
Swivel
joint for
oil gun,
M/F 1/2"

Gun for oil and similar Series 1/2" - 65AP




Art. 38034
Semiautomatic
drip-catcher nozzle ø 21 mm



Art. 38035
Semiautomatic
drip-catcher nozzle ø 27 mm



Art. 38029
Flexible terminal with
semiautomatic
drip-catcher nozzle ø 21 mm



Art. 38030
Rigid terminal with
semiautomatic
drip-catcher nozzle ø 21 mm



Art. 38031
Rigid terminal 45°
with semiautomatic
drip-catcher nozzle ø 21 mm



Art. 38032
High delivery rigid
terminal with free outlet ø 20 mm



Art. 37750
Grip in aluminium alloy
with inlet swivel joint F 1/2"
and lever locking button



Art. 38063
Swivel
joint for
oil gun,
M/F 1/2"



Gun for oil and similar Series 3/4" - 70AP - 85AP

Art. 38040
High delivery
semiautomatic
drip-catcher nozzle
ø 35 mm



Art. 38037
High delivery
flexible terminal
with semiautomatic
drip-catcher nozzle ø 35 mm



Art. 38038
High delivery rigid
terminal 45° with
semiautomatic drip-catcher
nozzle ø 35 mm



Art. 38039
High delivery rigid
terminal with
free outlet ø 26 mm



Art. 37775
Grip in aluminium alloy
with inlet swivel
joint F 3/4" and lever
locking button



Art. 33150
Grip in aluminium alloy
with inlet swivel
joint F 3/4" and level
locking button



Art. 38066
Swivel
joint for
oil gun,
M/F 3/4"



Art. 38065
Swivel joint for oil
gun, high delivery,
inlet M/F 3/4"




High delivery grip Series 3/4"


Example of used 3/4" oil gun with
quick coupler for tank refilling.



inlet filter



Inlet filter supplied with all our oil,
antifreeze, windshield liquid delivery gun.





Accessories

digital meters and volumetric guns



- Art. 37704**
Digital dispensing oil gun with preselection,
 equipped with:
- inlet swivel joint **F 1/2"**
 - adjustable rigid terminal
 - automatic closing nozzle $\varnothing$ 16 mm

* not type-approved for public use
 * articles not manufactured by us



- Art. 37701**
Mechanical litre-counter (weight 1 Kg) **for oil,**
 equipped with:
- connection **F 1/2" x F 1/2"**
 - indicator 0-10 litres

* not type-approved for public use
 * articles not manufactured by us



- Art. 37703**
Oil gun with mechanical litre-counter (Art. 37701),
 equipped with:
- inlet swivel joint **F 1/2"**
 - flexible terminal
 - semiautomatic nozzle $\varnothing$ 16 mm

* not type-approved for public use
 * articles not manufactured by us



- Art. 33122**
High delivery oil gun for transfer,
 equipped with:
- **F 3/4"** inlet swivel joint (max 8 bar)
 - rigid terminal with free outlet
- Ideal for high deliveries in transferring oil, waste oil and antifreeze liquid

Note: it is advisable to use it with hose 3/4" (Art. 997.505) and with pumps R 1:1 (max 8 bar)


* articles not manufactured by us



Accessories for oil pumps



Art. 38046
Bung adaptor
ø 32 mm, with double body
for pumps with suction tube,
series 500



Art. 33434
Bung adaptor
ø 34 mm, with double body
for pumps with suction tube,
series 600

Art. 38042
Bung adaptor
ø 42 mm, with double body
for pumps with suction tube,
series 600 e 650



Art. 38044
Bung adaptor
ø 38 mm, with double body
for pumps manual double
acting oil pumps



Art. 38051
Bung adaptor
ø 50 mm, for pumps
with suction tube,
series 500


Art. 10/14
Bung adaptor
ø 45 mm for industrial
pumps with suction tube,
series 900 e 1200

Art. 10/15
Bung adaptor
ø 53 mm for industrial
pumps with suction tube,
series 900 e 1200




Art. 38047
Wall bracket ø 32 mm
with double body
for wall-mounting of pumps,
series 500


Art. 38043
Wall bracket ø 42 mm
with double body
for wall-mounting of pumps,
series 600 and 650



Art. 38052
Wall bracket ø 50 mm
with clamping system
with screw for
wall-mounting
of pumps,
series 500





Art. 33115
Wall bracket in steel
for wall-mounting of
transfer pumps,
series 600 and 650




Art. 33590
**Wall bracket in painted
steel** for wall-mounting
of diaphragm pumps
1/2" and 3/4"

Art. 33591
**Wall bracket in painted
steel** for wall-mounting
of diaphragm pumps
1" and 1.1/4"



Art. 10/10
**Wall bracket in painted
steel** for wall-mounting
of integral and flanged
industrial pumps,
series 900 and 1200




Art. 10/11
**Wall bracket in
painted steel**
with dampers for
wall-mounting of
integral and flanged
industrial pumps,
series 900 and 1200




Accessories for oil pumps

Union F2"



Drum cover with 2" F union suitable for standard bung adaptor


- Art. **65160** Drum cover ø 600 mm (drums ø external 550 - 600 mm)
 Art. **65142** Drum cover ø 420 mm (drums ø external 370 - 420 mm)
 Art. **65138** Drum cover ø 385 mm (drums ø external 340 - 385 mm)



Art. **88630**

Modular drip-tray.

Equipped with hook for gun and removable drip-tray. Applied under the hose reel, it is a handy holder for the delivery gun. Essential for a clean and orderly workplace



*



Art. **33126**

Female quick connector

- thread F 3/4"G
- high pressure 250 bar



Art. **33127**

Male quick connector

- thread F 3/4"G
- high pressure 250 bar

* articles not manufactured by us

*



Art. **38069**

- 90° union
- 3/4" G - F/M

Art. **38070**

- 90° union
- 1/2" G - F/M

* articles not manufactured by us

*



- Art. **33106** Nipple M 3/4"NPT x F 3/4"G
- Art. **33107** Nipple M 3/4"G x F 1"NPT
- Art. **33108** Nipple M 1"G x F 3/4"NPT
- Art. **33109** Nipple M 1"G x F 1"NPT
- Art. **38075** Nipple M 1/2"G x F 1/2"NPT
- Art. **38076** Nipple M 1/2"NPT x F 1/2"G
- Art. **38077** Nipple M 3/8"NPT x F 3/8"G
- Art. **38078** Nipple M 3/8"G x F 3/8"NPT
- Art. **38079** Nipple M 1/2"NPT x M 3/8"NPT
- Art. **33111** Nipple M 1.1/4"G x F 1.1/4"NPT
- Art. **33112** Nipple M 3/4"G x F 3/4"NPT
- Art. **33113** Nipple M 1/2"G x F 3/4"NPT

* articles not manufactured by us



- Art. **38071** Nipple M 1/2"G x M 1/2"G ●●
- Art. **38072** Nipple M 1/2"G x M 3/8"G ●
- Art. **38073** Nipple M 3/8"G x M 3/8"G ●●
- Art. **33114** Nipple M 1"G x M 1/2"G ●
- Art. **33116** Nipple M 1"G x M 1"G ●
- Art. **33117** Nipple M 3/4"G x M 3/4"G ●
- Art. **33118** Nipple M 1/2"G x M 3/4"G ●
- Art. **33119** Nipple M 1"G x M 3/4"G ●
- Art. **33275** Nipple M 1/2"G x F 3/4"G ●
- Art. **33276** Nipple M 3/4"G x F 1"G ●
- Art. **33277** Nipple M 3/4"G x F 1/2"G ●


- tapered/cylindrical thread
- cylindrical/cylindrical thread



Accessories 4-way evacuation valve and flow regulator chamber



The 4-way evacuation valve is used for extraction and discharge of waste oil fluid hydraulic gear and engine oil and antifreeze



extraction

Art. 38130


4-way evacuation valve with connection F 3/4"G

Art. 38131

4-way evacuation valve with connection F 1"G

Art. 38132

4-way evacuation valve with connection F 1.1/2"G



discharge

Article	Seals	Connection	Pressure	Weight
38130	Viton	F 3/4"	14 bar	3 Kg
38131	Viton	F 1"	14 bar	3 Kg
38132	Viton	F 1.1/2"	14 bar	3 Kg



Art. 38097

Art. 38098

Art. 38097

Flow regulator chamber F 3/4" x F 3/4" equipped with:


- one-way valve eliminates sudden pressure changes, ensuring a regular flow
- suitable for R 1:1 - 3:1 - 5:1 pumps
- max pressure 100 bar

Art. 38098

Flow regulator chamber F 3/4" x F 3/4" with air tank equipped with:


- one-way valve eliminates sudden pressure changes, ensuring a regular flow
- suitable for pumps till R 20:1
- max pressure 100 bar

Pressure trend of oil pump outlet




with pump R 3:1 - 8 bar

■ without chamber Art. 38097
■ with chamber Art. 38097



with pump R 3:1 - 8 bar

■ without chamber Art. 38098
■ with chamber Art. 38098





Accessories for oil pumps

*



Art. 38210
Ball cock F 1/2" x F 1/2"
total passage for system
- max pressure 70 bar

Art. 38211
Ball cock F 1" x F 1"
total passage for system
- max pressure 70 bar

* articles not manufactured by us

*



Art. 38095
"Y" filter in line F/F 1/2" for
fitting on the outlet of pumps
for oil and allied products,
max pressure 100 bar

Art. 38096
"Y" filter in line F/F 1" for
fitting on the outlet of pumps
for oil and allied products,
max pressure 100 bar

* articles not manufactured by us

*



Art. 38099
**System overpressure
control valve**
- F 1/2" x F 1/2"
- Calibration 5 - 50 bar

Art. 38100
**System overpressure
control valve**
- F 3/4" x F 3/4"
- Calibration 5 - 50 bar

* articles not manufactured by us

*



Art. 37812
Pressure regulator
with condensate discharge
filter, lubricator, pressure
gauge and inlet-outlet
connections F/F 1/4"

Art. 37817
Pressure regulator
with condensate discharge
filter, lubricator, pressure
gauge and inlet-outlet
connections F/F 1/2"

* articles not manufactured by us



Art. 38091
Check valve
with connection for
flexible hose 1.1/4"
- thread 1"G - M to be
fitted on the draining
cock of tanks



Art. 38080
Hose holder ø 1.1/4" with
M 3/4" inlet connection

Art. 38081
Hose holder ø 1.1/4" with
M 1" inlet connection

Art. 38082
Hose holder ø 1.1/4" with
M 1.1/4" inlet connection

Art. 38083
Stainless steel hose holder
ø 3/4" with **M 1" inlet
connection**



Art. 38026
Flexible suction tube
ø 1.1/4" - 30 mm
- length 2 m for
wall-mounted pumps

Art. 38028
Flexible suction tube
ø 1.1/4" - 30 mm
- length 1 m for
wall-mounted pumps



Art. 33426
Flexible suction tube
ø 3/4"
- length 2 m for
wall-mounted s/steel
pumps



Art. 993.201 Hose M 1/4" x F 1/4" - 1 m - 20 bar
Art. 993.202 Hose M 1/4" x F 1/4" - 2 m - 20 bar
Art. 996.301 Hose M 1/2" x F 1/2" - 1 m - 150 bar
Art. 996.302 Hose F 1/2" x F 1/2" - 2 m - 150 bar
Art. 996.304 Hose M 1/2" x F 1/2" - 4 m - 150 bar
Art. 997.505 Hose M 1/4" x F 1/4" - 5 m - 150 bar
Art. 998.501 Hose M 1" x F 1" - 1 m - 150 bar
Art. 998.502 Hose M 1" x F 1" - 2 m - 150 bar



Accessories for oil pumps



Art. 38056


Flexible and rigid suction tube for wall mounted pump series 500 - 600 - 650 - 900 equipped with:

- Art. 38026 flexible suction tube 2 m - $\varnothing$ 1.1/4"
- Art. 38027 rigid suction tube 940 mm
- Art. 38042 bung adaptor

Art. 38057

Flexible and rigid suction tube for wall mounted pump series 500 - 600 - 650 - 900 equipped with:

- Art. 38026 flexible suction tube 2 m - $\varnothing$ 1.1/4"
- Art. 38055 rigid suction tube 1260 mm
- Art. 33434 bung adaptor



Art. 33583



Flexible and rigid suction tube for wall mounted diaphragm pump equipped with:

- Art. 38026 flexible suction tube 2 m - $\varnothing$ 1.1/4"
- Art. 33581 rigid suction tube 940 mm - $\varnothing$ 1.1/4"
- Art. 33434 bung adaptor

Art. 33585

Flexible and rigid suction tube for wall mounted diaphragm pump equipped with:

- Art. 38026 flexible suction tube da 2 m - $\varnothing$ 1.1/4"
- Art. 33582 rigid suction tube 1240 mm
- Art. 33434 bung adaptor



Art. 33424


Flexible and rigid suction tube for wall mounted pump series 600 INOX equipped with:

- Art. 33426 flexible suction tube 2 m - $\varnothing$ 3/4"
- Art. 33427 stainless steel suction tube 940 mm - $\varnothing$ 3/4"
- Art. 33434 bung adaptor

Art. 33425

Flexible and rigid suction tube for wall mounted pump series 600 INOX equipped with:

- Art. 33426 flexible suction tube 2 m - $\varnothing$ 3/4"
- Art. 33428 stainless steel suction tube 1260 mm - $\varnothing$ 3/4"
- Art. 33434 bung adaptor





Accessories extensions 1" thread



Art. 38092

Top connector - filetto F 1" x F 1"
allows to connect pump M 1" thread with
extensions M 1" thread



Art. 10/21



Art. 10/22



Art. 10/23



Art. 10/24



Art. 10/25

Art. 10/21

Extension ø 34 - thread M 1"G x M 1"G - 460 mm
- suitable for modular and extendable pumps with F 1" connection

Art. 10/22

Extension ø 34 - thread M 1"G x M 1"G - 660 mm
- suitable for modular and extendable pumps with F 1" connection

Art. 10/23


Extension ø 34 - thread M 1"G x M 1"G - 960 mm
- suitable for modular and extendable pumps with F 1" connection

Art. 10/24

Extension ø 34 - thread M 1"G x M 1"G - 1260 mm
- suitable for modular and extendable pumps with F 1" connection

Art. 10/25

Extension ø 34 - thread M 1"G x M 1"G - 1460 mm
- suitable for modular and extendable pumps with F 1" connection



Art. 38092

Art. 10/21

Art. 10/22

Art. 10/23

Art. 10/24

Art. 10/25

Art. 38090

Art. 10/20



Art. 38090



Art. 10/20


Art. 38090

Foot valve with air eliminator - F 1" thread
suitable to fit ø 34 extensions M 1"G thread


Art. 10/20

Foot valve with filter - F 1" thread
suitable to fit ø 34 extensions M 1"G thread


Extendable pumps suction tube 1"




1
Obtain a water pipe (normally
available on the market) ø 1"
and thickness 2,5 mm



2
Cutting the length
suitable for
the container



3
Thread the 2
ends with
1" gas Male



4
Screw the threaded pipe
between the pump and the
foot valve (Art. 10/20)

Note: apply a sealant to prevent air infiltration in the pumping phase or oil leaks during stops



Accessories extensions for customising pumps



Art. 38084



Art. 38085



Art. 38086



Art. 38087



Art. 38088

Art. 38084
Top connector F 1"
for connection between
pump and extension

Art. 38085
Extension $\varnothing$ 32 mm
- 500 mm

Art. 38086
Connector to joint together
to extensions

Art. 38087
Extension $\varnothing$ 32 mm
- 200 mm

Art. 38088
Foot valve
complete with union and
filter



Art. 38084



Art. 38085



Art. 38086



Art. 38087



Art. 38088



Art. 38089




Art. 38093

Art. 38089
**Differentiated union with
valve** for suction tubes
 $\varnothing$ 42 mm with the foot
valve removed it enables
connection between the
suction tube and the modular
extensions

Art. 38093
Union for foot valve
it connects the modular
extension, added to
the suction tube, to the
previously removed foot
valve

Suction tube bottom connections

Extension of the rigid suction
tube for adapting to tank depth




for trolleys
see page 130



Art. 80201



Art. 80210




Art. 80050



FLUIDS AND LUBRICATION EQUIPMENT



Grease dispensing pumps




AIR-OPERATED GREASE PUMPS

page 116



GREASING KIT

page 120



GUNS AND ACCESSORIES

page 126



TROLLEYS FOR CONTAINERS 20 - 220 KG



page 130






Air-operated pumps for DISTRIBUTION grease

Ratio **50:1** Flow rate **1500 g/min**




**HIGH PRESSURE
MEDIUM-LONG DISTANCE**

Series 600 air-operated pumps for short-long distance grease distribution, for high pressure greasing. Ideal for dispensing medium-high viscosity grease. Suitable for mobile installations and centralised fixed systems.




series 600

Article with seals in	PU	62041	62048	62074	62095
Compatible fluids		Greases, medium-high viscosity			
Suction tube upper body		Aluminium			
Suction tube		Carbon steel			
Air inlet connection	bsp	F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G
Fluid outlet connection	bsp	F 3/8" G	F 3/8" G	F 3/8" G	F 3/8" G
Air working pressure	bar	6 - 8	6 - 8	6 - 8	6 - 8
Average air consumption	l/min	330	330	330	330
Noise level	dB	81	81	81	81
Air max pressure	bar	8	8	8	8
Suitable for drums	Kg	16 - 20	20 - 30	50 - 60	180 - 220
Pump	Art.	-	-	-	-
Hose reel	Art.	-	-	-	-
Gun	Art.	-	-	-	-
Drum cover	Art.	-	-	-	-
Follower plate	Art.	-	-	-	-
Connection hose	Art.	-	-	-	-
Nipple	Art.	-	-	-	-
Drip-tray	Art.	-	-	-	-
Packing	N° - m ³	1 - 0,010	1 - 0,010	1 - 0,020	1 - 0,020
Weight	Kg	4,6	4,8	6,1	6,7
Dimensions (A - B - C)	cm	26,5 - 41 - 3	26,5 - 48 - 3	26,5 - 74 - 3	26,5 - 94 - 3




Ratio **65:1** Flow rate **1900 g/min**



series **700**

63041	63048	63074	63095
Greases, medium-high viscosity			
Aluminium			
Carbon steel			
F 1/4" G	F 1/4" G	F 1/4" G	F 1/4" G
F 3/8" G	F 3/8" G	F 3/8" G	F 3/8" G
6 - 8	6 - 8	6 - 8	6 - 8
440	440	440	440
81	81	81	81
8	8	8	8
16 - 20	20 - 30	50 - 60	180 - 220
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
1 - 0,010	1 - 0,010	1 - 0,020	1 - 0,020
5,9	6,1	7,4	8,2
33,5 - 41 - 3	33,5 - 48 - 3	33,5 - 74 - 3	33,5 - 94 - 3




Ratio **50:1** Flow rate **1500 g/min**



series **600**


64200	64210
Greases, medium-high viscosity	
Aluminium	
Carbon steel	
F 1/4" G	F 1/4" G
F 3/8" G	F 3/8" G
6 - 8	6 - 8
330	330
81	81
8	8
180 - 220	180 - 220
62095	62095
8420.501	8440.501
66889	66889
65600	65600
66590	66590
995.702	995.702
38073	38073
88630	88630
4 - 0,150	4 - 0,160
66,8	72







Air-operated pumps for DISTRIBUTION grease



Ratio **45:1**
Flow rate **4400 g/min**





Series 900 industrial air-operated pumps for short-long distance grease distribution, for high pressure greasing. Ideal for transferring grease and high viscosity oil. The double action guarantees the delivery of a continuous and constant flow, suitable for the numerous needs of modern industry. The high quality of the materials used and the anticorrosion treatments reduce internal friction and limit wear over time.



series 900

Article with seals in	PU	90F/451	91F/451
Compatible fluids		Greases, high viscosity oils	
Suction tube upper body		Carbon steel	
Suction tube		Carbon steel	
Air inlet connection	bsp	F 1/2" G	F 1/2" G
Fluid outlet connection	bsp	F 1/2" G	F 1/2" G
Flow rate	g/min	4400	4400
Max air consumption 8 bar	m ³ /min	1,6	1,6
Noise level	dB	80	80
Air max pressure	bar	8	8
Suitable for drums			
			
		tank	suitable for drums 180-220 Kg
Packing	N° - m ³	1 - 0,050	1 - 0,070
Weight	Kg	17	19
Dimensions (A - B - C)	cm	44,5 - 50 - 4,5	44,5 - 94 - 4,5



Ratio **70:1**
Flow rate **3000 g/min**



series 900

91C/701

Greases, high viscosity oils
Aluminium
Carbon steel

F 1/2" G


F 1/2" G

3000

1,6

80

8



suitable for drums
180-220 Kg

1 - 0,070

19

43 - 94 - 4,5

Ratio **75:1**
Flow rate **4400 g/min**



series 1200

116F/751

117F/751

Greases, high viscosity oils
Carbon steel

F 1/2"


F 1/2"

4400

2,8

80

8



suitable for drums
180-220 Kg

1 - 0,070

21

44,5 - 94 - 4,5

F 1/2"


F 1/2"

4400

2,8

80

8





suitable for drums
50-60 Kg

1 - 0,070

20

44,5 - 74 - 4,5




Ratio **40:1**
Flow rate **10000 g/min**



with ram hoist Art.10/85

10/12401P1N

example of pump installation on a twin column ram hoist. **For more info see page 212**






Mobile or fixed grease dispensing kits suitable for drums 180 - 220 kg

Mobile grease dispenser kits.

The ideal combination for dispensing grease in any workplace. The very easy to handle trolley is equipped with a drum (180 - 220 kg) clamping device, adjustable side support for hooking accessories, and wheel with brake. The mobile unit comes with a handy hose reel with 12 m of hose. By request the mobile unit can be equipped with other hose reels (see page 142).



Article	64195	64196	64197	64070	64070/65	64070/75
Ratio	50:1	65:1	75:1	50:1	65:1	75:1
Flow rate g/min	1500	1900	4400	1500	1900	4400
For drums with internal ø mm	from 550 to 600			from 550 to 600		
Pump Art.	62095	63095	116F/751	62095	63095	116F/751
Trolley Art.	-	-	-	80200	80200	80200
Hose reel o tubo erogazione Art.	993.504	993.504	993.504	993.504	993.504	993.504
Gun Art.	66888	66888	66888	66888	66888	66888
Drum cover Art.	65600	65600	10/50	65600	65600	10/50
Follower plate Art.	66590	66590	10/60	66590	66590	10/60
Grease connecting hose Art.	-	-	-	-	-	-
Air connecting hose Art.	993.202	993.202	996.302	-	-	-
Nipple Art.	66892	66892	66893	66892	66892	66893
Air regulator Art.	37801	37801	37814	-	-	-
Air quick coupler Art.	37805	37805	37807	-	-	-
Packing N° - m³	2 - 0,060	2 - 0,060	2 - 0,110	3 - 0,120	3 - 0,120	3 - 0,170
Weight kg	21	22,5	38	40,3	41,7	57
Dimensions (A - B - C) cm	60 - 60 - 120	60 - 60 - 127	60 - 60 - 138	67 - 77 - 131,5	67 - 77 - 131,5	67 - 77 - 131,5



Art. 116F/751

Art. 63095

Art. 62095

Art. 37801 - Art. 37814

Art. 37805

Art. 37807

Art. 993.202

Art. 66888

Art. 993.504

Art. 65600

Art. 10/50

Art. 66590

Art. 10/60

Art. 66892

Art. 66893

Art. 116F/751

Art. 63095

Art. 993.504

Art. 66892 - Art. 66893

Art. 62095

Art. 65600

Art. 10/50

Art. 66590


Art. 10/60

Art. 66888

Art. 80200

with hose reel

with hose reel




64000 **64000/65** **64000/75**
50:1 **65:1** **75:1**
1500 **1900** **4400**


64071 **64071/65** **64071/75**
50:1 **65:1** **75:1**
1500 **1900** **4400**

64001 **64001/65** **64001/75**
50:1 **65:1** **75:1**
1500 **1900** **4400**


from 550 to 600



from 550 to 600



from 550 to 600



62095	63095	116F/751
80201	80201	80201
8430.501	8430.501	8430.501
66889	66889	66889
65600	65600	10/50
66590	66590	10/60
995.702	995.702	995.702
-	-	-
66892	66892	38072
-	-	-
4 - 0,234	4 - 0,234	4 - 0,285
86	87,5	102
93 - 81 - 137	93 - 81 - 137	93 - 81 - 137

62095	63095	116F/751
80210	80210	80210
993.504	993.504	993.504
66889	66889	66889
65600	65600	10/50
66590	66590	10/60
-	-	-
66892	66892	66893
-	-	-
3 - 0,120	3 - 0,120	3 - 0,170
45,8	47,2	62,5
90 - 77 - 126	90 - 77 - 126	90 - 77 - 126

62095	63095	116F/751
80210	80210	80210
8430.501	8430.501	8430.501
66889	66889	66889
65600	65600	10/50
66590	66590	10/60
995.702	995.702	995.702
-	-	-
66892	66892	38072
-	-	-
4 - 0,234	4 - 0,234	4 - 0,285
66,2	67,6	82,5
90 - 77 - 126	90 - 77 - 126	90 - 77 - 126

Art. 116F/751

Art. 63095

Art. 995.702

Art. 66892 - Art. 38072

Art. 62095

Art. 8430.501

Art. 66889

Art. 80201

Art. 65600
Art. 10/50

Art. 66590
Art. 10/60

Art. 116F/751

Art. 63095

Art. 993.504

Art. 66892 - Art. 66893

Art. 62095

Art. 65600
Art. 10/50

Art. 80210

Art. 66889

Art. 66590
Art. 10/60

Art. 116F/751

Art. 63095

Art. 995.702

Art. 66892 - Art. 38072

Art. 62095

Art. 8430.501

Art. 66889
Art. 80210

Art. 65600
Art. 10/50

Art. 66590
Art. 10/60




Mobile or fixed grease dispensing kits suitable for drums 50 - 60 kg




Mobile grease dispenser kits.

The ideal combination for dispensing grease in any workplace.

The compact trolley has 2 fixed wheels and 2 castors (Art. 80050) or only 2 fixed wheels (Art. 80040 and Art. 80035), that make it very easy to handle. It is equipped with a pump support and is suitable for small-medium size containers.



Article		64145	64146	64063	64064
Ratio		50:1	65:1	50:1	50:1
Flow rate	g/min	1500	1900	1500	1500
For drums with internal ø	mm	from 370 to 420 		from 370 to 420 	
Pump	Art.	62074	63074	62074	62074
Trolley	Art.	-	-	80050	80050
Delivery hose	Art.	993.504	993.504	993.504	993.504
Air connecting hose	Art.	993.202	993.202	-	-
Gun	Art.	66888	66888	66888	66888
Drum cover	Art.	65420	65420	65420	65420
Follower plate	Art.	66400	66400	-	66400
Nipple	Art.	66892	66892	66892	66892
Air regulator	Art.	37801	37801	-	-
Air quick coupler	Art.	37805	37805	-	-
Packing	 N° - m³	2 - 0,040	2 - 0,040	3 - 0,059	3 - 0,059
Weight	 kg	17	18	19,5	22,4
Dimensions (A - B - C) cm		43 - 43 - 99	43 - 43 - 106	46 - 50 - 107,5	46 - 50 - 114,5






64040	64041	64037	64038	64042	64042/65	64039	64039/65
50:1	50:1	50:1	50:1	50:1	65:1	50:1	65:1
1500	1500	1500	1500	1500	1900	1500	1900
from 370 to 420		from 340 to 385		from 370 to 420		from 340 to 385	
62074	62074	62074	62074	62074	63074	62074	63074
80035	80035	80035	80035	80040	80040	80040	80040
993.504	993.504	993.504	993.504	993.504	993.504	993.504	993.504
-	-	-	-	-	-	-	-
66888	66888	66888	66888	66888	66888	66888	66888
65420	65420	65385	65385	65420	65420	65385	65385
-	66400	-	66370	66400	66400	66370	66370
66892	66892	66892	66892	66892	66892	66892	66892
-	-	-	-	-	-	-	-
3 - 0,048	3 - 0,048	3 - 0,048	3 - 0,048	3 - 0,048	3 - 0,048	3 - 0,048	3 - 0,048
19	22	18	20	22	23,5	21	22,5
44 - 39,5 - 106	44 - 39,5 - 106	44 - 39,5 - 106	44 - 39,5 - 106	43 - 47,5 - 107,5	43 - 47,5 - 114,5	43 - 47,5 - 107,5	43 - 47,5 - 114,5

Art. 66892
Art. 993.504

Art. 62074


Art. 66888
Art. 66370 - Art. 66400



Art. 62074
Art. 66892
Art. 993.504

Art. 63074

Art. 66888
Art. 66400 - Art. 66370





Mobile or fixed grease dispensing kits suitable for drums 12 - 30 kg

Mobile grease dispenser kits.


The ideal combination for dispensing grease in any workplace.

The compact trolley (Art. 80040 and Art. 80035) has 2 fixed wheels that make it very easy to handle.

It is equipped with a pump support and is suitable for small-medium size containers.



Article		64034	64035	64032	64033
Ratio		50:1	50:1	50:1	50:1
Flow rate	g/min	1500	1500	1500	1500
For drums with internal ø	mm	from 300 to 350 		from 260 to 300 	
Pump	Art.	62048	62048	62048	62048
Trolley	Art.	80035	80035	80035	80035
Delivery hose	Art.	993.504	993.504	993.504	993.504
Gun	Art.	66888	66888	66888	66888
Drum cover	Art.	65350	65350	65310	65310
Follower plate	Art.	-	66340	-	66310
Nipple	Art.	66892	66892	66892	66892
Kit carrying handle	Art.	-	-	-	-
Packing	 N° - m³	3 - 0,040	3 - 0,040	3 - 0,040	3 - 0,040
Weight	 kg	15,9	17,5	15	17
Dimensions (A - B - C)	cm	44 - 39,5 - 99,5	44 - 39,5 - 99,5	44 - 39,5 - 99,5	44 - 39,5 - 99,5



Art. 66892

Art. 62048


Art. 993.504

Art. 65350 - Art. 65310






Art. 66340 - Art. 66310

Art. 66888

Art. 80035





64036	64033/40	64025	64031	64021
50:1	50:1	50:1	50:1	50:1
1500	1500	1500	1500	1500
from 300 to 350	from 260 to 300	from 240 to 280	from 260 to 300	from 240 to 280
				
62048	62048	62041	62048	62041
80040	80040	80040	-	-
993.504	993.504	993.504	993.504	993.504
66888	66888	66888	66888	66888
65350	65310	65280	65310	65280
66340	66310	66265	66310	66265
66892	66892	66892	66892	66892
-	-	-	66599	66599
3 - 0,040	3 - 0,040	3 - 0,040	2 - 0,025	2 - 0,030
18,5	18	17	11,4	11
43 - 47,5 - 99	43 - 47,5 - 99	43 - 47,5 - 99	33 - 33 - 74,5	30 - 30 - 67,5

Art. 62048

Art. 66892

Art. 993.504

Art. 66888

Art. 62041

Art. 65350
Art. 65310 - Art. 65280

Art. 66340
Art. 66310 - Art. 66265

Art. 80040

Art. 66599

Art. 62048

Art. 66892

Art. 993.504

Art. 66888

Art. 62041

Art. 65280 - Art. 65310

Art. 66265 - Art. 66310




Accessories for grease pumps

Union $\varnothing$ 30 mm



Follower plate for pumps series 600 - 700 with suction tube $\varnothing$ 30

- Art. 66265 Follower plate $\varnothing$ 265 mm (drum internal $\varnothing$ 240 - 260 mm)
- Art. 66310 Follower plate $\varnothing$ 310 mm (drum internal $\varnothing$ 255 - 300 mm)
- Art. 66340 Follower plate $\varnothing$ 340 mm (drum internal $\varnothing$ 300 - 330 mm)
- Art. 66370 Follower plate $\varnothing$ 370 mm (drum internal $\varnothing$ 335 - 360 mm)
- Art. 66400 Follower plate $\varnothing$ 400 mm (drum internal $\varnothing$ 360 - 400 mm)
- Art. 66590 Follower plate $\varnothing$ 585 mm (drum internal $\varnothing$ 540 - 580 mm)




Union $\varnothing$ 45 mm



Follower plate for pumps series 900 - 1200 with suction tube $\varnothing$ 45


- Art. 10/60 Follower plate $\varnothing$ 585 mm (drum internal $\varnothing$ 540 - 580 mm)
- Art. 10/61 Follower plate $\varnothing$ 400 mm (drum internal $\varnothing$ 360 - 400 mm)
- Art. 10/62 Follower plate $\varnothing$ 370 mm (drum internal $\varnothing$ 335 - 360 mm)



The **follower plate** is always recommended but becomes indispensable when using particularly hard greases. The follower plate is pulled towards the bottom of the drum by the vacuum created by the pump and always ensures the following advantages:

- it compresses the grease, preventing air pockets from forming and possible cavitation of the pump
- it keeps the grease clean, as well as preserving its characteristics
- it enables collection of all the grease from the bottom of the drum, that would otherwise remain stuck to the sides

Details and advantages




The atmospheric pressure at sea-level is 1 bar, equivalent to approx. 1 kg per cm^2 . When the pump sucks the grease from the container, a vacuum is created under the follower plate and, at the same time, depending on the width of its surface, a pressure from 370 kg to 2000 kg is created above it.

Pump

Drum cover

Follower plate

Vacuum created by pump sucking the grease



Union $\varnothing$ 30 mm



Drum cover for pumps series 600 - 700 with suction tube $\varnothing$ 30

- Art. 65280 Drum cover $\varnothing$ 280 mm (drums external $\varnothing$ 240 - 280 mm)
- Art. 65310 Drum cover $\varnothing$ 310 mm (drums external $\varnothing$ 260 - 300 mm)
- Art. 65350 Drum cover $\varnothing$ 350 mm (drums external $\varnothing$ 300 - 350 mm)
- Art. 65385 Drum cover $\varnothing$ 385 mm (drums external $\varnothing$ 340 - 385 mm)
- Art. 65420 Drum cover $\varnothing$ 420 mm (drums external $\varnothing$ 370 - 420 mm)
- Art. 65600 Drum cover $\varnothing$ 600 mm (drums external $\varnothing$ 550 - 600 mm)



Union $\varnothing$ 45 mm



Drum cover for pumps series 900 - 1200 with suction tube $\varnothing$ 45

- Art. 10/50 Drum cover $\varnothing$ 600 mm (drums external $\varnothing$ 550 - 600 mm)
- Art. 10/51 Drum cover $\varnothing$ 420 mm (drums external $\varnothing$ 370 - 420 mm)
- Art. 10/52 Drum cover $\varnothing$ 385 mm (drums external $\varnothing$ 340 - 385 mm)





Accessories for grease pumps

Union ø 25 - 30 - 38 mm




Drum cover for manual pumps with suction tube ø 25 - 30 - 38

Art. **65309** Drum cover ø 337 mm
(drums external ø 270 - 330 mm) for Art. 60311 (suction tube ø 25 mm)

Art. **65311** Drum cover ø 337 mm
(drums external ø 270 - 330 mm) for Art. 60411 (suction tube ø 38 mm)

Art. **65312** Drum cover ø 337 mm
(drums external ø 270 - 330 mm) for pumps with ø 30 mm suction tube



Art. **66891** Nipple M 1/4"G x
M 1/4"G tapered/cylindrical thread
Art. **66892** Nipple M 1/4"G x
M 3/8"G cylindrical/cylindrical thread
Art. **66893** Nipple M 1/4"G x
M 1/2"G cylindrical/cylindrical thread



Art. **66739** 4-jaw grease coupler
with antisplash valve fitted standard
on manual grease pumps. Inlet M10x1
Art. **66740** Special 4-jaw grease
coupler with antisplash valve fitted
standard on all grease guns. Inlet M10x1



Art. **66895**
Nipple M 3/8"G x F 1/4"NPT
Art. **66896**
Nipple M 1/4"G x F 1/4"NPT
Art. **66897**
Nipple F 1/4"G x M 1/4"NPT



Art. **66741**
90° grease coupler.
Inlet thread M10x1

*



Art. **60450**
Female quick connector
complete with check valve -
F 1/4"G max pressure 350 bar



Art. **66742**
Hooking grease coupler.
Inlet thread M10x1

*



Art. **60451**
Male quick connector
complete with check valve -
F 1/4"G max pressure 350 bar



Art. **66743**
Push-on grease coupler.
Inlet thread M10x1



Art. **66661**
Straight single swivel joint
M/F 1/4" G supplied with grease
guns Art. 66888 - Art. 66881



Art. **66663**
Triple swivel joint
M/F 1/4" G supplied with grease
guns Art. 66889 - Art. 66882



Art. **66599**
Handle for portable grease kit
supplied with grease kits Art. 64020 -
Art. 64021 - Art. 64030 - Art. 64031




Art. **993.201**
Hose M/F 1/4" - 1 m - 20 bar
Art. **993.202**
Hose M/F 1/4" - 2 m - 20 bar
Art. **993.504**
Hose M/F 1/4" - 4 m - 600 bar
Art. **993.512**
Hose M/F 1/4" - 12 m - 600 bar
Art. **993.518**
Hose M/F 1/4" - 18 m - 600 bar
Art. **995.701**
Hose M/F 3/8" - 1 m - 600 bar
Art. **995.702**
Hose M/F 3/8" - 2 m - 600 bar
Art. **995.710**
Hose M/F 3/8" - 10 m - 600 bar
Art. **995.715**
Hose M/F 3/8" - 15 m - 600 bar




Grease guns



Flexible terminal



Art. 66860
Grease gun with flexible terminal
inlet F 1/4", special 4-jaw grease coupler



Art. 66888
Grease gun with flexible terminal
inlet F 1/4", Art. 66661 single swivel joint
special 4-jaw grease coupler



Art. 66889
Grease gun with flexible terminal
inlet F 1/4", Art. 66663 triple swivel joint
special 4-jaw grease coupler

Without terminal



Art. 66855
Grease gun
valve inlet F 1/4"

Rigid terminal




Art. 66880
Grease gun with rigid terminal
inlet F 1/4", with special 4-jaw
grease coupler



Art. 66881
Grease gun with rigid terminal
inlet F 1/4", Art. 66661 single swivel joint
with special 4-jaw grease coupler



Art. 66882
Grease gun with rigid terminal
inlet F 1/4", Art. 66663 triple swivel joint
with special 4-jaw grease coupler



Art. 66856
Flexible terminal with special 4-jaw grease coupler



Art. 66857
Rigid terminal with special 4-jaw grease coupler



Accessories for grease pumps

*




Art. 37801

Pressure regulator with pressure gauge, connections M/F 1/4"G. Applied on a pump or on the tank of a suction/drainer, for regulating the compressed air inlet pressure

Art. 37814

Pressure regulator with pressure gauge, connections M/F 1/2"G. Applied on a pump or on the tank of a suction/drainer, for regulating the compressed air inlet pressure



* articles not manufactured by us

*




Art. 37810

Pressure regulator with condensate discharge filter and pressure gauge, connections F/F 1/4"G for application at the start of the compressed air line feeding the pump

Art. 37815

Pressure regulator with condensate discharge filter and pressure gauge, connections F/F 1/2"G for application at the start of the compressed air line feeding the pump



* articles not manufactured by us

*




Art. 37811

Air lubricator, connections F/F 1/4"G. Its application guarantees better efficiency of the pump over time

Art. 37816

Air lubricator, connections F/F 1/2"G. Its application guarantees better efficiency of the pump over time



* articles not manufactured by us

*




Art. 37812

Pressure regulator with condensate discharge filter, air lubricator and pressure gauge. Connections F/F 1/4"G the system guarantees that the pump feed air is free of condensate

Art. 37817

Pressure regulator with condensate discharge filter, air lubricator and pressure gauge. Connections F/F 1/2"G the system guarantees that the pump feed air is free of condensate




* articles not manufactured by us











MODULAR Trolleys

for drums 20 - 60 Kg









Modular trolleys, entirely galvanised, suitable for handling 20 - 220 kg drums. Equipped with 2 or 4 high fluency wheels that make them very easy to handle. Their compact size ensures perfect integration in the workplace and their modularity enables compact packing for easy storage.



Article	80035	80040	80050	
Suitable for drums	20 - 60	20 - 60	20 - 60	
Packing N° - m ³	1 - 0,010	1 - 0,010	2 - 0,020	
Weight Kg	5	6	9,2	
For drums with max external (D) cm	39	44	39,5	
Dimensions (A - B - C) cm	44 - 39,5 - 99,5	43 - 47,5 - 99	46 - 50 - 99	
Packing dimensions				
Modular structure				




for drums **180 - 220 Kg**

			
80200	80201	80210	80215
180 - 220	180 - 220	180 - 220	180 - 220
1 - 0,060	1 - 0,100	2 - 0,18	2 - 0,028
21,9	45,9	26,2	44
61,5	61,5	61,5	61,5
67 - 77 - 87	93 - 81 - 103	90 - 77 - 115	90 - 77 - 176
			
			


Technical features

Designed to complete our articles such as oil and grease kits

Art. 80035 - Art. 80040




Art. 80200 - Art. 80201
Art. 80210



Art. 80215

Pump,
hose reel
and oil gun
not included





FLUIDS AND LUBRICATION EQUIPMENT



Service columns



FRONTAL SERVICE COLUMNS

page 134

BILATERAL SERVICE COLUMNS

page 136




FRONTAL/BILATERAL SERVICE COLUMNS

page 138



FRONTAL service columns

Frontal service columns. Ideal service stations for rationalising the areas dedicated to delivery. Installable on walls, connected to the centralised distribution system, they are real independent operational stations. Made from top quality materials, with scratchproof painting.




Article	39323	39334	39335
Number of reels can be mounted	3	4	5
Packing  N° - m³	1 - 0,265	1 - 0,460	1 - 0,460
Weight  kg	54,5	84,5	91
Dimensions (A - B - C) cm	245 - 86 - 13	251 - 110 - 24	251 - 134 - 24

Art. 88630
Modular drip-tray.
Equipped with hook for gun and removable drip-tray. Applied under the hose reel, it is a handy holder for the delivery gun. Essential for a clean and orderly workplace.




Details and advantages


Universal drillings for application of accessories



Arrangement for fixing the fluids control system




Holes for drip tray




				
39322	39422 AISI 304 S. Steel	39320 for suction	39321	39421 AISI 304 S. Steel
2	2	1	1	1
1 - 0,265	1 - 0,265	1 - 0,265	1 - 0,265	1 - 0,265
48,5	44	41	42	37
245 - 62 - 13	245 - 62 - 13	245 - 29 - 12,5	245 - 29 - 12,5	245 - 29 - 12,5

The upper part of the support is arranged with holes for the application of hose reels series 330 - 390 - 430 - 450 - 530 and solenoid valves for stopping the fluid. The drip-tray can be applied frontally.



Ceiling installation




Floor installation





BILATERAL service columns

Bilateral service columns, usable from both sides for access. Installable anywhere in the workplace, connected to the centralised distribution system, they are real independent operational stations. Made from top quality materials, with scratchproof painting, and full width drip trays.




Article	39336	39338	39340
Number of reels can be mounted	3 + 3 + (2 hose reel S. 260)	4 + 4 + (2 hose reel S. 260)	5 + 5 + (2 hose reel S. 260)
Packing  N° - m ³	1 - 0,460	1 - 0,460	1 - 0,460
Weight  kg	86	94	101
Dimensions (A - B - C) cm	251 - 86 - 24	251 - 110 - 24	251 - 134 - 24


The upper part of the support is arranged with holes for the application of hose reels series 330 - 390 - 430 - 450 - 530 and solenoid valves for stopping the fluid. The drip-tray can be applied frontally.

Details and advantages


Universal drillings for application of accessories




Arrangement for fixing the fluids control system




Holes for drip tray



Drip-tray






Art. 88630
Modular drip-tray.
 Equipped with
 hook for gun and
 removable
 drip-tray.
 Applied under
 the hose reel,
 it is a handy
 holder for the
 delivery gun.
 Essential for
 a clean and
 orderly
 workplace.



39324	39328
4 + (2 hose reel S. 260)	8 + (2 hose reel S. 260)
1 - 1,035 228	1 - 1,035 276
268,5 - 145,2 - 50,5	268,5 - 250,3 - 50,5



Ceiling installation

Floor installation





FRONTAL/BILATERAL service columns

Frontal, bilateral service column or with containment tank.

Ideal service stations for rationalising the areas dedicated to delivery. Able to collect any leaks or accidental spills, by means of the containment tanks, in compliance with the new regulations. Installable on walls, they are real independent operational stations. Made from top quality materials, with scratchproof painting.



Article	39351	39352
Number of reels can be mounted	2 hose reel + 1 drum 180-220 kg	3 hose reel + 2 drums 180-220 kg
Packing N° - m³	2 - 1,080	2 - 1,120
Weight kg	161	183,5
Dimensions (A - B - C) cm	260 - 110 - 89,5	260 - 145 - 89,5

Art. 39901


Containment tank 1 drum 180 - 220 Kg (capacity 197 litre)

N°1 packing m³ 0,525 Kg 51

Art. 39902


Containment tank 2 drum 180 - 220 Kg (capacity 266 litre)

N°1 packing m³ 0,670 Kg 64,5




Details and advantages


Universal drillings for application of accessories




Holes for application of alternative pump



Holes for drip tray





Accessories for Art. 39314 - 39317

Art. 39405 PC holder for service columns

N°1 packing m³ 0,019


Kg 3,6



Art. 39406 Paper holder for service columns

N°1 packing m³ 0,044


Kg 3,3



Art. 39407 Basket for service columns

N°1 packing m³ 0,044


Kg 3,9




39304	39307	39314	39317
4	6	4 + (2 hose reel S. 260)	6 + (2 hose reel S. 260)
1 - 0,520	1 - 0,650	1 - 0,090	1 - 1,245
136	166	265	305
234 - 107 - 48,5	234 - 155 - 48,5	264 - 129 - 60	264 - 177 - 60

Details and advantages


Universal drillings for application of accessories



Delivery gun-hose hook




Drip-tray




Details and advantages


Universal drillings for application of accessories



Arrangement for fixing the fluids control system



Drip-tray





RAASM HOSE REEL

FLUIDS AND LUBRICATION EQUIPMENT



INDUSTRIAL HOSE REELS



Index hose reels

INTRODUCTION, ADVANTAGES AND CHOOSING A HOSE REEL

page 144

ENCLOSED IN SHOCK RESISTANT TECHNOPOLIMER SERIES 260



AIR-WATER 20 BAR

page 148

OPEN - HOSE POLYURETHANE



AIR-WATER 20 BAR

page 149

ENCLOSED IN PAINTED STEEL SERIES 450 - 440



AIR-WATER 20 BAR

page 150


OIL AND SIMILAR PRODUCTS 150 BAR

page 150

GREASE 600 BAR

page 150

ENCLOSED AND OPEN WITH DRUM IN ABS SHOCK PROOF



AIR-WATER 20 BAR

page 151

WATER MAX 130°C 100 BAR

page 151

WATER MAX 130°C 200 BAR

page 151


OIL AND SIMILAR PRODUCTS 150 BAR

page 151

GREASE 600 BAR

page 151

OPEN - AIR-WATER - PAINTED OR STAINLESS STEEL



AIR-WATER 20 BAR

page 154

WATER MAX 130°C 100 BAR

page 156


WATER MAX 130°C 200 BAR

page 158

WATER MAX 130°C 400 BAR

page 160

OPEN - STAINLESS STEEL AISI 304



WATER MAX 130°C 100 BAR

page 162

WATER MAX 130°C 200 BAR

page 162

WATER MAX 130°C 400 BAR

page 162

OPEN - STAINLESS STEEL AISI 316



WATER MAX 130°C 100 BAR

page 163

OPEN - OIL, GREASE AND ALLIED PRODUCTS - PAINTED OR STAINLESS STEEL



OIL AND SIMILAR PRODUCTS 150 BAR

page 164

GREASE 600 BAR

page 166

OPEN - DIESEL FUEL AND ADBLUE IN PAINTED OR STAINLESS STEEL



DIESEL FUEL 10 BAR page 168

ADBLUE 10 BAR page 170

OPEN - DOUBLE INLET AND OUTLET - PAINTED STEEL



AIR-WATER 20 BAR page 171

OIL-WATER 200 BAR page 171

OIL-PAINT 200 BAR page 171

OIL 400 BAR page 171

OPEN - WELDING OXYGEN-ACETYLENE AND LPG-METHANE - PAINTED STEEL



WELDING 20 BAR page 172

LPG-METHANE 20 BAR page 173

PNEUMATIC OR HYDRAULIC MOTOR OPERATED INDUSTRIAL SERIES - PAINTED STEEL



AIR-WATER 20 BAR page 174

WATER MAX 130°C 100 BAR page 174

OIL AND SIMILAR PRODUCTS 150 BAR page 174

GREASE 400 BAR page 174

DIESEL FUEL 10 BAR page 174

SERIES 500 - MANUAL - PAINTED STEEL



AIR-WATER 20 BAR page 176

WATER MAX 130°C 100 BAR page 176

WATER MAX 130°C 200 BAR page 176

WATER MAX 130°C 400 BAR page 176

OIL AND SIMILAR PRODUCTS 150 BAR page 176

DIESEL FUEL 10 BAR page 176

GROUNDING CABLE REEL - PAINTED STEEL



GROUNDING CABLE REEL page 177

SERIES 700 MOTOR DRIVEN AND MANUAL OPERATED - PAINTED STEEL




SERIES 700 page 178



ACCESSORIES - HOSES page 180



RAASM introduces his wide range of hose reels



RAASM's hose reels, equipped with rewinding spring with constant tension, are available in many versions: open or enclosed, fixed or swivelling, in painted steel, in stainless steel, in ABS material. Motor driven hose reels, pneumatic or hydraulic, are available as well. **The hose reels allow to manage, in a practical and safe way, all kind of flexible hoses to transfer every type of fluids.**

HOSE REEL ADVANTAGES



NO

ACCIDENT


The hose reel **allow workers to operate in a safe workplace, using equipment always ready for use.**



NO

BREAK

The hose reel **safeguards against wear and possible breakage of the hoses themselves.**



NO

DISORDER

With the hose reel, hose rewinding is quick and safe, for an **orderly workplace.**

Choosing a hose reel

When choosing a hose reel, it is important to consider the following aspects:

TYPE OF FLUID TO BE DELIVERED	FLOWRATE IN L/MIN TO BE DELIVERED	LENGTH AND DIAMETER OF HOSE TO BE USED	PRESSURE OF FLUID
-------------------------------	-----------------------------------	--	-------------------

TYPE OF FLUID TO BE DELIVERED AND PRESSURE OF FLUID


Air - Water 20 bar	AdBlue 10 bar
Water max 130° C 100 bar	Air - Water 20 bar
Water max 130° C 200 bar	Oil - Water 200 bar
Water max 130° C 400 bar	Oil - Paint 200 bar
Oil and similar products 150 bar	Oil 400 bar
Grease 600 bar	Welding 20 bar
Diesel fuel 10 bar	LPG - methane 20 bar

HOSE LENGTH AND DIAMETER

external diameter of hose	HOSE REELS SERIES									
	290	330	380 - 390	420 - 430	440 - 450	520 - 530	540 - 550	560	617 - 618	637 - 638
ø 12 mm	max. length 16 m	max. length 18 m	max. length 22 m	-	-	-	-	-	-	-
ø 14 mm	max. length 14 m	max. length 16 m	max. length 20 m	-	-	-	-	-	-	-
ø 17 mm	max. length 10 m	max. length 12 m	max. length 18 m	max. length 21 m	max. length 21 m	max. length 28 m	-	-	-	-
ø 19,5 mm		-	-	max. length 16 m	max. length 16 m	max. length 26 m	-	-	-	-
ø 22 mm		-	-	max. length 14 m	max. length 14 m	max. length 24 m	max. length 30 m	max. length 60 m	max. length 50 m	max. length 100 m
ø 28 mm		-	-	-	-	-	max. length 22 m	max. length 40 m	max. length 30 m	max. length 60 m
ø 34 mm		-	-	-	-	-	max. length 17 m	max. length 30 m	max. length 20 m	max. length 40 m
ø 44 mm		-	-	-	-	-	-	-	max. length 15 m	max. length 30 m
ø 50 mm		-	-	-	-	-	-	-	max. length 10 m	max. length 20 m
ø 13 + 13 mm		-	-	max. length 13 m	-	max. length 22 m	max. length 37 m	-	-	-
ø 15 + 15 mm		-	-	max. length 12 m	-	max. length 20 m	max. length 35 m	-	-	-
ø 16 + 16 mm		-	-	max. length 10 m	-	max. length 15 m	max. length 27 m	-	-	-

HOSE STOP

Adapters for hoses of different diameter (supplied with the hose stop)



Universal hose stop comes with all hose reels supplied without hose, complete with adapters for using hoses of different diameter.

Article	Hose reels series	ø Reductions
KR7201	290 - 330 380 - 390	Painted - S. steel 12 - 14 - 16 mm
KR8104	420 - 430 - 440 450 - 520 - 530	Painted - S. steel 14 - 17 - 19 mm
KR8705	540 - 550 - 560	Painted - S. steel 14 - 17,5 - 21 28,5 - 30 - 34 mm
KR8907	420 - 520 - 540	Double hose 12 - 14 - 15 - 16 mm



Technical characteristics

Corrosion proof: all the components are treated or painted for external use.
Easy to install anywhere: on wall, floor, ceiling, vehicles, etc.

Automatic stopping system: allows hose to be locked at the required length


Fluid conveyance joint

The wall bracket with bayonet hooking is easy to mount and allows to remove quickly the hose reel when necessary

Rewinding spring

Adjustable hose stop

Self-lubricating hose guide rollers



Drum support bushings in self-lubricating material

The easy to install adjustable bracket allows the hose reel to be removed for any maintenance


The trip enables automatic stopping at the required length

Fluid conveyance joint

Rewinding spring

Adjustable hose stop

Self-lubricating hose guide rollers



Automatic stopping system: allows the hose to be locked at the required length

Adjustable arm: to favour hose extraction according to hose reel installation

Self-lubricating hose guide rollers: wide multi-way opening


Adjustable hose stop

Drum support bushings in brass alloy, self-lubricating, effective and corrosion resistant

Hose reel drum: sturdy and practical with ribbing and rounded edges

Fully enclosed and protected constant-force automatic rewinding spring

Fluid passage swivel joint in brass / carbon steel / s/steel / AISI 304 s/steel with polyurethane / viton / teflon seals





Guide to reading the catalogue

1. Type of fluid
to be delivered
(water, air, oil,
grease, other)

2. Pressure
of fluid to be
delivered linked
to the feed pressure

3. Hose length
the distance between
the hose reel and the
places where the fluid
is to be delivered

4. Hose diameter
on which the capacity of the
hose itself depends

S. 290

AIR / WATER - 20 bar

PAINTED STEEL

A. Stainless steel or painted
this depends on the
workplace (closed or open)
and the type of hose reel
use (protected or exposed
to water sprays)

B. Fixed or swivelling
if the hose reel is used in a
battery its operating range will
be limited, therefore the fixed
version is preferable.
For uses requiring a greater
operating range the swivelling
version is recommended


C. Open or enclosed
the enclosed version is
available only for the
following fluids: air, oil
and grease. The choice
is up to the customer

FIXED	SWIVELLING	Supplied with:
		- hoses in black synthetic - galvanised steel fitting - swivel in brass - seals in "viton"
Article	Article	Hose supplied
8290.100	-	without hose
8290.101	-	10m - 3/8" (995.210)
8290.104	-	15m - 1/4" (993.215)
8330.100	-	without hose
8330.101	-	12m - 3/8" (995.211)


HOSE REEL INSTALLATION

Example of installation: the adjustable arms can be easily repositioned according to needs


Standard installation




Wall installation



Bench installation



Ceiling installation



ACCESSORIES FOR HOSE REEL

Art. 88650
Latch mechanism
protective cover
rack side for hose reels
series 420 - 430

Art. 88651
Latch mechanism
protective cover
rack side for hose reels
series 520 - 530
540 - 550 - 560



Art. 88630
Modular drip-tray.
Equipped with hook
for gun and removable
drip-tray.
Applied under the
hose reel, it is a
handy holder for the
delivery gun.
Essential for a clean
and orderly workplace.





AIR / WATER - 20 bar


Series 260




SWIVELLING wall support with BAYONET hooking

Article	Hose supplied	Connection	
		inlet	outlet
89010	11m - 8x12 (971.111)	M1/4"G	M1/4"G
89011	11m - 6x10 (971.011)	M1/4"G	M1/4"G

OVERALL DIMENSIONS



To prevent removal or theft of the hose reel, it can be secured with a bolt or padlock.




Series 260



SWIVELLING SIMPLE wall support

Article	Hose supplied	Connection	
		inlet	outlet
89109	11m - 8x12 (971.111)	M1/4"G	M1/4"G
89110	11m - 6x10 (971.011)	M1/4"G	M1/4"G

OVERALL DIMENSIONS





Supplied with

- polyurethane hose
- zinc plated steel couplings
- brass swivel joint
- "viton" seals



Art. 89001

Series 260 hose reels are equipped with a **wall bracket with bayonet hooking**. The placing of several brackets in the service points allows the hose reel to be easily moved to the various workstations.





AIR / WATER - 20 bar PAINTED STEEL



In accordance with directive
Atex 94/9 II 3 GD c X

FIXED



Supplied with:
- polyurethane hose
- brass fitting
- brass swivel joint
- "viton" seals



S. 288

Article	Hose supplied	Connection	
		inlet	outlet
8288.100	without hose	M3/8"G	F3/8"G
8288.102	13m - 10x14,5 (972.113)	M3/8"G	M3/8"G
8288.103	15m - 8x12 (971.115)	M3/8"G	M1/4"G
8288.104	10m - 6x10 (971.010)	M3/8"G	M1/4"G
8288.105	15m - 6x10 (971.015)	M3/8"G	M1/4"G

S. 328

8328.100	without hose	M3/8"G	F3/8"G
8328.102	15m - 10x14,5 (972.115)	M3/8"G	M3/8"G
8328.103	18m - 8x12 (971.118)	M3/8"G	M1/4"G
8328.104	8m - 13x19 (976.108)	M1/2"G	M1/2"G
8328.105	12m - 13x19 (976.112)	M1/2"G	M1/2"G




S. 378

8378.100	without hose	M3/8"G	F3/8"G
8378.102	20m - 10x14,5 (972.120)	M3/8"G	M3/8"G
8378.103	20m - 8x12 (971.120)	M3/8"G	M1/4"G
8378.104	10m - 13x19 (976.110)	M1/2"G	M1/2"G
8378.105	15m - 13x19 (976.114)	M1/2"G	M1/2"G

S. 438

8430.100	without hose	F1/2"G	F1/2"G
8438.101	10m - 13x19 (976.111)	F1/2"G	M1/2"G
8438.102	15m - 13x19 (976.115)	F1/2"G	M1/2"G

FIXED OVERALL DIMENSIONS




Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 288	186	140	196	226	110	310	300	320	-	0,037	from 7 to 12
S. 328	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 378	186	140	196	226	110	400	390	410	20	0,068	from 10 to 17
S. 438	186	140	196	226	115	450	420	460	20	0,098	from 14 to 21

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.





ENCLOSED IN PAINTED STEEL

Series 450

Series 440



In accordance with directive
Atex 94/9
IIB 2 GD c T4 T135 °C X




Supplied with:
- hoses in black synthetic rubber
- zinc plated steel couplings




	Article	Article	Hose supplied	Connection	
				inlet	outlet
Air - Water 20 bar - bras swivel joint - "viton" seals	8450.100	8440.100	without hose	F1/2"G	F1/2"G
	8450.101	8440.101	12m - 3/8" (995.212)	F1/2"G	M3/8"G
	8450.102	8440.102	18m - 3/8" (995.218)	F1/2"G	M3/8"G
	8450.103	8440.103	10m - 1/2" (996.210)	F1/2"G	M1/2"G
	8450.104	8440.104	15m - 1/2" (996.215)	F1/2"G	M1/2"G
Oil and similar products 150 bar - carbon steel swivel joint - "polyurethane" seals	8450.400	8440.400	without hose	F1/2"G	F1/2"G
	8450.401	8440.401	10m - 1/2" (996.310)	F1/2"G	M1/2"G
	8450.402	8440.402	15m - 1/2" (996.315)	F1/2"G	M1/2"G
Grease 600 bar - carbon steel swivel joint - "polyurethane" seals	8450.500	8440.500	without hose	F3/8"G	F1/2"G
	8450.501	8440.501	12m - 1/4" (993.512)	F3/8"G	M1/4"G
	8450.502	8440.502	18m - 1/4" (993.518)	F3/8"G	M1/4"G
	8450.505	8440.505	10m - 3/8" (995.710)	F3/8"G	M1/4"G
	8450.506	8440.506	15m - 3/8" (995.715)	F3/8"G	M1/4"G

FIXED OVERALL DIMENSIONS



N°1 packing m³ 0,111 from kg 21 to 29

SWIVELLING OVERALL DIMENSIONS




N°1 packing m³ 0,111 from kg 22 to 30

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





ENCLOSED IN PAINTED STEEL with **ABS** spool



In accordance with directive
Atex 94/9 II 3 GD c X

Series 450

cover in
painted steel

ABS shock
proof drum

Supplied with:
- hoses in black synthetic rubber
- zinc plated steel couplings



FIXED support

Article

Hose supplied

Connection

inlet

outlet

Air - Water 20 bar

- bras swivel joint
- "viton" seals

9450.100

9450.101

9450.102

9450.103

9450.104

without hose

F1/2"G

F1/2"G

12m - 3/8" (995.212)

F1/2"G

M3/8"G

18m - 3/8" (995.218)

F1/2"G

M3/8"G

10m - 1/2" (996.210)

F1/2"G

M1/2"G

15m - 1/2" (996.215)

F1/2"G

M1/2"G

Oil and similar products 150 bar

- carbon steel swivel joint
- "polyurethane" seals

9450.400

9450.401

9450.402

without hose

F1/2"G

F1/2"G

10m - 1/2" (996.310)

F1/2"G

M1/2"G

15m - 1/2" (996.315)

F1/2"G

M1/2"G

Grease 600 bar

- carbon steel swivel joint
- "polyurethane" seals

9450.500

9450.501

9450.502

9450.505

9450.506

without hose

F3/8"G

F1/2"G

12m - 1/4" (993.512)

F3/8"G

M1/4"G

18m - 1/4" (993.518)

F3/8"G

M1/4"G

10m - 3/8" (995.710)

F3/8"G


M1/4"G

15m - 3/8" (995.715)

F3/8"G

M1/4"G

FIXED OVERALL DIMENSIONS




N°1 packing m³ 0,111 from kg 20 to 29

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.


TEMPLATE




HOSE REEL INSTALLATION

Example of installation: the hose reel can be easily repositioned according to needs


Standard installation




Wall installation



Bench installation



Ceiling installation





PAINTED STEEL with ABS spool

Series 430

Painted steel bracket



In accordance with directive
Atex 94/9 II 3 GD c X

ABS shock proof drum

Supplied with:
- hoses in black synthetic rubber
- zinc plated steel couplings



FIXED support

Article

Hose supplied

Connection

inlet

outlet

Air - Water 20 bar

- bras swivel joint
- "viton" seals

9430.100

9430.101

9430.102

9430.103

9430.104

without hose

F1/2"G

F1/2"G

12m - 3/8" (995.212)

F1/2"G

M3/8"G

18m - 3/8" (995.218)

F1/2"G

M3/8"G

10m - 1/2" (996.210)

F1/2"G

M1/2"G

15m - 1/2" (996.215)

F1/2"G

M1/2"G

Water max 130° C 100 bar

- AISI 304 stainless steel swivel joint
- "viton" seals

9430.200

9430.201

9430.202

hygieninc hose

9431.202

without hose

F1/2"G

F1/2"G

10m - 1/2" (996.311)

F1/2"G

M1/2"G

15m - 1/2" (996.316)

F1/2"G

M1/2"G

15m - 1/2" (996.415)

F1/2"G

M1/2"G

Water max 130° C 200 bar

- AISI 304 stainless steel swivel joint
- "viton" seals

9430.300

9430.301

9430.302

hygieninc hose

9431.302

without hose

F3/8"G

F1/2"G

12m - 3/8" (995.512)

F3/8"G

F3/8"G

18m - 3/8" (995.518)

F3/8"G

F3/8"G

18m - 3/8" (995.618)

F3/8"G

F3/8"G

Oil and similar products 150 bar

- carbon steel swivel joint
- "polyurethane" seals

9430.400

9430.401

9430.402

without hose

F1/2"G

F1/2"G

10m - 1/2" (996.310)

F1/2"G

M1/2"G

15m - 1/2" (996.315)

F1/2"G

M1/2"G

Grease 600 bar

- carbon steel swivel joint
- "polyurethane" seals

9430.500

9430.501

9430.502

9430.505

9430.506

without hose

F3/8"G

F1/2"G

12m - 1/4" (993.512)

F3/8"G

M1/4"G

18m - 1/4" (993.518)

F3/8"G

M1/4"G

10m - 3/8" (995.710)

F3/8"G





M1/4"G

15m - 3/8" (995.715)

F3/8"G

M1/4"G


FIXED OVERALL DIMENSIONS



1 N°1 packing m³ 0,098 from kg 14 to 24

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.



TEMPLATE



STAINLESS STEEL with ABS spool

Series 430

AISI 304 stainless steel bracket



In accordance with directive
Atex 94/9 II 3 GD c X

ABS shock
proof drum

Supplied with:
- hoses in black synthetic rubber
- zinc plated steel couplings



FIXED support

Article

Hose supplied

Connection

inlet

outlet

Air - Water 20 bar

- bras swivel joint
- "viton" seals

9432.100

9432.101

9432.102

9432.103

9432.104

without hose

F1/2"G

F1/2"G

12m - 3/8" (995.212)

F1/2"G

M3/8"G

18m - 3/8" (995.218)

F1/2"G

M3/8"G

10m - 1/2" (996.210)

F1/2"G

M1/2"G

15m - 1/2" (996.215)

F1/2"G

M1/2"G

Water max 130° C 100 bar

- AISI 304 stainless steel swivel joint
- "viton" seals

9434.200

9432.201

9432.202

hygieninc hose

9433.202

without hose

F1/2"G

F1/2"G

10m - 1/2" (996.311)

F1/2"G

M1/2"G

15m - 1/2" (996.316)

F1/2"G

M1/2"G

15m - 1/2" (996.415)

F1/2"G

M1/2"G

Water max 130° C 200 bar

- AISI 304 stainless steel swivel joint
- "viton" seals

9434.300

9432.301

9432.302

hygieninc hose

9433.302

without hose

F3/8"G

F1/2"G

12m - 3/8" (995.512)

F3/8"G

F3/8"G

18m - 3/8" (995.518)

F3/8"G

F3/8"G

18m - 3/8" (995.618)

F3/8"G

F3/8"G

Oil and similar products 150 bar

- AISI 304 stainless steel swivel joint
- "viton" seals

9434.200

9432.401

9432.402

without hose

F1/2"G

F1/2"G

10m - 1/2" (996.310)

F1/2"G

M1/2"G

15m - 1/2" (996.315)

F1/2"G

M1/2"G

Grease 600 bar

- carbon steel swivel joint
- "polyurethane" seals

9432.500

9432.501

9432.502

9432.505

9432.506

without hose

F3/8"G

F1/2"G

12m - 1/4" (993.512)

F3/8"G

M1/4"G

18m - 1/4" (993.518)

F3/8"G

M1/4"G

10m - 3/8" (995.710)

F3/8"G





M1/4"G

15m - 3/8" (995.715)

F3/8"G

M1/4"G


FIXED OVERALL DIMENSIONS



📦 N°1 packing m³ 0,098 📦 from kg 14 to 24

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.





AIR / WATER - 20 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED




Article

8290.100
8290.101
8290.104

S. 290

SWIVELLING



Article

-
-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- brass swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F3/8"G
10m - 3/8" (995.210)	F3/8"G	M3/8"G
15m - 1/4" (993.215)	F3/8"G	M1/4"G
without hose	F3/8"G	F3/8"G
12m - 3/8" (995.211)	F3/8"G	M3/8"G
without hose	F3/8"G	F3/8"G
18m - 3/8" (995.217)	F3/8"G	M3/8"G
without hose	F1/2"G	F1/2"G
12m - 3/8" (995.212)	F1/2"G	M3/8"G
18m - 3/8" (995.218)	F1/2"G	M3/8"G
10m - 1/2" (996.210)	F1/2"G	M1/2"G
15m - 1/2" (996.215)	F1/2"G	M1/2"G
for ABS hose reels Series 430 see page 152		
without hose	F1/2"G	F1/2"G
20m - 1/2" (996.220)	F1/2"G	M1/2"G
25m - 1/2" (996.225)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
15m - 3/4" (997.215)	F1"G	M3/4"G
20m - 3/4" (997.220)	F1"G	M3/4"G
15m - 1" (998.215)	F1"G	M1"G
without hose	F1/2"G	F1/2"G
30m - 1/2" (996.230)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
30m - 3/4" (997.230)	F1"G	M3/4"G
40m - 3/4" (997.240)	F1"G	M3/4"G
20m - 1" (998.220)	F1"G	M1"G
30m - 1" (998.230)	F1"G	M1"G
without hose	F1/2"G	F1/2"G





FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





AIR / WATER - 20 bar

STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED




Article

8292.100
8292.101
8292.104

S. 290

SWIVELLING



Article

-
-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- brass swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F3/8"G
10m - 3/8" (995.210)	F3/8"G	M3/8"G
15m - 1/4" (993.215)	F3/8"G	M1/4"G
without hose	F3/8"G	F3/8"G
12m - 3/8" (995.211)	F3/8"G	M3/8"G
without hose	F3/8"G	F3/8"G
18m - 3/8" (995.217)	F3/8"G	M3/8"G
without hose	F1/2"G	F1/2"G
12m - 3/8" (995.212)	F1/2"G	M3/8"G
18m - 3/8" (995.218)	F1/2"G	M3/8"G
10m - 1/2" (996.210)	F1/2"G	M1/2"G
15m - 1/2" (996.215)	F1/2"G	M1/2"G
for ABS hose reels Series 430 see page 153		
without hose	F1/2"G	F1/2"G
20m - 1/2" (996.220)	F1/2"G	M1/2"G
25m - 1/2" (996.225)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
15m - 3/4" (997.215)	F1"G	M3/4"G
20m - 3/4" (997.220)	F1"G	M3/4"G
15m - 1" (998.215)	F1"G	M1"G
without hose	F1/2"G	F1/2"G
30m - 1/2" (996.230)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
30m - 3/4" (997.230)	F1"G	M3/4"G
40m - 3/4" (997.240)	F1"G	M3/4"G
20m - 1" (998.220)	F1"G	M1"G
30m - 1" (998.230)	F1"G	M1"G
without hose	F1/2"G	F1/2"G

8332.100
8332.101

S. 330

8382.100
8382.102

8432.100
8432.101
8432.102
8432.103
8432.104

S. 430

8422.100
8422.101
8422.102
8422.103
8422.104

8532.100
8532.101
8532.102

S. 530

8522.100
8522.101
8522.102

8542.100
8542.101
8542.102
8542.103
8542.105
8542.106

S. 540


8552.100
8552.101
8552.102
8552.103
8552.105
8552.106

8562.100
8562.101
8562.103
8562.104
8562.105
8562.106


S. 560

-
-
-
-
-
-

FIXED OVERALL DIMENSIONS



SWIVELLING OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 290	186	140	196	226	110	310	300	320	-	0,037	from 7 to 12
S. 330	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 390	186	140	196	226	110	400	390	410	20	0,068	from 11 to 18
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40
S. 560	488	399	238	272	368	550	510	578	0	0,310	from 30 to 80

Art.	A	B	C	D	E	F	G	H	1-m ³	Kg
S. 380	184	146	106	144	110	400	390	484	0,098	from 12 to 19
S. 420	208	162	118	164	115	460	420	541	0,098	from 15 to 25
S. 520	228	182	154	200	115	560	510	642	0,120	from 20 to 43
S. 550	300	218	226	268	190	560	510	702	0,175	from 25 to 41

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.



WATER MAX 130°C - 100 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

8330.200
8330.201

SWIVELLING



Article

-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "viton" seals



S. 330

S. 390

S. 430

S. 530

S. 540

S. 560

8390.200
8390.202

8430.200
8430.201
8430.202

8530.200
8530.201

8540.200
8540.202
8540.203

8560.200
8560.205

8380.200
8380.202

8420.200
8420.201
8420.202

8520.200
8520.201

8550.200
8550.202
8550.203

-
-

Hose supplied

without hose
12m - 3/8" (995.313)

Connection

inlet

outlet

F1/2"G F 3/8"-1/2"G
F1/2"G M3/8"G

without hose
17m - 3/8" (995.318)

without hose
10m - 1/2" (996.311)
15m - 1/2" (996.316)

without hose
20m - 1/2" (996.321)

without hose
20m - 3/4" (997.320)
15m - 1" (998.315)

without hose
30m - 1" (998.330)

F1/2"G F3/8"-1/2"G
F1/2"G M3/8"G

F1/2"G F1/2"G
F1/2"G M1/2"G
F1/2"G M1/2"G

F1/2"G F1/2"G
F1/2"G M1/2"G

F1"G F1"G
F1"G M3/4"G
F1"G M1"G


F1"G F1"G
F1"G M1"G

for ABS hose reels Series 430 see page 152

FIXED HOSE REELS INSTALLATION


The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.



SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





WATER MAX 130°C - 100 bar

STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED




Article

8332.400
8332.201
8333.202

S. 330
hygienic hose

SWIVELLING



Article

-
-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F1/2"G	F 3/8"-1/2"G
12m - 3/8" (995.313)	F1/2"G	M3/8"G
12m - 3/8" (995.412)	F1/2"G	M3/8"G

8392.200
8392.202
8393.201

S. 390
hygienic hose

8382.200
8382.202
8383.201

without hose	F1/2"G	F3/8"-1/2"G
17m - 3/8" (995.318)	F1/2"G	M3/8"G
12m - 3/8" (995.412)	F1/2"G	M3/8"G

8434.200
8432.201
8432.202
8433.202

S. 430
hygienic hose

8424.200
8422.201
8422.202
8423.202

without hose	F1/2"G	F1/2"G
10m - 1/2" (996.311)	F1/2"G	M1/2"G
15m - 1/2" (996.316)	F1/2"G	M1/2"G
15m - 1/2" (996.415)	F1/2"G	M1/2"G

for ABS hose reels Series 430 see page 153

8534.200
8532.201
8533.202

S. 530
hygienic hose

8524.200
8522.201
8523.202

without hose	F1/2"G	F1/2"G
20m - 1/2" (996.321)	F1/2"G	M1/2"G
25m - 1/2" (996.425)	F1/2"G	M1/2"G

8544.200
8542.202
8542.203
8543.202

S. 540
hygienic hose

8554.200
8552.202
8552.203
8553.202

without hose	F1"G	F1"G
20m - 3/4" (997.320)	F1"G	M3/4"G
15m - 1" (998.315)	F1"G	M1"G
20m - 3/4" (997.420)	F1"G	M3/4"G


8564.200
8562.205

S. 560

-
-


without hose	F1"G	F1"G
30m - 1" (998.330)	F1"G	M1"G

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 330	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 390	186	140	196	226	110	400	390	410	20	0,068	from 11 to 18
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40
S. 560	488	399	238	272	368	550	510	578	0	0,310	from 30 to 80

SWIVELLING OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	1-m ³	Kg
S. 380	184	146	106	144	110	400	390	484	0,098	from 12 to 19
S. 420	208	162	118	164	115	460	420	541	0,098	from 15 to 25
S. 520	228	182	154	200	115	560	510	642	0,120	from 20 to 43
S. 550	300	218	226	268	190	560	510	702	0,175	from 25 to 41

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.



WATER MAX 130°C - 200 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

8330.300
8330.301

SWIVELLING



Article

-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F3/8"G
12m - 5/16" (994.512)	F3/8"G	F3/8"G

S. 330

S. 390

8390.300
8390.302

8380.300
8380.302

without hose F3/8"G F3/8"G
17m - 5/16" (994.517) F3/8"G F3/8"G

S. 430

8430.300
8430.301
8430.302

8420.300
8420.301
8420.302

without hose F3/8"G F1/2"G
12m - 3/8" (995.512) F3/8"G F3/8"G
18m - 3/8" (995.518) F3/8"G F3/8"G

for ABS hose reels Series 430 see page 152

S. 530

8530.300
8530.301
8530.302

8520.300
8520.301
8520.302

without hose F3/8"G F1/2"G
20m - 3/8" (995.520) F3/8"G F3/8"G
25m - 3/8" (995.525) F3/8"G F3/8"G

S. 540

8540.300
8540.301

8550.300
8550.301

without hose F3/8"G F1/2"G
30m - 3/8" (995.530) F3/8"G F3/8"G

S. 560

8560.300
8560.301
8560.302

-
-
-

without hose F3/8"G F1/2"G
40m - 3/8" (995.540) F3/8"G F3/8"G
50m - 3/8" (995.550) F3/8"G F3/8"G



FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





WATER MAX 130°C - 200 bar

STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED




Article

8332.300
8332.301
8333.301

S. 330
hygieninc hose

SWIVELLING



Article

-
-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F 3/8"G
12m - 5/16" (994.512)	F3/8"G	F3/8"G
12m - 5/16" (994.612)	F3/8"G	F3/8"G

8392.300
8392.302
8393.301

S. 390
hygieninc hose

8382.300
8382.302
8383.301

without hose	F3/8"G	F 3/8"G
17m - 5/16" (994.517)	F3/8"G	F3/8"G
12m - 5/16" (994.612)	F3/8"G	F3/8"G

8434.300
8432.301
8432.302
8433.302

S. 430
hygieninc hose

8424.300
8422.301
8422.302
8423.302

without hose	F3/8"G	F1/2"G
12m - 3/8" (995.512)	F3/8"G	F3/8"G
18m - 3/8" (995.518)	F3/8"G	F3/8"G
18m - 3/8" (995.618)	F3/8"G	F3/8"G

for ABS hose reels Series 430 see page 153

8534.300
8532.301
8532.302
8533.302

S. 530
hygieninc hose

8524.300
8522.301
8522.302
8523.302

without hose	F3/8"G	F1/2"G
20m - 3/8" (995.520)	F3/8"G	F3/8"G
25m - 3/8" (995.525)	F3/8"G	F3/8"G
25m - 3/8" (995.625)	F3/8"G	F3/8"G

8544.300
8542.301
8543.301

S. 540
hygieninc hose

8554.300
8552.301
8553.301

without hose	F3/8"G	F1/2"G
30m - 3/8" (995.530)	F3/8"G	F3/8"G
30m - 3/8" (995.630)	F3/8"G	F3/8"G


8564.300
8562.301
8562.302

S. 560

-
-
-


without hose	F3/8"G	F1/2"G
40m - 3/8" (995.540)	F3/8"G	F3/8"G
50m - 3/8" (995.550)	F3/8"G	F3/8"G

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 330	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 390	186	140	196	226	110	400	390	410	20	0,068	from 11 to 18
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40
S. 560	488	399	238	272	368	550	510	578	0	0,310	from 30 to 80

SWIVELLING OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	1-m ³	Kg
S. 380	184	146	106	144	110	400	390	484	0,098	from 12 to 19
S. 420	208	162	118	164	115	460	420	541	0,098	from 15 to 25
S. 520	228	182	154	200	115	560	510	642	0,120	from 20 to 43
S. 550	300	218	226	268	190	560	510	702	0,175	from 25 to 41

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.



WATER MAX 130°C - 400 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

8330.350

SWIVELLING



Article

-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "teflon" seals



S. 330

S. 390

S. 430

S. 530

S. 540

S. 560

8390.350

8390.352

8430.350

8430.352

8530.350

8530.352

8540.350

8560.350

8380.350

8380.352

8420.350

8420.352

8520.350

8520.352

8550.350

-

Hose supplied

without hose

without hose

17m - 5/16" (994.717)

without hose

18m - 3/8" (995.818)

without hose

25m - 3/8" (995.825)

without hose

without hose

Connection

inlet

F3/8"G

outlet

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F1/2"G

F3/8"G

F1/2"G

F3/8"G


F1/2"G

F1/2"G

FIXED HOSE REELS INSTALLATION


The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.



SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





WATER MAX 130°C - 400 bar

STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X


FIXED



Article

8332.350

SWIVELLING



Article

-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "teflon" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F3/8"G



S. 330

S. 390

S. 430

hygieninc hose

S. 530

hygieninc hose

S. 540

S. 560

8392.350

8392.352

8434.350

8432.352

8433.352

8534.350

8532.352

8533.352

8544.350

8564.350

8382.350

8382.352

8424.350

8422.352

8423.352

8524.350

8522.352

8523.352

8554.350

-

without hose

17m - 5/16" (994.717)

without hose

18m - 3/8" (995.818)

18m - 3/8" (995.918)

without hose

25m - 3/8" (995.825)

25m - 3/8" (995.925)

without hose

without hose

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F1/2"G

F3/8"G

F3/8"G

F1/2"G


F3/8"G

F3/8"G

F1/2"G


F1/2"G

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 330	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 390	186	140	196	226	110	400	390	410	20	0,068	from 11 to 18
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40
S. 560	488	399	238	272	368	550	510	578	0	0,310	from 30 to 80

SWIVELLING OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	1-m ³	Kg
S. 380	184	146	106	144	110	400	390	484	0,098	from 12 to 19
S. 420	208	162	118	164	115	460	420	541	0,098	from 15 to 25
S. 520	228	182	154	200	115	560	510	642	0,120	from 20 to 43
S. 550	300	218	226	268	190	560	510	702	0,175	from 25 to 41

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.



WATER MAX 130°C - 100-200-400 bar

AISI 304 STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X


Supplied with:

- AISI 304 stainless steel couplings
- AISI 304 stainless steel swivel joint
- "viton" seals (100-200 bar)
- "teflon" seals (400 bar)


FIXED



SWIVELLING



S. 430



Water 130° C 100 bar

Article 8434.200

Article 8424.200

Connection

inlet

outlet

F1/2"G

F1/2"G

Water 130° C 200 bar

Article 8434.300

Article 8424.300

F3/8"G

F1/2"G

Water 130° C 400 bar

Article 8434.350

Article 8424.350

F3/8"G

F1/2"G

S. 530



Water 130° C 100 bar

Article 8534.200

Article 8524.200

F1/2"G

F1/2"G

Water 130° C 200 bar

Article 8534.300

Article 8524.300

F3/8"G

F1/2"G

Water 130° C 400 bar

Article 8534.350

Article 8524.350

F3/8"G

F1/2"G

S. 540



Water 130° C 100 bar

Article 8544.200

Article 8554.200

F1"G

F1"G

Article 8544.205

Article 8554.205

F1/2"G

F1/2"G

Water 130° C 200 bar

Article 8544.300

Article 8554.300

F3/8"G

F1/2"G

Water 130° C 400 bar

Article 8544.350

Article 8554.350

F3/8"G

F1/2"G

S. 560



Water 130° C 100 bar

Article 8564.200

-

F1"G

F1"G

Article 8564.206

-

F1/2"G

F1/2"G

Water 130° C 200 bar

Article 8564.300

-

F3/8"G

F1/2"G

Water 130° C 400 bar

Article 8564.350

-

F3/8"G

F1/2"G



FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables 55° rotation to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





WATER MAX 130°C - 100 bar

AISI 316 STAINLESS STEEL

Supplied with:

- AISI 316 stainless steel couplings
- AISI 316 stainless steel swivel joint
- "viton" seals



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X



S. 540

Water 130° c 100 bar

FIXED



Article

8545.200

Connection





inlet

outlet

F1"G

F1"G

EXAMPLE OF USE



Hose reel capacity

To establish the **capacity of a hose reel** (max length of hose to be wound) it is necessary to know the following data:

- hose reel spring rewinding capacity
- external diameter of hose to be used


	ø 17 mm	max. 21 m	Series 430
	ø 19,5 mm	max. 16 m	
	ø 22 mm	max. 14 m	

	ø 18,5 mm	max. 28 m	Series 530
	ø 20 mm	max. 26 m	
	ø 22 mm	max. 24 m	

	ø 22 mm	max. 30 m	Series 540 outlet 1/2"
	ø 28 mm	max. 22 m	Series 540 outlet 1"
	ø 34 mm	max. 17 m	


	ø 22 mm	max. 60 m	Series 560 outlet 1/2"
	ø 30 mm	max. 40 m	Series 560 outlet 1"
	ø 35 mm	max. 30 m	

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m³	Kg
S. 430	186	140	196	226	115	460	420	460	20	0,098	16
S. 530	203	153	220	258	115	550	510	560	20	0,120	21
S. 540	300	218	228	268	190	550	510	573	0	0,175	28,5
S. 560	488	399	238	272	368	550	510	578	0	0,310	48

SWIVELLING OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	1-m³	Kg
S. 420	208	162	118	164	115	460	420	541	0,098	16,5
S. 520	228	182	154	200	115	560	510	642	0,120	21,5
S. 550	300	218	226	268	190	560	510	702	0,175	34



OIL AND SIMILAR PRODUCTS - 150 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

8330.400
8330.402

SWIVELLING



Article

-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- carbon steel swivel joint
- "polyurethane" seals



S. 330

S. 390

S. 430

S. 530

S. 540


S. 560

Hose supplied	Connection	
	inlet	outlet
without hose	F1/2"G	F 3/8"-1/2"G
12m - 3/8" (995.312)	F1/2"G	M1/2"G
without hose	F1/2"G	F 3/8"-1/2"G
12m - 3/8" (995.312)	F1/2"G	M1/2"G
17m - 3/8" (995.317)	F1/2"G	M1/2"G
without hose	F1/2"G	F1/2"G
10m - 1/2" (996.310)	F1/2"G	M1/2"G
15m - 1/2" (996.315)	F1/2"G	M1/2"G
for ABS hose reels Series 430 see page 152		
without hose	F1/2"G	F1/2"G
20m - 1/2" (996.320)	F1/2"G	M1/2"G
25m - 1/2" (996.325)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
15m - 3/4" (997.515)	F1"G	M3/4"G
20m - 3/4" (997.520)	F1"G	M3/4"G
15m - 1" (998.515)	F1"G	M1"G
without hose	F1/2"G	F1/2"G
30m - 1/2" (996.330)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
30m - 1" (998.530)	F1"G	M1"G

FIXED HOSE REELS INSTALLATION


The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.



SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





OIL AND SIMILAR PRODUCTS - 150 bar

STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

SWIVELLING



Article

Supplied with:

- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "viton" seals

Hose supplied

Connection

inlet

outlet



S. 390

8392.200

8382.200

without hose

F1/2"G

F 3/8"-1/2"G

S. 430

8434.200

8424.200

without hose

F1/2"G

F1/2"G

for ABS hose reels Series 430 see page 153

S. 530

8534.200

8524.200

without hose

F1/2"G

F1/2"G

S. 540

8544.200


8554.200

without hose

F1"G


F1"G

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 330	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 390	186	140	196	226	110	400	390	410	20	0,068	from 11 to 18
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40
S. 560	488	399	238	272	368	550	510	578	0	0,310	from 30 to 80

SWIVELLING OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	1-m ³	Kg
S. 380	184	146	106	144	110	400	390	484	0,098	from 12 to 19
S. 420	208	162	118	164	115	460	420	541	0,098	from 15 to 25
S. 520	228	182	154	200	115	560	510	642	0,120	from 20 to 43
S. 550	300	218	226	268	190	560	510	702	0,175	from 25 to 41

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.



GREASE - 600 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED




Article

8330.500
8330.501

S. 330

SWIVELLING



Article

-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- carbon steel swivel joint
- "polyurethane" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F3/8"
12m - 1/4" (993.511)	F3/8"G	M1/4"G

S. 390	8390.500	8380.500	without hose	F3/8"G	F3/8"G
	8390.501	8380.501	12m - 1/4" (993.511)	F3/8"G	M1/4"G
	8390.502	8380.502	16m - 1/4" (993.516)	F3/8"G	M1/4"G

S. 430	8430.500	8420.500	without hose	F3/8"G	F1/2"G
	8430.501	8420.501	12m - 1/4" (993.512)	F3/8"G	M1/4"G
	8430.502	8420.502	18m - 1/4" (993.518)	F3/8"G	M1/4"G
	8430.505	8420.505	10m - 3/8" (995.710)	F3/8"G	M1/4"G
	8430.506	8420.506	15m - 3/8" (995.715)	F3/8"G	M1/4"G

for ABS hose reels Series 430 see page 152


S. 530	8530.500	8520.500	without hose	F3/8"G	F1/2"G
	8530.501	8520.501	20m - 3/8" (995.720)	F3/8"G	M1/4"G
	8530.502	8520.502	25m - 3/8" (995.725)	F3/8"G	M1/4"G

S. 540	8540.500	8550.500	without hose	F3/8"G	F1/2"G
	8540.501	8550.501	30m - 3/8" (995.730)	F3/8"G	M1/4"G

FIXED HOSE REELS INSTALLATION


The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.



SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.





GREASE - 600 bar

STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

SWIVELLING



Article

Supplied with:


- zinc plated steel couplings
- carbon steel swivel joint
- "polyurethane" seals

Hose supplied

Connection

inlet

outlet



S. 390

8392.500

8382.500

without hose

F3/8"G

F 3/8"G

S. 430

8432.500

8422.500

without hose

F3/8"G

F1/2"G

for ABS hose reels Series 430 see page 153

S. 530

8532.500


8522.500

without hose

F3/8"G


F1/2"G

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 330	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 390	186	140	196	226	110	400	390	410	20	0,068	from 11 to 18
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40

SWIVELLING OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	1-m ³	Kg
S. 380	184	146	106	144	110	400	390	484	0,098	from 12 to 19
S. 420	208	162	118	164	115	460	420	541	0,098	from 15 to 25
S. 520	228	182	154	200	115	560	510	642	0,120	from 20 to 43

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.



DIESEL FUEL - 10 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Supplied with:

- hoses in antistatic black synthetic rubber
- zinc plated steel couplings
- brass swivel joint
- "viton" seals



Article
8530.600
8530.603
8530.604

S. 530

Hose supplied	Connection	
	inlet	outlet
without hose	F1"G	F1"G
12m - 3/4" (997.812)	F1"G	M3/4"G
8m - 1" (998.808)	F1"G	M1"G

8540.100
8540.601
8540.602
8540.603

S. 540




without hose	F1"G	F1"G
15m - 3/4" (997.815)	F1"G	M3/4"G
20m - 3/4" (997.820)	F1"G	M3/4"G
15m - 1" (998.815)	F1"G	M1"G

8560.100
8560.603
8560.604
8560.605

S. 560

without hose	F1"G	F1"G
40m - 3/4" (997.840)	F1"G	M3/4"G
20m - 1" (998.820)	F1"G	M1"G
30m - 1" (998.830)	F1"G	M1"G

FIXED OVERALL DIMENSIONS




Art.	A	B	C	D	E	F	G	H	I	1-m³	Kg *
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40
S. 560	488	399	238	272	368	550	510	578	0	0,310	from 30 to 80

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.



TEMPLATE



DIESEL FUEL - 10 bar

STAINLESS STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

Supplied with:

- hoses in antistatic black synthetic rubber
- zinc plated steel couplings
- brass swivel joint
- "viton" seals



Hose supplied

Connection

inlet

outlet

8542.100

without hose

F1"G

F1"G

S. 540

8542.601

15m - 3/4" (997.815)

F1"G

M3/4"G

8542.602

20m - 3/4" (997.820)

F1"G

M3/4"G

8542.603

15m - 1" (998.815)

F1"G

M1"G

8562.100

without hose

F1"G

F1"G

S. 560

8562.603

40m - 3/4" (997.840)

F1"G

M3/4"G

8562.604

20m - 1" (998.820)

F1"G


M1"G

8562.605

30m - 1" (998.830)

F1"G

M1"G





ADBLUE - 10 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X



S. 436

FIXED



Article

8436.200

8436.204

8436.205

Supplied with:

- hoses in antistatic EPDM rubber
- AISI 316L stainless steel couplings
- AISI 316L stainless steel swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F1"G	F3/4"G
10m - 19x27 (967.210)	F3/4"G	M3/4"G
15m - 19x27 (967.215)	F3/4"G	M3/4"G

ADBLUE - 10 bar

INOX

FIXED



Article

8537.200

8537.204

8537.205

Supplied with:

- hoses in antistatic EPDM rubber
- AISI 316L stainless steel couplings
- AISI 316L stainless steel swivel joint
- "viton" seals






Hose supplied	Connection	
	inlet	outlet
without hose	F1"G	F3/4"G
10m - 19x27 (967.210)	F3/4"G	M3/4"G
15m - 19x27 (967.215)	F3/4"G	M3/4"G



S. 537

Hose reels for AdBlue, the fluid used in SCR systems which are present in Euro4 and Euro5 trucks, have been purposely designed by using **stainless steel AISI 316L** for those parts which get in contact with the fluid, avoiding in this way any contamination of the same fluid.

FIXED OVERALL DIMENSIONS




Art.	A	B	C	D	E	F	G	H	I	1-m³	Kg
S. 436	337	302	160	203	168	450	420	460	20	0,122	from 19 to 42
S. 537	203	153	220	258	115	550	510	560	0	0,120	from 19 to 42

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel. The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.





SERIES WITH DOUBLE INLET AND OUTLET PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

S. 430



Air - Water **20** bar

8430.1000

Oil - Water **200** bar

8430.3000

Oil - Paint **200** bar

8430.4000

Oil **400** bar

8430.5000

Connection		Equipped with	
inlet	outlet	2 swivels	seals
F1/2"G	M3/8"G	brass	viton
F3/8"G	M3/8"G	AISI 304 stainless steel	viton
F1/2"G	M3/8"G	steel	polyurethane
F3/8"G	M3/8"G	steel	polyurethane

S. 530



Air - Water **20** bar

8530.1000

Oil - Water **200** bar

8530.3000

Oil - Paint **200** bar

8530.4000

Oil **400** bar

8530.5000

F1/2"G	M3/8"G	brass	viton
F3/8"G	M3/8"G	AISI 304 stainless steel	viton
F1/2"G	M3/8"G	steel	polyurethane
F3/8"G	M3/8"G	steel	polyurethane

S. 540




Oil **400** bar

8540.5000

F3/8"G	M3/8"G	steel	polyurethane
--------	--------	-------	--------------

Hose reels for dual hoses can be used for the applications where it is requested **the distribution of two fluids simultaneously** (e.g. air and paint in painting systems) or the recycle of the same fluid (e.g. for hydraulic tools).


FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m³	Kg
S. 430	186	140	196	226	115	460	420	460	20	0,098	17,5
S. 530	203	153	220	258	115	550	510	560	20	0,120	24,5
S. 540	300	218	228	268	190	550	510	573	0	0,175	30

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.





WELDING - 20 bar

PAINTED STEEL




In accordance with directive Atex
94/9 II 3 GD c (T5) 100 °C X

FIXED



Supplied with:

- double hose Standard EN559, hoses SBR/EPDM rubber
- brass fitting
- brass swivel joint
- "viton" seals



S. 430

Article

8430.700

8430.701

8430.702

Hose supplied

without hose

13m - 2x1/4" - 2x6 (973.913)

12m - 2x5/16" - 2x8 (974.912)

Connection

inlet

outlet

M3/8"G

M3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

S. 530

8530.700

8530.701

8530.702

without hose

17m - 2x1/4" - 2x6 (973.917)

20m - 2x1/4" - 2x6 (973.920)

15m - 2x5/16" - 2x8 (974.915)

20m - 2x5/16" - 2x8 (974.920)

15m - 2x3/8" - 2x9 (975.915)

M3/8"G

M3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

S. 540

8540.700

8540.701

8540.702

without hose

25m - 2x1/4" - 2x6 (973.925)

30m - 2x1/4" - 2x6 (973.930)

25m - 2x5/16" - 2x8 (974.925)

30m - 2x5/16" - 2x8 (974.930)

20m - 2x3/8" - 2x9 (975.920)

27m - 2x3/8" - 2x9 (975.927)

M3/8"G

M3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G

F3/8"G




F3/8"G

F3/8"G

F3/8"G

F3/8"G

FIXED OVERALL DIMENSIONS




Art.	A	B	C	D	E	F	G	H	I	1-m³	Kg *
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.





LPG / METHANE - 20 bar

PAINTED STEEL



In accordance with directive Atex
94/9 II 3 GD c (T5) 100 °C X

FIXED



Supplied with:

- orange hose Standard EN559
- brass fitting
- brass swivel joint
- "viton" seals



S. 330

Article
8330.800
8330.801
8330.802

Hose supplied	Connection	
	inlet	outlet
without hose	M3/8"G Sx	M3/8"G Sx
8m - 8x15 (974.1008)	F3/8"G Sx	F3/8"G Sx
10m - 10x17 (975.1010)	F3/8"G Sx	F3/8"G Sx

S. 390

8390.800
8390.801
8390.802

without hose	M3/8"G Sx	M3/8"G Sx
15m - 8x15 (974.1015)	F3/8"G Sx	F3/8"G Sx
15m - 10x17 (975.1015)	F3/8"G Sx	F3/8"G Sx

S. 430

8430.800
8430.802
8430.804

without hose	M3/8"G Sx	M3/8"G Sx
20m - 8x15 (974.1020)	F3/8"G Sx	F3/8"G Sx
18m - 10x17 (975.1018)	F3/8"G Sx	F3/8"G Sx

S. 530

8530.800
8530.802
8530.804




without hose	M3/8"G Sx	M3/8"G Sx
28m - 8x15 (974.1028)	F3/8"G Sx	F3/8"G Sx
27m - 10x17 (975.1027)	F3/8"G Sx	F3/8"G Sx

S. 540

8540.800
8540.802

without hose	M3/8"G Sx	M3/8"G Sx
30m - 10x17 (975.1030)	F3/8"G Sx	F3/8"G Sx

FIXED OVERALL DIMENSIONS




Art.	A	B	C	D	E	F	G	H	I	1-m³	Kg *
S. 330	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 390	186	140	196	226	110	400	390	410	20	0,068	from 11 to 18
S. 430	186	140	196	226	115	460	420	460	20	0,098	from 14 to 24
S. 530	203	153	220	258	115	550	510	560	20	0,120	from 19 to 42
S. 540	300	218	228	268	190	550	510	573	0	0,175	from 24 to 40

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.







HYDRAULIC MOTOR-OPERATED SERIES

S. 617 HYDRAULIC

S. 637 HYDRAULIC

The **adjustable arms** can be easily repositioned according to needs.




HYDRAULIC	Connection	
Article	inlet	outlet

HYDRAULIC	Connection	
Article	inlet	outlet

Air - Water 20 bar - brass swivel joint - "viton" seals	8617.100	F1"G	F1"G	8637.100	F1"G	F1"G
Water max 130° C 100 bar - AISI 304 stainless steel swivel joint - "viton" seals	8617.200	F1"G	F1"G	8637.200	F1"G	F1"G
Oil and similar products 150 bar - carbon steel swivel joint - "polyurethane" seals	8617.400	F1"G	F1"G	8637.400	F1"G	F1"G
Grease 400 bar - carbon steel swivel joint - "polyurethane" seals	8617.500	F1"G	F1"G	8637.500	F1"G	F1"G
Diesel fuel 10 bar - carbon steel swivel joint - "viton" seals	8617.600	F1.1/2"G	F1.1/2"G	8637.600	F1.1/2"G	F1.1/2"G

WALL MOUNTING


After choosing the ideal position, checking the consistency and thickness of the wall, marking the holes for the plugs (see template supplied with the hose reel) and making sure they do not interfere with hydraulic pipes or electrical wires, proceed with drilling. Fix the plugs in the wall and insert the hose reel in the special seats. Tighten the 4 fixing nuts.




HOSE MOUNTING - 1" Connector

Before carrying out the operation, make sure the hose reel drum is locked by means of the parking brake **F**.

Screw one Nipple **N** on the outlet elbow **G**. Apply the hose on Nipple **N**.



HYDRAULIC OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	L	M	1-m ³	Kg
S. 617	283	185	140	130	310	360	220	463	692	570	621	0,310	from 55 to 86
S. 637	467	370	140	130	310	360	400	649	692	570	621	0,473	from 75 to 137





AIR MOTOR-OPERATED SERIES

S. 618 PNEUMATIC

S. 638 PNEUMATIC

The **adjustable arms** can be easily repositioned according to needs.




PNEUMATIC Article	Connection	
	inlet	outlet

Air - Water 20 bar - bras swivel joint - "viton" seals	8618.100	F1"G	F1"G	8638.100	F1"G	F1"G
Water max 130° C 100 bar - AISI 304 stainless steel swivel joint - "viton" seals	8618.200	F1"G	F1"G	8638.200	F1"G	F1"G
Oil and similar products 150 bar - carbon steel swivel joint - "polyurethane" seals	8618.400	F1"G	F1"G	8638.400	F1"G	F1"G
Grease 400 bar - carbon steel swivel joint - "polyurethane" seals	8618.500	F1"G	F1"G	8638.500	F1"G	F1"G
Diesel fuel 10 bar - brass swivel joint - "viton" seals	8618.100	F1"G	F1"G	8638.100	F1"G	F1"G

HOSE MOUNTING - 1.1/2" Connector


Before carrying out the operation, make sure the hose reel drum is locked by means of the brake **F**. Remove the outlet elbow **G**. Screw one Nipple **N** on the outlet elbow **G**. Screw the hose on nipple **N**. Hose with connections 1.1/2" must be connect directly to the elbow **G**. Refit the outlet elbow **G** with the assembled parts.




POWER SUPPLY

The **hydraulic motor-operated hose reels** are fed, by means of a control, by an electric control unit (control and control unit not supplied).

The **air motor-operated hose reels** are fed, by means of a control, with direct connection to the compressed air system (control not supplied).



PNEUMATIC OVERALL DIMENSIONS



HYDRAULIC MOTOR-OPERATED
Oil pressure max 170 bar at
5 l/min inlet feeding

AIR MOTOR-OPERATED HOSE REELS
Air pressure max 7 bar at
2000 l/min inlet feeding

Art.	A	B	C	D	E	F	G	H	I	L	M	1-m ³	Kg
S. 618	283	185	140	130	310	360	220	555	692	570	621	0,310	from 51 to 82
S. 638	467	370	140	130	310	360	400	740	692	570	621	0,473	from 71 to 133



SERIES 500 MANUAL

PAINTED STEEL


Manual rewinding hose reels are an easy and practical way to manage flexible hoses. Operation is extremely simple and needs very little maintenance. Made with high quality materials with a robust frame, manual rewinding hose reels are an inexpensive alternative to spring rewinding hose reels particularly for very long hoses.



	width 240 mm	width 320 mm	width 460 mm	width 600 mm	Connection	
					inlet	outlet
Air - Water 20 bar - brass swivel joint - "viton" seals	7522001.100	7532001.100	7552001.100	7562001.100	1"	1"1
	7522001.150	7532001.150	7552001.150	7562001.150	1/2"	1/2"
Water max 130° C 100 bar - AISI 304 stainless steel swivel joint - "viton" seals	7522001.200	7532001.200	7552001.200	7562001.200	1"	1"
	7522001.250	7532001.250	7552001.250	7562001.250	1/2"	1/2"
Water max 130° C 200 bar - AISI 304 stainless steel swivel joint - "viton" seals	7522001.300	7522001.300	7552001.300	7562001.300	3/8"	1/2"
Oil and similar products 150 bar - carbon steel swivel joint - "polyurethane" seals	7522001.400	7532001.400	7552001.400	7562001.400	1"	1"
	7522001.450	7532001.450	7552001.450	7562001.450	1/2"	1/2"
Oil and similar products 150 bar - carbon steel swivel joint - "polyurethane" seals	7522001.100	7532001.100	7552001.100	7562001.100	1"	1"

Hose reel capacity	L240	L320	L460	L600
 ø 3/8"	50 m	80 m	120 m	160 m
 ø 1/2"	40 m	70 m	105 m	140 m
 ø 3/4"	25 m	40 m	60 m	80 m
 ø 1"	20 m	30 m	45 m	60 m

OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg
L 240	297	373	313	631	242	342	510	555	468	0,208	25,2
L 320	377	373	313	711	322	422	510	555	468	0,243	26,8
L 460	517	373	313	851	462	562	510	555	468	0,304	29,3
L 600	657	373	313	991	602	702	510	555	468	0,365	31,9


Technical features

Stainless steel plate

Clutch control

Clutch in POM material for correct hose winding and rewinding

Reel locking





GROUNDING REEL

Grounding reel satisfies the need to ground fuel tanks during transferring operation in order to discharge electric charges.



APPLICATIONS:


tanks and oil-refinery, aviation, tank truck, boating.




Operation:

Before begin fuel transfer operator must connect the grounding clamp, mounted at the end of the cable, to the grounding plate which is compulsory on every tank truck (Pic. A). As an alternative the grounding reel may be installed on the tank truck and the clamp connected to the grounding plate (Pic. B). Grounding reel must be installed in a safe zone (potentially not dangerous) since it is not provided with Atex Certification. Antiexplosive clamp, standard on some models below listed, may be installed in a potential explosive area (Zone 1) as specified in the CE declaration.

Pic. A




Pic. B



Article	Cable material	Insulation	Cable cross section	Cable length	Grounding clamp
735000	without cable	max cable capacity 30 m - cross section 16 mm ²			
735131.60141	copper	PUR	6 mm ²	14,5 m	antiexplosive 10A
735131.60261	copper	PUR	6 mm ²	26 m	antiexplosive 10A
735131.60152	copper	PUR	6 mm ²	15 m	standard 50A
735131.60252	copper	PUR	6 mm ²	25 m	standard 50A
735141.60152	steel	PVC	7x7 ø 5 mm	15 m	standard 50A
735141.60252	steel	PVC	7x7 ø 5 mm	25 m	standard 50A

OVERALL DIMENSIONS



N°1 packing m³ 0,045
 from kg 10,3 to 11,5

Art. 735111 Standard grounding clamp 100A





SERIES 700 MOTOR-OPERATED AND MANUAL

PAINTED STEEL



...for the complete range of
Industrial hose reels Series 700
please refer to specific brochure



Industrial hose reels series 700 have been designed for fluids delivering in all the heavy applications of industry, mining, building construction, shipyard etc.
They are available in 4 different sizes each of them may be equipped with the following motor: **electric (high or low voltage), pneumatic, hydraulic or manual.**
They can manage hoses with max 2" I D, max length 250 m (with 3/8" hose), suitable for max pressure of 70 bar.



wall bracket for fixed hose reels

quick fit wall brackets supplied on request



Art. 843001



Art. 843002

Art. 843001


Fixed support in steel

for fixed hose reels in painted steel
series 290 - 330 - 390 - 430

Art. 843002

Fixed support in AISI 304 stainless steel

for fixed hose reels in stainless steel and Aisi 304
series 290 - 330 - 390 - 430




Art. 845001

Art. 845001

Fixed support in steel

for fixed enclosed hose reels in painted steel
series 450



Art. 853001



Art. 853002

Art. 853001


Fixed support in steel

for fixed hose reels in painted steel
series 530

Art. 853002

Fixed support in AISI 304 stainless steel

for fixed hose reels in stainless steel and Aisi 304
series 530



Art. 854001



Art. 854002

Art. 854001


Fixed support in steel

for fixed hose reels in painted steel
series 540

Art. 854002

Fixed support in AISI 304 stainless steel

for fixed hose reels in stainless steel and Aisi 304
series 540



Art. 856001



Art. 856002

Art. 856001



Fixed support in steel

for fixed hose reels in painted steel
series 560

Art. 856002

Fixed support in AISI 304 stainless steel

for fixed hose reels in stainless steel and Aisi 304
series 560



The **quick coupling support** that facilitates hooking of the single hose reel and optimises its installation in battery (i.e. with several hose reels side by side) is available by request



swivelling support for fixed hose reels

quick fit swivel brackets supplied on request



Art. 843005




Art. 843006

Art. 843005

Swivelling support in steel
for fixed hose reels in painted steel
series 290 - 330 - 390 - 430

Art. 843006


Swivelling support in AISI 304 stainless steel
for fixed hose reels in stainless steel and Aisi 304
series 290 - 330 - 390 - 430



Art. 845005

Art. 845005

Swivelling support in steel
for fixed enclosed hose reels in painted steel
series 450



Art. 853005




Art. 853006

Art. 853005

Swivelling support in steel
for fixed hose reels in painted steel
series 530

Art. 853006

Swivelling support in AISI 304 stainless steel
for fixed hose reels in stainless steel and Aisi 304
series 530



Art. 854005





Art. 854006

Art. 854005

Swivelling support in steel
for fixed hose reels in painted steel
series 540

Art. 854006

Swivelling support in AISI 304 stainless steel
for fixed hose reels in stainless steel and Aisi 304
series 540



The **quick coupling swivelling support** facilitates hose reel installation and enables 40° rotation to the right or left or locking in fixed positioned at 0° by means of clamping with two screws is available by request



Hoses

technical data

Hose reel outlet hose connections fittings




- Art. **66893** Nipple in carbon steel M 1/2"G x M 1/4"G cylindrical/cylindrical thread
- Art. **33114** Nipple in carbon steel M 1"G x M 1/2"G cylindrical/cylindrical thread
- Art. **33116** Nipple in carbon steel M 1"G x M 1"G cylindrical/cylindrical thread
- Art. **33117** Nipple in carbon steel M 3/4"G x M 3/4"G cylindrical/cylindrical thread
- Art. **33119** Nipple in carbon steel M 1"G x M 3/4"G cylindrical/cylindrical thread
- Art. **33270** Nipple in carbon steel M 1.1/2"G x M 3/4"G cylindrical/cylindrical thread
- Art. **33271** Nipple in carbon steel M 1.1/2"G x M 1"G cylindrical/cylindrical thread
- Art. **33272** Nipple in carbon steel M 1.1/2"G x M 1.1/4"G cylindrical/cylindrical thread
- Art. **33273** Nipple in carbon steel M 1.1/2"G x F 1.1/4"G cylindrical/cylindrical thread
- Art. **33274** Nipple in carbon steel M 1"G x F 1/2"G cylindrical/cylindrical thread
- Art. **38071** Nipple in carbon steel M 1/2"G x M 1/2"G tapered/cylindrical thread
- Art. **38072** Nipple in carbon steel M 1/2"G x M 3/8"G cylindrical/cylindrical thread




- Art. **33128** Nipple in AISI 304 stainless steel M 1"G x M 3/4"G cylindrical/cylindrical thread
- Art. **33129** Nipple in AISI 304 stainless steel M 1"G x M 1"G cylindrical/cylindrical thread
- Art. **33130** Nipple in AISI 304 stainless steel M 3/4"G x M 3/4"G cylindrical/cylindrical thread
- Art. **38120** Nipple in AISI 304 stainless steel M 1/2"G x M 3/8"G cylindrical/cylindrical thread
- Art. **38121** Nipple in AISI 304 stainless steel M 1/2"G x M 1/2"G tapered/cylindrical thread


HOSE REEL OUTLET HOSE CONNECTION




Series 290 - 330 - 380 - 390




Series 420 - 430 - 520 - 530




Series 440 - 450



Series 540-550-560
outlet 1"



Series 540-550-560
outlet 1/2"



Series Welding - Natural Gas

HOSES - TECHNICAL DATA

The range of hoses offered by RAASM for its hose reels is in line with company's quality standards and guarantees excellent performance in the applications with the pressures specified in the catalogue. For conditions different from those recommended, RAASM is available to appraise every aspect of the application context (compatibility of the materials used with the fluid, temperature of use, working pressure, etc.) together with the customer for identifying the right hose for each specific case.



The hoses to be assembled on the hose reels must be suitable for the **working pressures specified on the label**.

HOSE REEL - SYSTEMS EQUIPMENT CONNECTION HOSES TABLE

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet	Pressure	Unions
967.206	0,6m	rubber EPDM antistatic	3/4"	19 x 27	F 3/4"G	M 1"G	10 bar	s/steel AISI 316
971.102	1,5m	polyurethane	5/16"	8 x 12	M 1/4"G	SNODO	20 bar	brass
975.902	1,5m	SBR/EPDM	2 x 3/8"	9 + 9x16	F 3/8"G	F 3/8"G	20 bar	brass
975.1002	1,5m	NBR/PVC	3/8"	10 x 17	F 3/8"G-Sx	F 3/8"G-Sx	20 bar	brass
972.102	1,5m	polyurethane	10 x 14,5	10 x 14,5	M 3/8"G	F 3/8"G	20 bar	brass
976.102	1,5m	polyurethane	13 x 19	13 x 19	F 1/2"G	M 1/2"G	20 bar	brass
993.201	1m	black rubber	1/4"	6,4 x 13	F 1/4"G	M 1/4"G	20 bar	galvanised steel
993.202	2m	black rubber	1/4"	6,4 x 13	F 1/4"G	M 1/4"G	20 bar	galvanised steel
995.206	0,6m	black rubber	3/8"	9,5 x 16	F 3/8"G	M 3/8"G	20 bar	galvanised steel
996.406	0,6m	hygienic cover	1/2"	12,7 x 18,5	F 1/2"G	M 1/2"G	100 bar	galvanised steel
998.406	0,6m	hygienic cover	1"	24,5 x 31,5	F 1"G	M 1"G	100 bar	galvanised steel
996.306	0,6m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G	150 bar	galvanised steel
996.301	1m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G	150 bar	galvanised steel
996.302	2m	black rubber	1/2"	12,7 x 19	F 1/2"G	F 1/2"G	150 bar	galvanised steel
996.304	4m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G	150 bar	galvanised steel
997.505	5m	black rubber	3/4"	19 x 26,5	F 3/4"G	M 3/4"G	150 bar	galvanised steel
998.506	0,6m	black rubber	1"	25,4 x 31,5	F 1"G	M 1"G	150 bar	galvanised steel
998.501	1m	black rubber	1"	25,4 x 31,5	F 1"G	M 1"G	150 bar	galvanised steel
998.502	2m	black rubber	1"	25,4 x 31,5	F 1"G	M 1"G	150 bar	galvanised steel
995.506	0,6m	black rubber	3/8"	9,5 x 17	F 3/8"G	M 3/8"G	200 bar	galvanised steel
995.606	0,6m	hygienic cover	3/8"	9,5 x 17	F 3/8"G	M 3/8"G	200 bar	galvanised steel
995.806	0,6m	black rubber	3/8"	9,5 x 17,5	F 3/8"G	M 3/8"G	400 bar	galvanised steel
995.906	0,6m	hygienic cover	3/8"	9,5 x 17,5	F 3/8"G	M 3/8"G	400 bar	galvanised steel
993.504	4m	black rubber	1/4"	6,3 x 17,5	F 1/4"G	M 1/4"G	600 bar	galvanised steel
995.706	0,6m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 3/8"G	600 bar	galvanised steel
995.701	1m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 3/8"G	600 bar	galvanised steel
995.702	2m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 3/8"G	600 bar	galvanised steel



Hoses

technical data

**Air
Water**
20 bar

Fittings
Galvanised steel
for black rubber hoses

Brass
for polyurethane hoses

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
971.010	10m	polyurethane	1/4"	6 x 10	M 3/8"G	M 1/4"G
971.011	11m	polyurethane	1/4"	6 x 10	M 1/4"G	M 1/4"G
971.015	15m	polyurethane	1/4"	6 x 10	M 3/8"G	M 1/4"G
971.111	11m	polyurethane	5/16"	8 x 12	M 1/4"G	M 1/4"G
971.115	15m	polyurethane	5/16"	6 x 12	M 3/8"G	M 1/4"G
971.118	18m	polyurethane	5/16"	8 x 12	M 3/8"G	M 1/4"G
971.120	20m	polyurethane	5/16"	8 x 12	M 3/8"G	M 1/4"G
972.113	13m	polyurethane	3/8"	10 x 14,5	M 3/8"G	M 3/8"G
972.115	15m	polyurethane	3/8"	10 x 14,5	M 3/8"G	M 3/8"G
972.120	20m	polyurethane	3/8"	10 x 14,5	M 3/8"G	M 3/8"G
976.108	8m	polyurethane	1/2"	13 x 19	M 1/2"G	M 1/2"G
976.110	10m	polyurethane	1/2"	13 x 19	M 1/2"G	M 1/2"G
976.111	10m	polyurethane	1/2"	13 x 19	F 1/2"G	M 1/2"G
976.112	12m	polyurethane	1/2"	13 x 19	M 1/2"G	M 1/2"G
976.114	15m	polyurethane	1/2"	13 x 19	M 1/2"G	M 1/2"G
976.115	15m	polyurethane	1/2"	13 x 19	F 1/2"G	M 1/2"G
993.215	15m	black rubber	1/4"	6,5 x 12,6	M 3/8"G	M 1/4"G
995.210	10m	black rubber	3/8"	9,5 x 17	M 3/8"G	M 3/8"G
995.211	12m	black rubber	3/8"	9,5 x 16	M 3/8"G	M 3/8"G
995.212	12m	black rubber	3/8"	9,5 x 16	F 3/8"G	M 3/8"G
995.217	18m	black rubber	3/8"	9,5 x 16	M 3/8"G	M 3/8"G
995.218	18m	black rubber	3/8"	9,5 x 16	F 3/8"G	M 3/8"G
996.210	10m	black rubber	1/2"	12,7 x 20	F 1/2"G	M 1/2"G
996.215	15m	black rubber	1/2"	12,7 x 20	F 1/2"G	M 1/2"G
996.220	20m	black rubber	1/2"	12,7 x 20	F 1/2"G	M 1/2"G
996.225	25m	black rubber	1/2"	12,7 x 20	F 1/2"G	M 1/2"G
996.230	30m	black rubber	1/2"	12,7 x 20	F 1/2"G	M 1/2"G
997.215	15m	black rubber	3/4"	19 x 26,5	F 3/4"G	M 3/4"G
997.220	20m	black rubber	3/4"	19 x 26,5	F 3/4"G	M 3/4"G
997.230	30m	black rubber	3/4"	19 x 26,5	F 3/4"G	M 3/4"G
997.240	40m	black rubber	3/4"	19 x 26,5	F 3/4"G	M 3/4"G
998.215	15m	black rubber	1"	25,4 x 32,5	F 1"G	M 1"G
998.220	20m	black rubber	1"	25,4 x 32,5	F 1"G	M 1"G
998.230	30m	black rubber	1"	25,4 x 32,5	F 1"G	M 1"G

Water
max 130° C
100 bar

Fittings
Galvanised steel

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
995.313	12m	black rubber	3/8"	9,5 x15	M 3/8"G	M 3/8"G
995.318	17m	black rubber	3/8"	9,5 x15	M 3/8"G	M 3/8"G
995.412	12m	hygieninc cover	3/8"	9,5 x15	M 3/8"G	M 3/8"G
996.311	10m	black rubber	1/2"	12,7 x 18,5	F 1/2"G	M 1/2"G
996.316	15m	black rubber	1/2"	12,7 x 18,5	F 1/2"G	M 1/2"G
996.321	20m	black rubber	1/2"	12,7 x 18,5	F 1/2"G	M 1/2"G
996.415	15m	hygienic cover	1/2"	12,7 x 18,5	F 1/2"G	M 1/2"G
996.425	25m	hygienic cover	1/2"	12,7 x 18,5	F 1/2"G	M 1/2"G
997.320	20m	black rubber	3/4"	19 x 25	F 3/4"G	M 3/4"G
997.420	20m	hygienic cover	3/4"	19 x 25	F 3/4"G	M 3/4"G
998.315	15m	black rubber	1"	25,4 x 31,5	F 1"G	M 1"G
998.330	30m	black rubber	1"	25,4 x 31,5	F 1"G	M 1"G



Hoses technical data

Water
max 130° C
200 bar

Fittings
Galvanised steel

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
994.512	12m	black rubber	5/16"	8 x 15	M 3/8"G	F 3/8"G
994.517	17m	black rubber	5/16"	8 x 15	M 3/8"G	F 3/8"G
994.612	12m	hygienic cover	5/16"	8 x 15	M 3/8"G	F 3/8"G
995.512	12m	black rubber	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.518	18m	black rubber	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.520	20m	black rubber	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.525	25m	black rubber	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.530	30m	black rubber	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.540	40m	black rubber	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.550	50m	black rubber	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.618	18m	hygienic cover	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.625	25m	hygienic cover	3/8"	9,5 x 17	F 3/8"G	F 3/8"G
995.630	30m	hygienic cover	3/8"	9,5 x 17	F 3/8"G	F 3/8"G

Water
max 130° C
400 bar

Fittings
Galvanised steel

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
994.717	17m	black rubber	5/16"	8 x 16	M 3/8"G	F 3/8"G
995.818	18m	black rubber	3/8"	9,5 x 17,5	F 3/8"G	F 3/8"G
995.825	25m	black rubber	3/8"	9,5 x 17,5	F 3/8"G	F 3/8"G
995.918	18m	hygienic cover	3/8"	9,5 x 17,5	F 3/8"G	F 3/8"G
995.925	25m	hygienic cover	3/8"	9,5 x 17,5	F 3/8"G	F 3/8"G

Oil and similar
products
150 bar

Fittings
Galvanised steel

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
995.312	12m	black rubber	3/8"	9,5 x 17	M 3/8"G	M 1/2"G
995.317	17m	black rubber	3/8"	9,5 x 17	M 3/8"G	M 1/2"G
996.310	10m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G
996.315	15m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G
996.320	20m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G
996.325	25m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G
996.330	30m	black rubber	1/2"	12,7 x 19	F 1/2"G	M 1/2"G
997.515	15m	black rubber	3/4"	19 x 26,5	F 3/4"G	M 3/4"G
997.520	20m	black rubber	3/4"	19 x 26,5	F 3/4"G	M 3/4"G
998.515	15m	black rubber	1"	25,4 x 35,5	F 1"G	M 1"G
998.530	30m	black rubber	1"	25,4 x 35,5	F 1"G	M 1"G

Grease
600 bar

Fittings
Galvanised steel

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
993.511	12m	black rubber	1/4"	6,3 x 17,5	M 3/8"G	M 1/4"G
993.512	12m	black rubber	1/4"	6,3 x 17,5	F 1/4"G	M 1/4"G
993.516	16m	black rubber	1/4"	6,3 x 17,5	M 3/8"G	M 1/4"G
993.518	18m	black rubber	1/4"	6,3 x 17,5	F 1/4"G	M 1/4"G
995.710	10m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 1/4"G
995.715	15m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 1/4"G
995.720	20m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 1/4"G
995.725	25m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 1/4"G
995.730	30m	black rubber	3/8"	9,5 x 18	F 3/8"G	M 1/4"G



Hoses technical data

Diesel fuel
10 bar

Fittings
Galvanised steel

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
997.812	12m	black rubber	3/4"	19 x 27	F 1/2"G	M 1/2"G
997.815	15m	black rubber	3/4"	19 x 27	F 3/4"G	M 3/4"G
997.820	20m	black rubber	3/4"	19 x 27	F 3/4"G	M 3/4"G
997.840	40m	black rubber	3/4"	19 x 27	F 3/4"G	M 3/4"G
998.808	8m	black rubber	1"	25 x 35	F 1"G	M 1"G
998.815	15m	black rubber	1"	25 x 35	F 1"G	M 1"G
998.820	20m	black rubber	1"	25 x 35	F 1"G	M 1"G
998.830	30m	black rubber	1"	25 x 35	F 1"G	M 1"G

AdBlue
10 bar

Fittings
AISI 316
Stainless steel

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
967.210	10m	rubber EPDM antistatic	3/4"	19 x 27	F 3/4"G	M 3/4"G
967.215	15m	rubber EPDM antistatic	3/4"	19 x 27	F 3/4"G	M 3/4"G

Welding
20 bar
EN 559

Fittings
Brass

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
973.913	13m	SBR/EPDM	2x1/4"	6,3 + 6,3x13	F 3/8"G	M 3/8"G
973.917	17m	SBR/EPDM	2x1/4"	6,3 + 6,3x13	F 3/8"G	F 3/8"G
973.920	20m	SBR/EPDM	2x1/4"	6,3 + 6,3x13	F 3/8"G	F 3/8"G
973.925	25m	SBR/EPDM	2x1/4"	6,3 + 6,3x13	F 3/8"G	F 3/8"G
973.930	30m	SBR/EPDM	2x1/4"	6,3 + 6,3x13	F 3/8"G	F 3/8"G
974.912	12m	SBR/EPDM	2x5/16"	8 + 8x15	F 3/8"G	F 3/8"G
974.915	15m	SBR/EPDM	2x5/16"	8 + 8x15	F 3/8"G	F 3/8"G
974.920	20m	SBR/EPDM	2x5/16"	8 + 8x15	F 3/8"G	F 3/8"G
974.925	25m	SBR/EPDM	2x5/16"	8 + 8x15	F 3/8"G	F 3/8"G
974.930	30m	SBR/EPDM	2x5/16"	8 + 8x15	F 3/8"G	F 3/8"G
975.915	15m	SBR/EPDM	2x3/8"	9 + 9x16	F 3/8"G	F 3/8"G
975.920	20m	SBR/EPDM	2x3/8"	9 + 9x16	F 3/8"G	F 3/8"G
975.927	27m	SBR/EPDM	2x3/8"	9 + 9x16	F 3/8"G	F 3/8"G

Lpg and
Natural gas
20 bar
EN 559

Fittings
Brass

Article	Hose length	Hose characteristics	ø Hose	Dimensions	Inlet	Outlet
974.1008	8m	NBR/PVC	5/16"	8 x 15	F 3/8"G-Sx	F 3/8"G-Sx
974.1015	15m	NBR/PVC	5/16"	8 x 15	F 3/8"G-Sx	F 3/8"G-Sx
974.1020	20m	NBR/PVC	5/16"	8 x 15	F 3/8"G-Sx	F 3/8"G-Sx
974.1028	28m	NBR/PVC	5/16"	8 x 15	F 3/8"G-Sx	F 3/8"G-Sx
975.1010	10m	NBR/PVC	3/8"	10 x 17	F 3/8"G-Sx	F 3/8"G-Sx
975.1015	15m	NBR/PVC	3/8"	10 x 17	F 3/8"G-Sx	F 3/8"G-Sx
975.1018	18m	NBR/PVC	3/8"	10 x 17	F 3/8"G-Sx	F 3/8"G-Sx
975.1027	27m	NBR/PVC	3/8"	10 x 17	F 3/8"G-Sx	F 3/8"G-Sx
975.1030	30m	NBR/PVC	3/8"	10 x 17	F 3/8"G-Sx	F 3/8"G-Sx




INDUSTRIAL PUMPS





RAASM INDUSTRIAL
FLUIDS AND LUBRICATION EQUIPMENT

Industrial Pumps



INTRODUCTION

page 190



PUMPS FOR OILS AND SIMILAR PRODUCTS

page 196



HIGH FLOW PUMPS FOR OIL AND SIMILAR PRODUCTS

page 200



GREASE PUMPS

page 202



PUMPS FOR INDUSTRIAL FLUIDS

page 206



AISI 304 STAINLESS STEEL PUMPS

page 208



ACCESSORIES

page 210



PUMP ELEVATORS AND RAM

page 212



Total Quality



Innovative design for optimising the pump work cycle.
The result of years of research and development, during which numerous tests were carried out for thousands of work hours.

High quality materials used, cutting-edge processes, hardening and grinding for reducing internal friction and limiting wear.

Fewer moving parts for easy and occasional maintenance with savings in running costs.

The industrial pumps guarantee high efficiency in capacity and operating pressure.

Double action ensures a continuous and constant flow of the fluid delivered.

Versatility

INTEGRAL INDUSTRIAL PUMPS



Air motor and pumping unit form a single body. They are recommended for transferring non-corrosive fluids, oil and allied products.

FLANGED INDUSTRIAL PUMPS



Air motor and pumping unit form a single body. They are recommended for transferring non-corrosive fluids, oil and allied products. The motor base is flanged to enable application of the handles which are useful for easy moving and for simple fixing in various other applications.

DIVORCED INDUSTRIAL PUMPS




Air motor and pumping unit are separate so that the fluid cannot come into direct contact with the motor body. They are recommended for transferring non-aggressive industrial and chemical fluids. The motor base is flanged to enable application of the handles which are useful for easy moving and for simple fixing in various other applications.


The **integral pumps** and **flanged pumps** are available in the drum version and modular version (modular = extendable with a rigid suction tube, or in the wall application with a flexible suction tube)




Examples of industrial pump applications




Stations for continuous feed of machinery by means of distribution of fluids in line (lubricants, inks, adhesives, etc.) with pump connected to the tank or fixed to the floor with bracket.



Automated system for the delivery of preselected quantities of fluids (inks, paints, greases, etc.), fed by pumps mounted on drum, with lift.



Application of sealants, adhesives, greases, etc., by means of special delivery gun fed by pump mounted on drum in fixed or mobile station.




Fluid distribution system (for paints, lubricants, protective liquids, etc.) fed by pump mounted on drum in fixed station and delivery with spray gun.




Industrial pump installations on tanks or drums


For tank with pump in vertical position mounted on bracket




For tank with pump in vertical position mounted on floor with bracket




For tank with pump in horizontal position




For tank with pump in inclined position




For 200 kg drum, with double ram hoist and follower




For 200 kg drums, standard application




Industrial pumps installed on vertical bulk containers



Industrial pumps installed on pedestals connected to horizontal bulk containers





Bank of pumps connected with bulk containers





...everything for mining
technology, functionality, safety







Air-operated INDUSTRIAL PUMPS

oil and similar products

Ratio **5:1**
Flow rate **45 l/min**

Double action series 900 air-operated industrial pumps for distribution.

Suitable for transferring oils, lubricants and similar products, also high viscosity. The double action guarantees the delivery of a continuous and constant flow. Ideal for every needs. Particularly effective in systems equipped with several dispensing points.



series **900**

Article with seals in **PU**

Compatible fluids	
Suction tube upper body	
Suction tube	
Air inlet connection	bsp
Fluid outlet connection	bsp
Max. air consumption 8 bar	m ³ /min
Noise level	dB
Air max. feed pressure	bar

Suitable for drums or tanks

Packing	N° - m ³
Weight	Kg
Dimensions (A - B - C)	cm



integral

90C/51

flanged

90F/51


Oils, lubricants and similar
Aluminium
Carbon steel




modular







modular




Ratio **7:1**
Flow rate **30 l/min**



series **900**

integral	integral	integral	integral	flanged	flanged
90C/71	93C/71	91C/71	92C/71	90F/71	91F/71
Oils, lubricants and similar				Oils, lubricants and grease	
Aluminium				Carbon steel	
Carbon steel				Carbon steel	
F 1/2"	F 1/2"	F 1/2"	F 1/2"	F 1/2"	F 1/2"
F 3/4"	F 3/4"	F 3/4"	F 3/4"	F 3/4"	F 3/4"
1,6	1,6	1,6	1,6	1,6	1,6
80	80	80	80	80	80
8	8	8	8	8	8
					
modular	suitable for drums 50-60 Kg	suitable for drums 180-220 Kg	tank	modular	suitable for drums 180-220 Kg
1 - 0,040	1 - 0,080	1 - 0,080	1 - 0,080	1 - 0,040	1 - 0,070
11	13,5	14,5	15	12	14
43 - 27 - 5,3	43 - 74 - 5,3	43 - 94 - 5,3	43 - 126 - 5,3	44,5 - 27 - 5,3	44,5 - 94 - 5,3






Air-operated INDUSTRIAL PUMPS



oil and similar products

Ratio **11:1**
Flow rate **30 l/min**

Double action series 900 and 1200 air-operated industrial pumps for distribution.

Suitable for transferring oils, lubricants and similar products, also high viscosity. The double action guarantees the delivery of a continuous and constant flow. Ideal for every needs. Particularly effective in systems equipped with several dispensing points.




Article with seals in	PU	90C/111	92C/111	91C/111
Compatible fluids		Oils, lubricants and grease		
Suction tube upper body		Aluminium		
Suction tube		Carbon steel		
Air inlet connection	bsp	F 1/2"	F 1/2"	F 1/2"
Fluid outlet connection	bsp	F 3/4"	F 3/4"	F 3/4"
Max. air consumption 8 bar	m ³ /min	1,7	1,7	1,7
Noise level	dB	80	80	80
Air max. feed pressure	bar	8	8	8
Suitable for drums or tanks		 modular	 suitable for drums 50-60 Kg	 suitable for drums 180-220 Kg
Packing	 N° - m ³	1 - 0,040	1 - 0,070	1 - 0,070
Weight	 Kg	11	15	16
Dimensions (A - B - C)	cm	43 - 27 - 4,5	43 - 74 - 4,5	43 - 94 - 4,5



series 900

integral










Ratio **9:1**
Flow rate **45 l/min**

Ratio **12:1**
Flow rate **30 l/min**

Ratio **18:1**
Flow rate **23 l/min**



series 900		series 1200		series 1200		series 1200	
flanged		flanged		flanged		flanged	
90F/111	91F/111	115F/91		115F/121	116F/121	115F/181	116F/181
Oils, lubricants and grease		Oils, lubricants and similar		Oils, lubricants and similar		Oils, lubricants and grease	
Carbon steel Carbon steel		Carbon steel Carbon steel		Carbon steel Carbon steel		Carbon steel Carbon steel	
F 1/2"	F 1/2"	F 1/2"		F 1/2"	F 1/2"	F 1/2"	F 1/2"
F 3/4"	F 3/4"	F 3/4"		F 3/4"	F 3/4"	F 3/4"	F 3/4"
1,7	1,7	2,8		2,8	2,8	2,8	2,8
80	80	80		80	80	80	80
8	8	8		8	8	8	8
							
1 - 0,045	1 - 0,070	1 - 0,40		1 - 0,040	1 - 0,070	1 - 0,045	1 - 0,070
13	17	14		13	15	15,5	18
44,5 - 48 - 4,5	44,5 - 94 - 4,5	44,5 - 23 - 6,2		44,5 - 23 - 5,3	44,5 - 94 - 5,3	44,5 - 48 - 4,5	44,5 - 94 - 4,5





Air-operated INDUSTRIAL PUMPS

oil and similar products

Ratio **2:1**
Flow rate **95 l/min**

Ratio **3:1**
Flow rate **100 l/min**



Series 900, 1200, 1500 and 1800 industrial air-operated pumps for medium-long distance distribution. Suitable for transferring oils, lubricants and similar products, they guarantee high performance in capacity (l/min) and operating pressure. The version with viton seals can also be used for the transfer of industrial and chemical fluids. The high quality of the components ensures lasting and reliable operation even in extreme conditions.



200



Article with seals in PU	90D/21		115D/31	
Article with seals in VITON		90DV/21		115DV/31
Compatible fluids	Oils, lubricants and similar	Chemical and industrial fluids	Oils, lubricants and similar	Chemical and industrial fluids
Suction tube upper body	Carbon steel		Carbon steel	
Suction tube	Carbon steel		Carbon steel	
Air inlet connection	bsp	F 1/2"	F 1/2"	F 1/2"
Fluid outlet connection	bsp	F 1.1/2"	F 1.1/2"	F 1.1/2"
Max. air consumption 8 bar	m ³ /min	1,6	1,6	2,8
Noise level	dB	80	80	80
Air max. feed pressure	bar	8	8	8

Suitable for drums or tanks



Packing	N° - m ³	1 - 0,20	1 - 0,20	1 - 0,20	1 - 0,20
Weight	Kg	45	45	46	46
Dimensions (A - B - C)	cm	36 - 62,5 - 16,2	36 - 62,5 - 16,2	36 - 62,5 - 16,2	36 - 62,5 - 16,2

PUMP AIR FEEDING PRESSURE
A 8 bar 116 psi
B 6 bar 87 psi
C 4 bar 58 psi





Air-operated INDUSTRIAL PUMPS grease



Ratio **45:1**
Flow rate **4400 g/min**



Series 900 - 1200 industrial air-operated pumps for medium-long distance distribution. Suitable for the transfer of medium-high viscosity oils and greases. The high quality of the components ensures lasting and reliable operation even in extreme conditions whereas the double action guarantees the delivery of a continuous and constant flow. Particularly effective in systems equipped with several dispensing points.



series 900


flanged

Article with seals in	PU	90FSP/451	90F/451	92F/451	91F/451
Compatible fluids		High viscosity oils and greases			
Suction tube upper body		Carbon steel			
Suction tube		Carbon steel			
Air inlet connection	bsp	F 1/2"	F 1/2"	F 1/2"	F 1/2"
Fluid outlet connection	bsp	F 1/2"	F 1/2"	F 1/2"	F 1/2"
Max. air consumption 8 bar	m ³ /min	1,6	1,6	1,6	1,6
Noise level	dB	80	80	80	80
Air max. feed pressure	bar	8	8	8	8
Suitable for drums or tanks		 pump elevator	 tank	 suitable for drums 50-60 Kg	 suitable for drums 180-220 Kg
Packing	N° - m ³	1 - 0,085	1 - 0,045	1 - 0,070	1 - 0,070
Weight	Kg	16	16	18	19
Dimensions (A - B - C)	cm	44,5 - 50 - 4,5	44,5 - 50 - 4,5	44,5 - 74 - 4,5	44,5 - 94 - 4,5



Ratio **70:1**
Flow rate **3000 g/min**

Ratio **75:1**
Flow rate **4400 g/min**



series 900

integral

92C/701

91C/701

High viscosity oils and greases

Aluminium

Carbon steel

F 1/2"

F 1/2"

1,6

1,6

80

80

8

8



1 - 0,070

1 - 0,070

18

19

43 - 74 - 4,5

43 - 94 - 4,5

series 1200

flanged

115FSP/751

115F/751

117F/751

116F/751

High viscosity oils and greases

Carbon steel

Carbon steel

F 1/2"

F 1/2"

F 1/2"

F 1/2"

2,8

2,8

2,8

2,8

80

80

80



80

8

8

8

8



1 - 0,045

1 - 0,045

1 - 0,070

1 - 0,070

18

18

20



21

44,5 - 50 - 4,5

44,5 - 50 - 4,5

44,5 - 74 - 4,5

44,5 - 94 - 4,5





Air-operated INDUSTRIAL PUMPS grease


Ratio **40:1**
Flow rate **10000 g/min**

Series 1200 and 1500 industrial air-operated pumps for medium-long distance distribution.

Suitable for transferring oils, lubricants and allied products, they guarantee high performance in capacity (l/min) and operating pressure.

The version with viton seals can also be used for the transfer of industrial and chemical fluids.

The high quality of the components ensures lasting and reliable operation even in extreme conditions.



Article with seals in	PU
Compatible fluids	
Suction tube upper body	
Suction tube	
Air inlet connection	bsp
Fluid outlet connection	bsp
Max. air consumption 8 bar	m ³ /min
Noise level	dB
Air max. feed pressure	bar

Suitable for drums or tanks




Packing	N° - m ³
Weight	Kg
Dimensions (A - B - C)	cm


Art. 10/09
Adaptor for integral and flanged pumps series 900 and 1200, for application with other brackets



series **1200**

flanged

	118FSP/401	118F/401	115F/401
Compatible fluids	High viscosity oils and greases		
Suction tube upper body	Carbon steel		
Suction tube	Carbon steel		
Air inlet connection	F 1/2"	F 1/2"	F 1/2"
Fluid outlet connection	F 1/2"	F 1/2"	F 1/2"
Max. air consumption 8 bar	2,8	2,8	2,8
Noise level	80	80	80
Air max. feed pressure	8	8	8
	 pump elevator	 tank	 suitable for drums 50-60 Kg
Packing	1 - 0,090	1 - 0,090	1 - 0,090
Weight	21	21	23
Dimensions (A - B - C)	44,5 - 60 - 5,08	44,5 - 60 - 5,08	44,5 - 74 - 5,08



Ratio **70:1**
Flow rate **7000 g/min**



series **1200**

flanged

117F/401

116F/401

High viscosity oils and greases

Carbon steel

Carbon steel

F 1/2"

F 1/2"

F 1/2"

F 1/2"

2,8


2,8

80


80

8

8



tank



suitable for drums
180-200 Kg

1 - 0,090

1 - 0,090

24

25

44,5 - 86 - 5,08

44,5 - 94 - 5,08

series **1500**

flanged

153FSP/701

153F/701

150F/701

152F/701

151F/701

High viscosity oils and greases

Carbon steel

Carbon steel

F 1/2"

F 1/2"

F 1/2"

F 1/2"

F 1/2"

F 1/2"

F 1/2"

F 1/2"

F 1/2"

F 1/2"

4,3

4,3

4,3

4,3

4,3

80

80

80

80

80


8

8


8

8


8



pump elevator



tank



suitable for drums
50-60 Kg

1 - 0,20

1 - 0,20

31

32



50 - 74 - 5,08

50 - 86 - 5,08

1 - 0,20

33

50 - 94 - 5,08





Air-operated INDUSTRIAL PUMPS

industrial fluids

Series 900 and 1200 divorced industrial air-operated pumps for medium-long distance distribution.

The divorced version, with teflon seals, can also be used for the transfer of industrial and chemical fluids. The high quality of the components ensures lasting and reliable operation even in extreme conditions.



Article with seals in **TEFLON**

Compatible fluids	
Suction tube upper body	
Suction tube	
Air inlet connection	bsp
Fluid outlet connection	bsp
Max. air consumption 8 bar	m ³ /min
Noise level	dB
Air max. feed pressure	bar

Suitable for drums or tanks

Packing	N° - m ³
Weight	Kg
Dimensions (A - B - C)	cm

PUMP AIR FEEDING PRESSURE	
A	8 bar 116 psi
B	6 bar 87 psi
C	4 bar 58 psi

Ratio **5:1**
Flow rate **45 l/min**

Ratio **7:1**
Flow rate **30 l/min**



series **900**

divorced

90D/51

Chemical and industrial fluids

Carbon steel

Carbon steel

F 1/2"

F 3/4"

1,6

80


8

modular

1 - 0,045

14,5

36 - 48 - 6,2



series **900**

divorced

90D/71

Chemical and industrial fluids

Carbon steel

Carbon steel

F 1/2"

F 3/4"

1,6

80


8

modular

1 - 0,045

13,5

36 - 48 - 5,3



Ratio **11:1**
Flow rate **30 l/min**

Ratio **9:1**
Flow rate **45 l/min**

Ratio **12:1**
Flow rate **30 l/min**

Ratio **18:1**
Flow rate **23 l/min**



series **900**

series **1200**

series **1200**

series **1200**

divorced

divorced

divorced

divorced

90D/111

115D/91

115D/121

115D/181

Chemical and industrial fluids

Chemical and industrial fluids

Chemical and industrial fluids

Chemical and industrial fluids

Carbon steel

Carbon steel

Carbon steel

Carbon steel

Carbon steel

Carbon steel

Carbon steel

Carbon steel

F 1/2"

F 1/2"

F 1/2"

F 1/2"

F 3/4"

F 3/4"

F 3/4"

F 3/4"

1,7

2,8

2,8

2,8

80

80

80


80

8


8

8


8




modular



modular



modular



modular

1 - 0,045

1 - 0,045

1 - 0,045

1 - 0,045

13

15,5

14,5


14

36 - 48 - 4,5


36 - 48 - 6,2

36 - 48 - 5,3


36 - 48 - 4,5




KIND OF FLUID: SAE30 oil (ISO VG 100) - 20 °C



KIND OF FLUID: SAE30 oil (ISO VG 100) - 20 °C



KIND OF FLUID: SAE30 oil (ISO VG 100) - 20 °C




KIND OF FLUID: SAE30 oil (ISO VG 100) - 20 °C




S/Steel AISI 304 pumps for short-medium distance TRANSFER

Ratio **1:1**
Flow rate **30 l/min**



Ideal for transferring low-medium viscosity fluids such as: antifreeze liquid, windshield washing liquid and chemical products.



Article with seals in **VITON**

Compatible fluids	
Suction tube upper body	
Suction tube	
Air inlet connection	bsp
Fluid outlet connection	bsp
Max. air consumption 8 bar	m ³ /min
Noise level	dB
Air max. feed pressure	bar

Suitable for drums or tanks

Packing	N° - m ³
Weight	Kg
Dimensions (A - B - C)	cm

Art. 33440
Gun for antifreeze and
windshield liquid with
stainless steel rigid
terminal



series **600 INOX**

divorced

33360

divorced

33396

Suitable for antifreeze and windshield washing liquid

Stainless steel AISI 304

Stainless steel AISI 304

F 1/4" G

F 1/4" G

F 1/2" G

F 1/2" G

0,37


0,37

81

81

6 - 8

6 - 8



modular



suitable for drums
180-220 Kg

1 - 0,10

1 - 0,020


5,3

7,4

41 - 0 - 0

41 - 94 - 3,4

PUMP AIR
FEEDING
PRESSURE
A 8 bar
116 psi
B 6 bar
87 psi
C 4 bar
58 psi



KIND OF FLUID: windshield washing fluid with water



Air-operated INDUSTRIAL PUMPS S/STEEL AISI 304

industrial fluids

Series 900 - 1200 divorced stainless steel AISI 304 industrial air-operated pumps for medium-long distance distribution. They are suitable to transfer aggressive fluids compatible with the wet parts of the pump (stainless steel and teflon). The high quality of the components ensures lasting and reliable operation even in extreme conditions.



Article with seals in **TEFLON**
TEFLON+UHMW-PE

Compatible fluids	
Suction tube upper body	Stainless steel AISI 304
Suction tube	Stainless steel AISI 304
Air inlet connection	bsp
Fluid inlet connection	bsp
Fluid outlet connection	bsp
Max. air consumption 8 bar	m ³ /min
Noise level	dB
Air max. feed pressure	bar

Suitable for drums or tanks

Packing	N° - m ³
Weight	Kg
Dimensions (A - B - C)	cm

PUMP AIR FEEDING PRESSURE	
A	8 bar 116 psi
B	6 bar 87 psi
C	4 bar 58 psi

Ratio **6:1**
Flow rate **42 l/min**

Ratio **9:1**
Flow rate **42 l/min**



series **900**

divorced

94D/61

95D/61

Chemical and industrial fluids
Stainless steel AISI 304
Stainless steel AISI 304
F 1/2"
F 1.1/4"
F 1"
F 3/4"
1,6
1,6
80
80
8
8



modular



modular



series **1200**



divorced

120D/91

Chemical and industrial fluids
Stainless steel AISI 304
Stainless steel AISI 304
F 1/2"
F 1"
F 3/4"
2,8
2,8
80
80
8
8




modular








Accessories for industrial pumps




Art. 10/10
Wall bracket in painted steel for wall-mounting of integral and flanged industrial pumps, series 900 and 1200




Art. 10/18
Wall bracket in painted steel with dampers for wall-mounting of divorced industrial pumps, with suction tube Ø 100 mm, series 900 and 1200




Art. 10/11
Wall bracket in painted steel with dampers for wall-mounting of integral and flanged industrial pumps, series 900 and 1200



Art. 33115
Wall bracket in steel for wall-mounting of transfer pumps, series 600 and 650




Art. 10/12
Wall bracket in painted steel for wall-mounting of divorced industrial pumps, series 900 and 1200





Art. 10/14
Bung adaptor, for industrial pumps with suction tube, ø 45 mm series 900 and 1200


Art. 10/15
Bung adaptor, for industrial pumps with suction tube, ø 53 mm series 900 and 1200




Art. 10/13
Wall bracket in painted steel with dampers for wall-mounting of divorced industrial pumps, series 900 and 1200



Art. 33434
Bung adaptor ø 34 mm, with double body for pumps with suction tube, series 600



Art. 10/17
Wall bracket in painted steel with dampers for wall-mounting of flanged industrial pumps, series 1500 and 1800




Art. 10/09
Adaptor for integral and flanged pumps series 900 e 1200, for application with other brackets



Accessories for industrial pumps

Union ø 45 mm



Drum cover for pumps with suction tube ø 45

Art. 10/50 Drum cover ø 600 mm for drums 180 - 220 Kg
(drums external ø 550 - 600 mm)

Art. 10/51 Drum cover ø 420 mm for drums 50 - 60 Kg
(drums external ø 370 - 420 mm)

Art. 10/52 Drum cover ø 385 mm for drums 30 - 50 Kg
(drums external ø 340 - 385 mm)



Follower plate for pumps S. 900 - 1200 with suction tube ø 45

Art. 10/60 Follower plate ø 585 mm for drums 180 - 220 Kg
(drums internal ø 540 - 580 mm)

Art. 10/61 Follower plate Ø 400 mm for drums 50 - 60 Kg
(drums internal ø 360 - 400 mm)

Art. 10/62 Follower plate Ø 370 mm for drums 30 - 50 Kg
(drums internal ø 335 - 360 mm)



Union ø 50,8 mm




Drum cover for pumps with suction tube ø 50,8

Art. 10/55 Drum cover ø 600 mm for drums 180 - 220 Kg
(drums external ø 550 - 600 mm)

Art. 10/56 Drum cover ø 420 mm for drums 50 - 60 Kg
(drums external ø 370 - 420 mm)

Art. 10/57 Drum cover ø 385 mm for drums 30 - 50 Kg
(drums external ø 340 - 385 mm)



Follower plate for pumps S. 1200 - 1500 with suction tube ø 50,8

Art. 10/65 Follower plate ø 585 mm for drums 180 - 220 Kg
(drums internal ø 540 - 580 mm)

Art. 10/66 Follower plate ø 400 mm for drums 50 - 60 Kg
(drums internal ø 360 - 400 mm)

Art. 10/67 Follower plate ø 370 mm for drums 30 - 50 Kg
(drums internal ø 335 - 360 mm)



Union 2" F




Drum cover with threaded bushing 2" f

Art. 65160 Follower plate ø 600 mm for drums 180 - 220 kg
(drums external ø 550 - 600 mm)
suitable to fit pump bung adaptor

Art. 65142 Follower plate ø 420 mm for drums 50 - 60 kg
(drums external ø 370 - 420 mm)
suitable to fit pump bung adaptor

Art. 65138 Follower plate ø 385 mm for drums 30 - 50 kg
(drums external ø 340 - 385 mm)
suitable to fit pump bung adaptor





Air-operated pump elevator


1 column

The Pump elevators are available in single column (with or without basement) or twin column version. It is raised by compressed air, via the side mounted 3-way valve allowing to change the drum easily and quickly. A special version of the twin columns elevator is equipped with 2 rods which connected to a special follower plate (available on request) may push it downward making easier suction of the fluid and increasing the performance of the pump. They are available for 180-220 Kg drums.




Article		10/81	10/80
Column		1	1
Suitable for drums	kg	180 - 220	180 - 220
Working temperature	°C	+ 2 °C + 40 °C	+ 2 °C + 40 °C
Pressione max	bar	8	8
Usable pumps		S. 600 - 700 grease pump - 900 - 1200 - 1500 - 1800	
Noise level	dB	negligible (< 70)	
Pushing force upwards at:		* 4 bar 113 kg - 6 bar 170 kg - 8 bar 226 kg	4 bar 113 kg - 6 bar 170 kg - 8 bar 226 kg
Pushing force downwards at:		-	-
Packing	N° - m³	1 - 0,679	1 - 1,165
Gross weight	kg	75	97
Height max/min (A - B)	cm	271,5 - 171,5	275 - 175
Dimensions (C - D)	cm	14 - 25,5	86,6 - 63

Nota: *theoretical values, the coefficients of friction are not calculated.




STANDARD BRACKETS

All the elevators are equipped with 2 standard brackets (A - B) suitable for mounting all our industrial pumps.




BRACKETS ON REQUEST

KR1102: Special support suitable to mount pump with $\varnothing$ 30 mm suction tube.



2 column



10/82

2

180 - 220
+ 2 °C + 40 °C

8

S. 600 - 700 grease pump - 900 - 1200 - 1500 - 1800
negligible (< 70)

*

4 bar 226 kg - 6 bar 339 kg - 8 bar 452 kg

-

1 - 1,406

128

275 - 175

108,6 - 63

2 column + fluid press



10/85

2

180 - 220
+ 2 °C + 40 °C

8

S. 600 - 700 grease pump - 900 - 1200 - 1500 - 1800
negligible (< 70)

*

4 bar 509 Kg - 6 bar 763 Kg - 8 bar 1017 Kg

**

4 bar 432 Kg - 6 bar 648 Kg - 8 bar 864 Kg


1 - 1,840

187


280 - 180

108,6 - 63

Nota: **theoretical figures: friction has not been considered. Furthermore depression's force created by the pump during suction (+2100 Kg) must be added to the listed figures.



Fluid distribution system (for paints, lubricants, protective liquids, etc.) fed by pump mounted on drum in fixed station and delivery with spray gun.




Automated system for the delivery of preselected quantities of fluids (inks, paints, greases, etc.), fed by pump mounted on drum, with twin column ram





Air-operated twin column ram hoist

low pressure/high flow rate

Air-operated twin column ram hoist with industrial pump. It is raised and lowered by compressed air, via the side mounted 3-way valve. Essential when pumping high viscosity and heavy fluids since ram pushes down the follower plate helping pump working. It is suitable for 180- 220 Kg drums.



Article with follower plate with pump seals	NBR PU	10/1561P1N	10/1881P1N
Ratio		6:1	8:1
Flow rate		80 l/min	65 l/min
Pump	Art.	150D/61	180D/81
Suction tube		F 2" G	F 2" G
Twin column ram	Art.	10/85	10/85
Follower plate	Art.	11/60	11/60
Adaptors for follower plate	Art.	21/62	21/62
Pump connection hose	Art.	996.3015	996.3015
Follower plate connection hose	Art.	995.301	995.301
Suitable for drums	Kg	200	200
Packing	N° - m ³	1 - 1,80	1 - 1,80
Weight	Kg	263	266
Height max/min (A - B)	cm	280 - 180	280 - 180
Dimensions (C - D)	cm	108,6 - 63	108,6 - 63




medium pressure/medium flow rate

high pressure/low flow rate




10/09111P1N	10/12181P1N	10/12401P1N	10/09451P1N	10/12751P1N	10/15701P1N
11:1	18:1	40:1	45:1	75:1	70:1
30 l/min	23 l/min	10 kg/min	4,4 kg/min	4,4 kg/min	7 kg/min
90F/111	115F/181	118FSP/401	90FSP/451	115FSP/751	153FSP/701
ø 45	ø 45	ø 50,8	ø 45	ø 45	ø 50,8
10/85	10/85	10/85	10/85	10/85	10/85
11/60	11/60	11/60	11/60	11/60	11/60
21/64	21/64	21/65	21/64	21/64	21/65
996.3015	996.3015	996.3015	996.3015	996.3015	996.3015
995.301	995.301	995.301	995.301	995.301	995.301
200	200	200	200	200	200
1 - 1,80	1 - 1,80	1 - 1,80	1 - 1,80	1 - 1,80	1 - 1,80
225	226	231	228	230	238
280 - 180	280 - 180	280 - 180	280 - 180	280 - 180	280 - 180
108,6 - 63	108,6 - 63	108,6 - 63	108,6 - 63	108,6 - 63	108,6 - 63


Technical features




- 1 Ball cock for air bleeding during followerplate setting on new drum
- 2 Optional connection to pump outlet for pump starting and air bleeding when using a new drum
- 3 Air hose connection for follower plate lifting



References
to centre the drum




Conical follower plate
and bottom pumping group



Pump
feeding
air inlet

Support
with pump
positioning
clamps




- 1 Pressure regulator with manometer for pump air feeding
- 2 Pump air feeding ball cock
- 3A Follower plate and pump lifting position
- 3 Off position
- 3B Follower plate descent position
- 4 Pressure regulator with manometer for twin column ram air feeding
- 5 Ball cock to put air under the follower plate for pump lifting
- 6 Air inlet connection



Technical features

Follower plate ø 585 mm with double sealing **NBR** ring, to be used with air operated twin column ram for drums 180 - 220 Kg, for grease or high viscosity fluid.



The follower plate can be used with different kind of pumps thanks to special adaptors shown in the below list and available on request.

Article		Description
Art. 11/60		Follower plate ø 585 mm with double o-ring in NBR
Art. 21/61		Adaptor suitable for pumps with F 1" G suction tube
Art. 21/62		Adaptor suitable for pumps with F 2" G suction tube
Art. 21/64		Adaptor suitable for pumps with ø 45 mm suction tube
Art. 21/65		Adaptor suitable for pumps with ø 50,8 mm suction tube
Art. 21/63		Adaptor + Support (KR1102) suitable for pumps with ø 30 mm suction tube Grease pumps Series 600 - 700



Twin column ram: PERSONALIZED KIT

In order to satisfy any particular need it is possible to create one's personalized kit choosing pump, follower plate, adaptors and support. We suggest you to look at the information explained in the following pattern.

1 Twin column ram



Art. 10/85

2 Pumps

Choose the industrial pump with technical features (pressure ratio, flow rate, etc.) suitable for one's needs.



Article	150D/61	180D/81	90F/111	115F/181	90FSP/451	115FSP/751	118FSP/401	153FSP/701
Series	1500	1800	900	1200	900	1200	1200	1500
Ratio	6:1	8:1	11:1	18:1	45:1	75:1	40:1	70:1
Flow rate	80 l/min	65 l/min	30 l/min	23 l/min	4400 g/min	4400 g/min	10000 g/min	7000 g/min
Seals	polyurethane	polyurethane	polyurethane	polyurethane	polyurethane	polyurethane	polyurethane	polyurethane
Suct. tube	-	-	-	480 mm	500 mm	500 mm	600 mm	600 mm

3 Follower plate



Art. 11/60

4 Adaptors

Choose the adaptor to be mounted on follower plate 0AZ1160 which must fit pump's suction tube diameter.

Art.
21/61



Art.
21/62



Art.
21/63



Art.
21/64



Art.
21/65





Product customisation



RAASM offers its customers the opportunity of ordering the products included in its range in different colours **among the 6 made available**.

They can be requested by customers **without minimum quantity requirements, or extra costs, choosing from the 5 additional colours to the standard colour** (RAASM green).

Customisation is characterised exclusively by the colour and **does not include**: instruction handbooks, labels, brands, etc.

Delivery times can vary with respect to standard colour products (RAASM green).

The above-mentioned customisation does not include the brake bleeders, pit and floor drainers, air-operated pumps, trolleys, service columns and accessories.

Requests for different colours, in addition to those made available, or other types of customisation, must be appraised from time to time and will be tied to minimum quantities and additional costs

STANDARD COLOURS

Products for which a customised colour is not specified, are understood to be supplied with the standard colour as per the catalogue.

STANDARD



RAL 7035



To order an article with a colour **different from standard**, among the six made available, it is necessary to add the following to the article number

the suffix: /**GREEN** for green
 /**C1** for neutral
 /**C2** for yellow
 /**C4** for red
 /**C5** for blue

RAASM
Ral 7035
Ral 1004
Ral 3020
Ral 5002

OPPORTUNITY

RAASM offers its customers the opportunity of ordering articles in 4 different colours besides the standard one.

STANDARD



RAL 7035



RAL 1004



RAL 3020



RAL 5002





APPARECCHIO SPURGOFRENI E FRIZIONI A 2 CAMERE
TWO-CHAMBER BRAKE-CLUTCH BLEEDING DEVICE

The seal kit (e.g. KR1050) includes all the seals used in the article.
This kit is not mentioned or shown in the exploded view.

CODICE <i>CODE</i>	DESCRIZIONE <i>DESCRIPTION</i>	Q.TÀ <i>QTY</i>
KR1006	MEMBRANA CON SET DI VITI MEMBRANE WITH SET OF SCREWS	1
KR1050	KIT GUARNIZIONI COMPLETO COMPLETE GASKETS KIT	1
S105	MANOMETRO ø 50 mm GAUGE ø 50 mm.	1

Clearly, a KS cannot be shown in the exploded view



General sales terms



Reserved exclusively for the foreign market

Art. 1 : DELIVERY OF GOODS

The goods are only forwarded ex factory, by means of the carrier specified by the customer and, in any case, travel at the customer's risk and hazard.

Art. 2 : ORDERS

Orders for amounts of less than Eur 1500,00 (one thousand five hundred Euro) are not accepted. Whenever the execution of orders for amounts of less than Eur 1500,00 becomes essential, Eur 155,00 shall be charged for partial refund of our administrative costs.

Art. 3 : ACCESSORIES

All the accessories given in the price list (plugs, oil bar taps, oil guns, grease guns, probes, etc.) are supplied exclusively for fitting to or combining with the articles we produce.

Art. 4 : COMPLAINTS

Any complaint for shortages, errors or defects, noticed by a first exam of the goods, must be sent in writing to our Head office within 8 days of receiving the goods. Any defect of the product that is possible to notice only by using must be sent in writing to our Head office within 8 days from its discovering.

Art. 5 : DELIVERY TERMS

The delivery dates are always approximate. Possible delays in delivery do not give the customer any right to cancel the order or to claim ensuing damages. Urgent cases are subject acceptance by the Firm. The Firm has the right not to execute the order and to execute it fully or partially, without any claims or claims for damage being made towards the Firm.

Art. 6 : PACKS AND PACKAGING

Packaging costs are included in the price, except for special packing, which shall be charged at cost.

Art. 7 : PRICES

The current Price list cancels the previous price list. In the event of changes to our price list and/or individual articles, the goods shall be forwarded at the price in force on the day of delivery. The price-list and/or the prices of individual articles can be changed even without notice, according to the changes in market conditions or technical innovations/modifications made to the product. The prices are understood to be ex our Factory.

Art. 8 : PAYMENTS

Payments must be made exclusively to RAASM S.p.a. at the agreed conditions. Deductions or rounding off shall in no case be accepted. In the event of late payment with respect to the agreed conditions, the firm reserves the right to charge interest at the current rate and additional costs, starting from the day after that agreed on for payment. Discounts subject to payment already credited shall be re-charged.

Art. 9 : WARRANTY

RAASM S.p.a. provides every product with its manual, giving installation and maintenance instructions and indications about the controls that should be made. The warranty shall cover any defect due to material or manufacture procedure within validity and prescription terms fixed by the law, and, in this case, the only charge shall be of Eur 10,00. The guarantee will lapse in case of incorrect installation, operation or maintenance of the products. The articles must be returned free to our Factory for checking and acceptance. All technical information, drawings, illustrations etc. are supplied for guidance only. The company reserves the right to amend any design or specification without prior notice.

Art. 10 : RESPONSABILITY

RAASM S.p.a. is relieved of all responsibility and obligations for any accident to persons and things that can occur due to or during use of the equipment, or caused by and in connection with the equipment.

Art. 11 : COMPETENT LAW COURT

These conditions of sale shall be governed by and construed with Italian law, and any disputes shall be settled by the law-court of Bassano del Grappa (VI), Italy.



How to reach RAASM



by plane

With regular flights, the nearest airports are those Venice Tesserà, Verona Villafranca and Treviso.

- **FROM VENICE TESSERA**
Bassano can be reached by train:
Venice - Padova - Cittadella
Bassano del Grappa.
- **FROM VERONA VILAFRANCA**
Bassano can be reached by train:
Dossobuono - Verona - Vicenza
Cittadella - Bassano del Grappa.
- **FROM TREVISO**
Bassano can be reached by train:
Treviso - Castelfranco - Cassola.



by train

RAASM can be reached also by train, getting off at Bassano del Grappa station.

- **BOLZANO:** Bolzano - Verona
Vicenza - Cittadella - Bassano del Grappa.
- **MILAN:** Milan - Verona - Vicenza
Cittadella - Bassano del Grappa.
- **BOLOGNA:** Bologna - Padova
Cittadella - Bassano del Grappa.
- **TRIESTE - UDINE:** Trieste - Udine
Codroipo - Treviso - Castelfranco
Bassano del Grappa.

**RAASM is approx. 3 km
from the Train Station.**



by own transport

Arriving by car from the north or west, with Verona as the reference point take the A4 Motorway towards Vicenza - Valdastico. At the Dueville exit head for Bassano del Grappa.

If arriving from the south, with Padova as the reference point take State Road 47 towards Cittadella Bassano del Grappa.



Notes



Lined area for writing notes.



RAASNI

Index Articles

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

10/09	204-210	323
10/10	107-210	225-322
10/11	107-210	225-322
10/12	210	225-322
10/13	210	225-322
10/14	107-210	323
10/15	107-210	224-323
10/17	210	323
10/18	210	225-323
10/20	112	234-325
10/21	112	
10/22	112	234-325
10/23	112	234-325
10/24	112	234-325
10/25	112	
10/50	126-211	260-324
10/51	126-211	260-324
10/52	126-211	260-324
10/55	211	324
10/56	211	324
10/57	211	324
10/60	126-211	258-325
10/61	126-211	258-325
10/62	126-211	258-325
10/65	211	325
10/66	211	325
10/67	211	325
10/80	212	327
10/81	212	327
10/82	213	261-328
10/85	213	329
10/09111P1N	215	
10/09451P1N	215	
10/12181P1N	215	
10/12401P1N	215	
10/12751P1N	215	
10/1561P1N	214	
10/15701P1N	215	
10/1881P1N	214	
10105	32	48
10205	32	48
10207	32	48
10705	32	49
10801	35	51
10802	35	51
10805	32	49
10807	32	49
11/60	216	329
11000/A	34	50
11000/B	34	50
11000/C	34	50
11000/D	34	50
11000/E	34	50
11000/F	34	50
11000/G	34	50
11000/H	34	50
11000/I	34	50
11000/K	34	50
11000/L	34	50
11000/M	34	50
11000/P	34	50

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

11000/R	34	50
11000/T	34	50
11000/U	34	50
11000/W	34	50
11000/X	34	50
11000/Y	34	50
11000/Z	34	50
11001	34	50
11002	34	50
11003	35	51
11003/1	35	51
11003/2	35	51
11003/3	35	51
11003/4	35	51
11003/5	35	51
11003/6	35	51
11003/7	35	51
11003/8	35	51
11003/9	35	51
11004	35	51
115D/121	207	307
115D/181	207	308
115D/31	200	315
115D/91	207	306
115DV/31	200	315
115F/121	199	307
115F/181	199	308
115F/401	204	312
115F/751	203	311
115F/91	199	306
115FSP/751	203	
116F/121	199	307
116F/181	199	308
116F/401	205	312
116F/751	119-203	311
117F/401	205	312
117F/751	119-203	311
118F/401	204	
118FSP/401	204	
120D/91	209	321
150D/41	201	316
150D/61	201	317
150DV/61	201	317
150F/701	205	
151F/701	205	313
152F/701	205	313
153F/701	205	
153FSP/701	205	
180D/51	201	318
180D/81	201	319
180DV/81	201	319
21/61	216	
21/62	216	
21/63	216	
21/64	216	
21/65	216	
22017	36	54
22024	36	54
23024	36	55
23025	36	55
24891	36-60-62	55-116

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

26090	70	160
26091	70	160
26093	70	
26094	70	160
2B3/16117NH22	79	
2B3/16117TT22	79	
2B8/16117NH22	79	
2B8/16117TT22	79	
30050	61	115
30200	60	115
31200	60	114
31201	60	114
32016	61	116
32024	61	116
32065	61	116
32713	60-62	
33/2011NHHV2	77	
33/2611NHHV2	78	
33/3011NHHV2	78	
33016	62	120
33024	62	120
33060	71	163
33061	71	163
33070	71	163
33071	71	163
33072	71	163
33073	71	163
33080	71	162
33081	71	162
33082	71	162
33083	71	162
33094	71	163
33096	71	163
33106	108	
33107	108	
33108	108	
33109	108	
33111	108	
33112	108	226
33113	108	226
33114	108-182	403
33115	107-210	224
33116	108-182	226-403
33117	108-182	226-403
33118	108	226
33119	108-182	226-403
33120	98	210
33121	99	212
33122	106	223
33125	50-90	186
33126	108	186-226
33127	108	186-226
33128	182	403
33129	182	403
33130	182	403
33134	50-90	
33140	100	216
33146	102	
33147	102	
33148	102	
33150	102-105	218-222

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

33151	102	218
33152	102	218
33153	102	218-326
33160	71	165
33170	71	164
33172	71	164
33173	71	164
33194	71	165
33196	71	165
33270	182	403
33271	182	403
33272	182	403
33273	182	403
33274	182	403
33275	108	226
33276	108	226
33277	108	
33300	76	159
33360	76-208	158
33396	76-208	158
33424	111	
33425	111	
33426	110-111	228
33427	111	227
33428	111	
33434	107-111 210	224
33440	76-103 208	159-223
33441	103	
33500	77	156
33501	92	201
33505	77	
33550	50-90	186
33581	111	227
33582	111	227
33583	111	
33585	111	
33590	107	225
33591	107	225
35060	72	161
35061	72	161
35063	72	
35076	73	
35094	73	161
35160	73	166
35161	73	166
35163	73	167
35173	73	167
35176	73	167
35194	73	167
35196	73	167
35198	83	
35199	83	
35200	82	172
35201	82	
35210	82	173
35219	83	
35220	83	174
35249	85	

Index Articles

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

35250	85	175
35254	85	
35259	85	
35260	85	
35264	85	
35265	84	176
35270	84	177
35275	86	180
35276	87	181
35280	87	182
35281	87	183
35284	91	
35285	91	185
35290	91	178
35293	91	178
35296	91	178
35330	88	190
35415	83	
35425	83	
36060	74	168
36061	74	168
36063	74	169
36073	75	169
36076	75	169
36094	75	169
36096	75	169
36330	88	190
36340	89	191
36350	89	191
36602	89	194
36603	89	
36604	89	
36610	89	196
36620	89	196
37095	83	
37099	83	
37100	82	172
37150	82	173
37200	83	174
37499	85	
37500	85	175
37504	85	
37650	84	176
37670	84	177
37675	86	180
37676	87	181
37679	87	183
37680	87	182
37683	93	200
37685	91	185
37686	92	198
37687	92	198
37688	92	198
37689	92	198
37690	92	198
37691	92	198
37692	93	202
37693	93	202
37695	92	201
37697	93	200
37698	93	200

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

37699	93	200
37701	106	204
37703	106	206
37704	106	
37728	98	
37729	98	
37730	98	
37740	99-104	214-220
37741	99	214
37742	99	214
37743	99	214
37750	100-104	216-221
37751	100	216
37752	100	216
37758	99	
37759	99	
37760	99	
37762	103	
37764	103	
37775	101-105	
37776	101	
37777	101	
37778	101	
37780	94	
37781	94	
37785	94-103	
37786	99	
37794	100	
37795	100	
37796	100	
37797	101	
37798	101	
37799	101	
37801	129	264
37810	129	264
37811	129	264
37812	110-129	229-264
37814	129	264
37815	129	264
37816	129	264
37817	110-129	229-264
37830	93	
38010	104	220
38011	104	220
38012	104	220
38013	104	220
38014	104	
38015	104	220
38016	104	220
38017	104	220
38018	104	220
38020	99-104	212-220
38021	99	212
38022	99	212
38023	98-104	210-220
38024	98	210
38025	98	210
38026	110	228
38027	111	227
38028	110	228
38029	104	221

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

38030	104	221
38031	104	221
38032	104	221
38034	104	221
38035	104	221
38037	105	222
38038	105	222
38039	105	222
38040	105	222
38042	107	224
38043	107	224
38044	107	
38046	107	224
38047	107	224
38051	107	224
38052	107	224
38055	111	227
38056	111	
38057	111	
38062	104	220
38063	104	221
38065	105	222
38066	105	
38069	108	
38070	108	226
38071	108-182	226-403
38072	108-182	226-403
38073	108	226
38075	108	226
38076	108	226
38077	108	226
38078	108	226
38079	108	
38080	110	
38081	110	
38082	110	
38083	110	
38084	113	232
38085	113	232
38086	113	232
38087	113	232
38088	113	232
38089	113	233
38090	112	234
38091	110	226
38092	112	234
38093	113	233
38095	110	229
38096	110	229
38097	109	229
38098	109	229
38099	110	229
38100	110	229
38102	93	202
38105	93	202
38120	182	403
38121	182	403
38130	109	
38131	109	
38132	109	
38210	110	228

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

38211	110	228
39304	139	277
39307	139	277
39314	139	273
39317	139	273
39320	135	99
39321	135	279
39322	135	279
39323	134	
39324	137	275
39328	137	275
39334	134	
39335	134	
39336	136	
39338	136	
39340	136	
39351	138	281
39352	138	281
39405	139	
39406	139	
39407	139	
39421	135	
39422	135	
39901	138	282
39902	138	282
42000	51	66
42004	51	
42050	51	66
42055	52	
42056	52	
42059	52	64
42060	52	64
42061	52	64
42062	52	64
42065	46	68
42066	46	72
42069	53	65
42070	53	65
42072	53	65
42073	53	65
42075	53	
42076	53	
42090	46	68
42091	46	72
42115	46	68
42116	46	72
43016	45	79
43024	45	79
43060	47	80
43065	47	82
43090	47	80
43091	47	82
43114	47	80
43115	47	82
44060	47	84
44065	47	86
44090	47	84
44091	47	86
44115	47	84
44116	47	86
45100	55	97

Index Articles

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

45110	55	97
45111	55	97
45150	54	96
45180	54	96
45200	56	104
45250	56	104
45280	56	104
45290	56	104
45291	56	104
45292	56	104
45300	55	98
45310	55	99
45311	55	99
45498	44	100
45499	44	100
45500	44	100
45501	44	100
45502	44	100
45504	44	100
45505	44	100
45506	44	100
45515	44	100
45516	44	100
45517	44	100
45518	44	100
45526	44	100
45527	44	100
45528	44	100
45538	44	100
45539	44	100
45540	44	100-106
45550	44	101-109
45551	44	101-109
45560	44	100
45570	44	101
46064	48	90
46065	48	90
46114	49	91
46115	49	91
46116	49	92
46215	49	94
52010	39	60
52013	38	58
52015	38	59
52020	38	58
52024	38	59
53016	38	59
53024	38	59
60280	64	124
60310	64	124
60311	64	124
60410	65	126
60411	65	126
60450	65-127	126-262
60451	65-127	126-262
62041	116	238
62048	116	238
62074	116	238
62095	116	238
63041	117	239
63048	117	239

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

63074	117	239
63095	117	239
64000	121	242
64000/65	121	242
64000/75	121	242
64001	121	
64001/65	121	
64001/75	121	
64021	125	251
64025	125	250
64031	125	251
64032	124	249
64033	124	249
64033/40	125	249
64034	124	248
64035	124	248
64036	125	248
64037	123	246
64038	123	246
64039	123	247
64039/65	123	247
64040	123	244
64041	123	244
64042	123	245
64042/65	123	245
64063	122	244
64064	122	244
64070	120	243
64070/65	120	243
64070/75	120	243
64071	121	
64071/65	121	
64071/75	121	
64145	122	256
64146	122	256
64195	120	257
64196	120	257
64197	120	257
64200	117	254
64210	117	255
65138	108-211	229-324
65142	108-211	229-324
65160	108-211	229-324
65280	126	260
65309	127	260
65310	126	260
65311	127	260
65312	127	
65350	126	260
65385	126	260
65420	126	260
65600	126	260
66265	126	258
66310	126	258
66340	126	258
66370	126	258
66400	126	258
66590	126	258
66599	127	263
66661	127	262
66663	127	262

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

66739	127	263
66740	127	263
66741	127	263
66742	127	263
66743	127	263
66855	128	266
66856	128	267
66857	128	267
66860	128	266
66880	128	267
66881	128	267
66882	128	267
66888	128	266
66889	128	266
66891	127	262
66892	127	262
66893	127-182	262-403
66895	127	262
66896	127	262
66897	127	262
68012	63	122
68113	63	122
68213	63	123
70365	37	56
70809	37	56
735000	177	
735111	177	
735131.60141	177	
735131.60152	177	
735131.60252	177	
735131.60261	177	
735141.60152	177	
735141.60252	177	
7522001.100	176	
7522001.150	176	
7522001.200	176	
7522001.250	176	
7522001.300	176	
7522001.400	176	
7522001.450	176	
7532001.100	176	
7532001.150	176	
7532001.200	176	
7532001.250	176	
7532001.300	176	
7532001.400	176	
7532001.450	176	
7552001.100	176	
7552001.150	176	
7552001.200	176	
7552001.250	176	
7552001.300	176	
7552001.400	176	
7552001.450	176	
7562001.100	176	
7562001.150	176	
7562001.200	176	
7562001.250	176	
7562001.300	176	
7562001.400	176	
7562001.450	176	

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

80035	130	270
80040	130	270
80050	130	270
80200	131	271
80201	131	271
80210	131	
80215	131	
8288.100	149	
8288.102	149	
8288.103	149	
8288.104	149	
8288.105	149	
8290.100	154	
8290.101	154	
8290.104	154	
8292.100	155	
8292.101	155	
8292.104	155	
8328.100	149	
8328.102	149	
8328.103	149	
8328.104	149	
8328.105	149	
8330.100	154	
8330.101	154	
8330.200	156	
8330.201	156	
8330.300	158	
8330.301	158	
8330.350	160	
8330.400	164	
8330.402	164	
8330.500	166	
8330.501	166	
8330.800	173	
8330.801	173	
8330.802	173	
8332.100	155	
8332.101	155	
8332.201	157	
8332.300	159	
8332.301	159	
8332.350	161	
8332.400	157	
8333.202	157	
8333.301	159	
8378.100	149	
8378.102	149	
8378.103	149	
8378.104	149	
8378.105	149	
8380.100	154	342
8380.102	154	342
8380.200	156	350
8380.202	156	350
8380.300	158	356
8380.302	158	356
8380.350	160	360
8380.352	160	360
8380.400	164	372
8380.401	164	372

Index Articles

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

8380.402	164	372
8380.500	166	380
8380.501	166	380
8380.502	166	380
8382.100	155	343
8382.102	155	343
8382.200	157-165	351-373
8382.202	157	351
8382.300	159	357
8382.302	159	357
8382.350	161	361
8382.352	161	361
8382.500	167	381
8383.201	157	351
8383.301	159	357
8390.100	154	340
8390.102	154	340
8390.200	156	348
8390.202	156	348
8390.300	158	354
8390.302	158	354
8390.350	160	358
8390.352	160	358
8390.400	164	370
8390.401	164	370
8390.402	164	370
8390.500	166	378
8390.501	166	378
8390.502	166	378
8390.800	173	
8390.801	173	
8390.802	173	
8392.100	155	341
8392.102	155	341
8392.200	157-165	349-371
8392.202	157	349
8392.300	159	355
8392.302	159	355
8392.350	161	359
8392.352	161	359
8392.500	167	379
8393.201	157	349
8393.301	159	355
8420.100	154	342
8420.101	154	342
8420.102	154	342
8420.103	154	342
8420.104	154	342
8420.200	156	350
8420.201	156	350
8420.202	156	350
8420.300	158	356
8420.301	158	356
8420.302	158	356
8420.350	160	360
8420.352	160	360
8420.400	164	372
8420.401	164	372
8420.402	164	372
8420.500	166	380
8420.501	166	380

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

8420.502	166	380
8420.505	166	380
8420.506	166	380
8422.100	155	343
8422.101	155	343
8422.102	155	343
8422.103	155	343
8422.104	155	343
8422.201	157	351
8422.202	157	351
8422.301	159	357
8422.302	159	357
8422.352	161	361
8422.500	167	381
8423.202	157	351
8423.302	159	357
8423.352	161	361
8424.200	157-162 165	351-363 365-373
8424.300	159-162	357-367
8424.350	161-162	361-369
8430.100	149-154	340
8430.1000	171	
8430.101	154	340
8430.102	154	340
8430.103	154	340
8430.104	154	340
8430.200	156	348
8430.201	156	348
8430.202	156	348
8430.300	158	354
8430.3000	171	
8430.301	158	354
8430.302	158	354
8430.350	160	358
8430.352	160	358
8430.400	164	370
8430.4000	171	
8430.401	164	370
8430.402	164	370
8430.500	166	378
8430.5000	171	
8430.501	166	378
8430.502	166	378
8430.505	166	378
8430.506	166	378
8430.700	172	390
8430.701	172	390
8430.702	172	390
8430.800	173	392
8430.802	173	392
8430.804	173	392
843001	180	394
843002	180	394
843005	181	395
843006	181	395
8432.100	155	341
8432.101	155	341
8432.102	155	341
8432.103	155	341
8432.104	155	341

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

8432.201	157	349
8432.202	157	349
8432.301	159	355
8432.302	159	355
8432.352	161	359
8432.500	167	379
8433.202	157	349
8433.302	159	355
8433.352	161	359
8434.200	157-162 165	349-362 364-371
8434.300	159-162	355-366
8434.350	161-162	359-368
8436.200	170	
8436.204	170	
8436.205	170	
8438.101	149	
8438.102	149	
8440.100	150	344
8440.101	150	344
8440.102	150	344
8440.103	150	344
8440.104	150	344
8440.400	150	374
8440.401	150	374
8440.402	150	374
8440.500	150	382
8440.501	150	382
8440.502	150	382
8440.505	150	382
8440.506	150	382
8450.100	150	344
8450.101	150	344
8450.102	150	344
8450.103	150	344
8450.104	150	344
8450.400	150	374
8450.401	150	374
8450.402	150	374
8450.500	150	382
8450.501	150	382
8450.502	150	382
8450.505	150	382
8450.506	150	382
845001	180	394
845005	181	395
8520.100	154	342
8520.101	154	342
8520.102	154	342
8520.200	156	350
8520.201	156	350
8520.300	158	356
8520.301	158	356
8520.302	158	356
8520.350	160	360
8520.352	160	360
8520.400	164	372
8520.401	164	372
8520.402	164	372
8520.500	166	380
8520.501	166	380

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

8520.502	166	380
8522.100	155	343
8522.101	155	343
8522.102	155	343
8522.201	157	351
8522.301	159	357
8522.302	159	357
8522.352	161	361
8522.500	167	381
8523.202	157	351
8523.302	159	357
8523.352	161	361
8524.200	157-162 165	351-363 365-373
8524.300	159-162	357-367
8524.350	161-162	361-369
8530.100	154	340-386
8530.1000	171	
8530.101	154	340
8530.102	154	340
8530.200	156	348
8530.201	156	348
8530.300	158	354
8530.3000	171	
8530.301	158	354
8530.302	158	354
8530.350	160	358
8530.352	160	358
8530.400	164	370
8530.4000	171	
8530.401	164	370
8530.402	164	370
8530.500	166	378
8530.5000	171	
8530.501	166	378
8530.502	166	378
8530.600	168	
8530.603	168	
8530.604	168	
8530.700	172	390
8530.701	172	390
8530.702	172	390
8530.703	172	390
8530.704	172	390
8530.705	172	390
8530.800	173	392
8530.802	173	392
8530.804	173	392
853001	180	394
853002	180	394
853005	181	395
853006	181	395
8532.100	155	341-387
8532.101	155	341
8532.102	155	341
8532.201	157	349
8532.301	159	355
8532.302	159	355
8532.352	161	359
8532.500	167	379
8533.202	157	349

Index Articles

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

8533.302	159	355
8533.352	161	359
8534.200	157-162 165	349-362 364-371
8534.300	159-162	355-366
8534.350	161-162	359-368
8537.200	170	
8537.204	170	
8537.205	170	
8540.100	154-168	340-386
8540.101	154	340
8540.102	154	340
8540.103	154	340
8540.105	154	340
8540.106	154	340
8540.200	156	348
8540.202	156	348
8540.203	156	348
8540.300	158	354
8540.301	158	354
8540.350	160	358
8540.400	164	370
8540.401	164	370
8540.402	164	370
8540.403	164	370
8540.405	164	370
8540.406	164	370
8540.500	166	378
8540.5000	171	
8540.501	166	378
8540.601	168	386
8540.602	168	386
8540.603	168	386
8540.700	172	390
8540.701	172	390
8540.702	172	390
8540.704	172	390
8540.705	172	390
8540.707	172	390
8540.709	172	390
8540.800	173	392
8540.802	173	392
854001	180	394
854002	180	394
854005	181	395
854006	181	395
8542.100	155-169	341-387
8542.101	155	341
8542.102	155	341
8542.103	155	341
8542.105	155	341
8542.106	155	341
8542.202	157	349
8542.203	157	349
8542.301	159	355
8542.601	169	387
8542.602	169	387
8542.603	169	387
8543.202	157	349
8543.301	159	355

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

8544.200	157-162 165	349-362 364-371
8544.205	162	349-362 364-371
8544.300	159-162	355-366
8544.350	161-162	359-368
8545.200	163	
8550.100	154	342
8550.101	154	342
8550.102	154	342
8550.103	154	342
8550.105	154	342
8550.106	154	342
8550.200	156	350
8550.202	156	350
8550.203	156	350
8550.300	158	356
8550.301	158	356
8550.350	160	360
8550.400	164	372
8550.401	164	372
8550.402	164	372
8550.403	164	372
8550.405	164	372
8550.406	164	372
8550.500	166	380
8550.501	166	380
8552.100	155	343
8552.101	155	343
8552.102	155	343
8552.103	155	343
8552.105	155	343
8552.106	155	343
8552.202	157	351
8552.203	157	351
8552.301	159	357
8553.202	157	351
8553.301	159	357
8554.200	157-162 165	351-363 365-373
8554.205	162	351-363 365-373
8554.300	159-162	357-367
8554.350	161-162	361-369
8560.100	154-168	340-386
8560.101	154	340
8560.103	154	340
8560.104	154	340
8560.105	154	340
8560.106	154	340
8560.200	156	348
8560.205	156	348
8560.300	158	354
8560.301	158	354
8560.302	158	354
8560.350	160	358
8560.400	164	370
8560.405	164	370
8560.603	168	386
8560.604	168	386
8560.605	168	386

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

856001	180	394
856002	180	394
8562.100	155-169	341-387
8562.101	155	341
8562.103	155	341
8562.104	155	341
8562.105	155	341
8562.106	155	341
8562.205	157	349
8562.301	159	355
8562.302	159	355
8562.603	169	387
8562.604	169	387
8562.605	169	387
8564.200	157-162	349-362 364-371
8564.206	162	349-362 364-371
8564.300	159-162	355-366
8564.350	161-162	359-368
8617.100	174	346
8617.200	174	352
8617.400	174	376
8617.500	174	384
8617.600	174	388
8618.100	175	347-389
8618.200	175	353
8618.400	175	377
8618.500	175	385
8637.100	174	346
8637.200	174	352
8637.400	174	376
8637.500	174	384
8637.600	174	388
8638.100	175	347-389
8638.200	175	353
8638.400	175	377
8638.500	175	385
88630	86-108 134-137 147	203-265
88650	147	397
88651	147	397
89001	39-148	60-338
89010	148	338
89011	148	338
89109	148	339
89110	148	339
90C/111	81-198	304
90C/51	80-196	170-301
90C/71	81-197	171-302
90D/111	207	305
90D/21	200	314
90D/51	206	301
90D/71	206	303
90DV/21	200	314
90F/111	199	305
90F/451	118-202	240-309
90F/51	196	170-301
90F/71	197	171-303
90FSP/451	202	

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

91C/111	81-198	304
91C/701	119-203	241-310
91C/71	81-197	171-302
91F/111	199	305
91F/451	118-202	240-309
91F/71	197	171-303
92C/111	81-198	305
92C/701	203	
92C/71	81-197	303
92F/451	202	309
93C/71	197	
9430.100	152	
9430.101	152	
9430.102	152	
9430.103	152	
9430.104	152	
9430.200	152	
9430.201	152	
9430.202	152	
9430.300	152	
9430.301	152	
9430.302	152	
9430.400	152	
9430.401	152	
9430.402	152	
9430.500	152	
9430.501	152	
9430.502	152	
9430.505	152	
9430.506	152	
9431.202	152	
9431.302	152	
9432.100	153	
9432.101	153	
9432.102	153	
9432.103	153	
9432.104	153	
9432.201	153	
9432.202	153	
9432.301	153	
9432.302	153	
9432.401	153	
9432.402	153	
9432.500	153	
9432.501	153	
9432.502	153	
9432.505	153	
9432.506	153	
9433.202	153	
9433.302	153	
9434.200	153	
9434.300	153	
9450.100	151	
9450.101	151	
9450.102	151	
9450.103	151	
9450.104	151	
9450.400	151	
9450.401	151	
9450.402	151	
9450.500	151	

Index Articles

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

9450.501	151	
9450.502	151	
9450.505	151	
9450.506	151	
94D/61	209	
95D/61	209	320
967.206	183	
967.210	186	
967.215	186	
971.010	184	
971.011	184	405
971.015	184	
971.102	183	404
971.111	184	405
971.115	184	
971.118	184	
971.120	184	
972.102	183	
972.113	184	
972.115	184	
972.120	184	
973.913	186	409
973.917	186	409
973.920	186	409
973.925	186	409
973.930	186	409
974.1008	186	
974.1015	186	409
974.1020	186	409
974.1028	186	409
974.912	186	409
974.915	186	409
974.920	186	409
974.925	186	409
974.930	186	409
975.1002	183	404
975.1010	186	
975.1015	186	
975.1018	186	409

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

975.1027	186	409
975.1030	186	409
975.902	183	404
975.915	186	409
975.920	186	409
975.927	186	409
976.102	183	
976.108	184	
976.110	184	
976.111	184	
976.112	184	
976.114	184	
976.115	184	
993.201	110-127 183	404
993.202	110-127 183	404
993.215	184	
993.504	127-183	404
993.511	185	408
993.512	127-185	408
993.516	185	408
993.518	127-185	408
994.512	185	406
994.517	185	406
994.612	185	406
994.717	185	406
995.206	183	404
995.210	184	
995.211	184	405
995.212	184	405
995.217	184	405
995.218	184	405
995.312	185	408
995.313	184	405
995.317	185	408
995.318	184	405
995.412	184	405
995.506	183	404

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

995.512	185	406
995.518	185	406
995.520	185	406
995.525	185	406
995.530	185	406
995.540	185	406
995.550	185	406
995.606	183	404
995.618	185	406
995.625	185	406
995.630	185	406
995.701	127-183	404
995.702	127-183	404
995.706	183	404
995.710	127-185	408
995.715	127-185	408
995.720	185	408
995.725	185	408
995.730	185	408
995.806	183	404
995.818	185	406
995.825	185	406
995.906	183	404
995.918	185	406
995.925	185	406
996.210	184	405
996.215	184	405
996.220	184	405
996.225	184	405
996.230	184	405
996.301	110-183	404
996.302	110-183	404
996.304	110-183	404
996.306	183	404
996.310	185	408
996.311	184	405
996.315	185	408
996.316	184	405
996.320	185	408

Article	219 Catalogue page No.	217 Catalogue page No.
---------	------------------------------	------------------------------

996.321	184	405
996.325	185	408
996.330	185	408
996.406	183	404
996.415	184	405
996.425	184	405
997.215	184	405
997.220	184	405
997.230	184	405
997.240	184	405
997.320	184	405
997.420	184	405
997.505	110-183	404
997.515	185	408
997.520	185	408
997.812	186	
997.815	186	409
997.820	186	409
997.840	186	409
998.215	184	405
998.220	184	405
998.230	184	405
998.315	184	405
998.330	184	405
998.406	183	404
998.501	110-183	404
998.502	110-183	404
998.506	183	404
998.515	185	408
998.530	185	408
998.808	186	
998.815	186	409
998.820	186	409
998.830	186	409

The manufacturer declines all responsibility for possible imprecisions contained in this catalogue, due to misprints or clerical errors.

Moreover, the manufacturer reserves the right to bring about any technical-functional and design change or improvement, without any previous notice and with the utmost operational freedom.

FLUIDS AND LUBRICATION EQUIPMENT

RAASM



THREE WORDS TO DESCRIBE RAASM

■ Technology

The starting point for the entire production cycle is the research and development of cutting-edge new solutions which lead to the development of **high quality products, fully produced in Italy.**



■ Quality

The quality of our product manufacturing has always been our absolute priority. To reach this goal rigorous testing accompanies every phase of the manufacturing process.



■ Functionality

RAASM offers the most complete range of lubrication products suited to many sectors. Our aim is to always be available to provide solutions to our customers.



All rights reserved to Raasm S.p.A.

Authorized distributor

WRCA219-GB



RAASM S.p.A.
36022 S. ZENO DI CASSOLA (VI)
Via Marangoni, 33 - ITALY

Export department
Tel. +39 0424 571 130 - Fax 0424 571 135
Technical department
Tel. +39 0424 571 150 - Fax 0424 571 155

info@raasm.com
www.raasm.com